

**DEFENSE SUPPLY CENTER PHILADELPHIA
CRITICAL ITEM PROCUREMENT REQUIREMENTS DOCUMENT**

DOCUMENT NUMBER

MS27576-4-17


TITLE

**BOLT, SELF-RETAINING, IMPEDANCE TYPE,
95 KSI FSU, HEX HEAD, 450°F**

**APPLICABLE TO: NSN: 5306-00-121-8848
PART NUMBER: MS27576-4-17
COMMERCIAL AND GOVERNMENT ENTITY: 14153**

CRITICAL SAFETY ITEM

PREPARED BY:



DATE:

7/27/06

APPROVED BY:

DATE:

REVISIONS

| SYM | DESCRIPTION | DATE | APPROVED |
|------------|--------------------------------------|--------------|-----------------|
| A | Added Space-Lok as qualified source. | 21 July 2004 | |
| B | Revised Certification Requirements | 6 July 2006 | |

CRITICAL ITEM PROCURMENT REQUIREMENTS DOCUMENT (CIPRD)
MS27576-4-17

**TITLE: BOLT, SELF-RETAINING, IMPEDANCE TYPE, 95 KSI FSU, HEX HEAD,
450°F**

**NSN - 5306-00-121-8848
PART NUMBER – MS27576-4-17**

1. SCOPE:

This Critical Item Procurement Requirements Document (CIPRD) covers the technical requirements of the item specified in the solicitation or contract. The documents listed in paragraph 2, with current revisions are part of this package to the extent specified herein. All Military, Federal and commercial/industry specifications and standards appearing hereon or on referenced documents, are part of this procurement package to the extent specified and shall be the issue in effect on the date of the solicitation unless otherwise specified. Bolts furnished in accordance with this Critical Item Procurement Requirements Document (CIPRD) shall be products authorized by the qualifying activity (see paragraph 7(1)).

2. REFERENCE DOCUMENTS:

**NASM 27576 – BOLT, SELF-RETAINING, IMPEDANCE TYPE, 95 KSI FSU, HEX HEAD,
450°F.**

NASM 83050 – BOLT, SELF-RETAINING, IMPEDANCE TYPE

3. REQUIREMENTS:

- (1) This CIPRD takes precedence over all documents referenced herein.**
- (2) All dimensional, performance and verification requirements of NASM 27576 and NASM 83050 apply except as noted herein.**
- (3) External threads will be inspected for dimensional conformance in accordance with System 23 of FED-STD-H28/20.**
- (4) All parts will be subject to 100% non-destructive testing in accordance with ASTM E1444. Any part found to have an indication of cracks shall be rejected.**
- (5) For the purpose of determining conformance, the observed or calculated plating thickness shall be rounded to the nearest 0.0001 inch in accordance with ASTM E-29.**
- (6) Only the manufacturer's identification logo listed in MIL-HDBK-57 shall be applied directly to the surface of the part. Do not apply on bearing surfaces. The logo shall be listed with the Defense Supply Center Philadelphia, DSCP-NAS.**
- (7) The thread of each bolt will be protected with a sleeve.**
- (8) All specifications, standards, quality assurance provisions and/or drawings referenced in this CIPRD shall be of the latest revision at the time of contract award.**

4. QUALITY ASSURANCE PROVISIONS:

- QAP EQ001 - This Quality Assurance Provision will apply when sampling plans are not specified.**
- QAP EQ003 - This Quality Assurance Provision establishes requirements for contractors' inspection systems.**
- QAP 1075 - This Quality Assurance Provision establishes requirements for Product Verification Testing, Certificate of Quality Compliance and Measuring and Test Equipment.**

CRITICAL ITEM PROCUREMENT REQUIREMENTS DOCUMENT (CIPRD)

MS27576-4-17

5. PACKAGING:

- (1) In addition to the labeling information specified in the contract or purchase order, each container, including the outside pack, the internal package and/or the individual unit pack, will display a label, on each side of the package, containing the following information:

CRITICAL SAFETY ITEM

- (2) The words "CRITICAL SAFETY ITEM" will be imprinted on each thread protection sleeve.

6. QUALIFIED SOURCES:

SPS Technologies (CAGE 80539)
2701 S. Harbor Blvd.
Santa Ana, CA 92704

Avibank Manufacturing Co. (84256)
11500 Sherman Way
North Hollywood, CA 91609

Space-Lok Inc. (CAGE 16258)
13306 Halldale Avenue
Gardena, CA 90247

7. QUALIFICATION PROCEDURES:

- (1) Companies wishing to qualify their product for listing in this CIPRD shall submit their request to:

Defense Supply Center Philadelphia
Office of Engineering and Technical Support
Attn: DSCP-NAS
700 Robbins Avenue
Philadelphia, PA 19111

- (2) Application for qualification must comply with the requirements delineated in the Qualification Attachment and the Navy source approval requirements contained in the Naval Inventory Control Point, Source Approval Brochure For Replenishment Parts, dated August 98 which can be found at www.navicp.navy.mil/sabs/sas/sasindex.htm and the Army source approval requirements at www.redstone.army.mil/cmo/data/CASLSAR3.doc.

- (a) Any new source interested in manufacturing this item must submit a qualification test sample(s) and successfully pass testing in accordance with NASM 83050 and instructions provided by the Contracting Officer. In addition, sources that successfully meet qualification test requirements must also meet Production Lot Testing per QAP 1075, before they are deemed as an acceptable source for listing in this CIPRD.

CRITICAL ITEM PROCURMENT REQUIREMENTS DOCUMENT (CIPRD)

MS27576-4-17

- (b) Any established source that has manufactured this item within the last 3 years from the date of the contract order must comply with the following:
 - Demonstrate that this product is still available from the listed plant, can be produced under the same conditions as originally qualified and meets the requirements of the current issue of this CIPRD and the specifications referenced herein.
 - At the request of the qualifying activity, periodically submit new test data.
 - At the request of the qualifying activity complete re-qualification testing.
- (c) Any established source that has manufactured this item but not within the last 3 years from the date of the contract order are subject to qualification testing in accordance with NASM 83050 and Production Lot Testing in accordance with QAP 1075. However, these requirements are subject to waiver by the Contracting Officer in coordination with the responsible Engineering Support Activity (ESA).

8. CERTIFICATIONS:

1. A Certificate will be prepared in accordance with the format contained in QAP 1075. As a minimum the Certificate will include the following:
 - (a) Material certification and analysis documentation:
 - Body: - Alloy Steel (4140) AMS6382, AMS6349, AMS6322.
Alloy Steel (8740) AMS6322, AMS632, AMS6327.
Alloy Steel (4130) AMS6758
Alloy Steel (6150) AMS6448
 - Retaining Element: - 17-4PH (UNS 17400), AMS5643, 17-7PH
AMS5844/AMS5678, 440C CRES Steel (UNS44004) AMS-QQ-S-763
 - (b) Plating: Cadmium in accordance with AMS-QQ-P-416, Type II, Class 2.
 - (c) Surface Texture in accordance with ANSI B46.1
 - (d) Threads in accordance with System 22 of FED-STD-H28.
 - (e) Part hardness, tensile strength, shear strength and certification of part dimensions to the minimum drawing requirements.
 - (f) The Contractor's name, address, CAGE code, contract number, the applicable specification (NASM27576), part number identification and nomenclature, NSN.
 - (g) The identification of the specific requirement for each parameter in paragraph 8.1c.
 - (g) The actual results of inspection or tests conducted to demonstrate conformance with each of the specific requirements in paragraph 8.1a through 8.1d.
2. The Certificate must be maintained on file at the manufacturer's plant for a minimum of 10 years and be made available to the government upon request.
3. Upon request, certify that this product is still available from the listed plant and is being produced using the same manufacturing and quality control processes that were used to fabricate the qualification test sample. Documentation of the manufacturing process substantiating this certification must be on file at the manufacturer's plant for a minimum of 10 years and made available to the government upon request.

CRITICAL ITEM PROCURMENT REQUIREMENTS DOCUMENT (CIPRD)

MS27576-4-17

QUALIFICATION ATTACHMENT

The manufacturer's application shall be made by letter or other appropriate media and addressed to the Defense Supply Center Philadelphia, Attn: DPSC-NAS, 700 Robbins Ave., Philadelphia, PA 19114. Each application must contain the number and date of the CIPRD under which tests are desired and the exact location (including complete street address) of the plant at which the product was manufactured.

In addition, the application must include certification that the applicant:

- Is the manufacturer of the product.
- Has determined from actual tests (within the limits of test equipment commonly available, unless otherwise specified) that the product conforms to the applicable CIPRD. (Test reports and data should be furnished with the application.)
- When requested, will supply products for test which are samples from the manufacturer's normal production.
- Will supply products that meet the requirements of the specification in every respect.
- Will overcome deficiencies disclosed by qualification testing.
- Will not apply for a retest of the product until satisfactory evidence is furnished that any defects disclosed by previous tests have been corrected. (Test reports may be required as evidence.)
- Will notify the qualifying activity of any change in design, material, manufacturing processes (including quality control), or plant location after qualification approval. As part of the notification the applicant will state whether he believes the change will prejudice the capability of the product to meet the qualification test requirements and state whether they intend to submit new samples for testing or desire to be removed as a qualified source.
- Will, when requested by the qualifying activity, submit a certification signed by a responsible official attesting that the applicable product is still available from the listed plant, can be produced under the same conditions as originally qualified and meets the requirements of the current issue of the CIPRD.
- Will, include provisions for self-audit of the processing, fabrication, assembly, inspection, and testing of the product. The results of the self-audit program, which promptly reports nonconformance (deviations) and corrective action to management, will be made available upon request.
- Has maintained, and will continue to maintain, effective management for quality, clearly prescribed and documented by the manufacturer. Manufacturer personnel performing quality functions will have sufficient, well-defined responsibility, authority, and the organizational freedom to identify and evaluate product quality problems and to initiate, recommend, and enforce solutions. Management will periodically review the status of the quality program for effectiveness.
- Agrees to provide the government access, upon request, to technical records, personnel, and facilities pertaining to manufacturing, processing, inspection, and testing to assure compliance with all the specification requirements.

CRITICAL ITEM PROCURMENT REQUIREMENTS DOCUMENT (CIPRD)

MS27576-4-17

In certain cases the government may find the information required above insufficient to justify an authorization for qualification testing. In those cases the preparing activity,

**Defense Supply Center Philadelphia
Office of Engineering and Technical support
Attn: DSCP-NAS
700 Robbins Ave.
Philadelphia, PA 19111**

may request the following information, which is to be provided at no cost to the government:

- **The rate at which the applicant can produce the product with his present plant facilities.**
- **Sketches, photographs, descriptive booklets, or other technical literature bearing upon the product that will assist the government in obtaining a clear conception of the product or process the applicant is offering.**
- **Such additional information as is required by the applicable specification.**

Data

When requested by the qualifying activity, the applicant will furnish, at no cost to the government for test record purposes, copies of any detailed plans, specification test results, or other data required (number required and the media will be specified by the qualifying activity). If such data includes information which the applicant has determined is proprietary and does not wish disclosed to the public or used by the government for any purpose other than testing the product or process for which qualification is desired, the applicant will identify and mark the data which he considers to be proprietary. He will insert the following legend on each sheet containing proprietary data:

“These data are considered by the supplier to be submitted in confidence and furnished for the purpose of facilitating qualification testing and are not to be disclosed outside the Government nor to be duplicated, used, or disclosed in whole or in part, for any purpose other than to evaluate the product submitted for qualification testing. This restriction does not limit the Government’s right to use information contained in such data if it is obtained from another source.”



Data Source: USAINFO.COM

7/27/2006 11:25:20 AM

NSN INFORMATION 5306-00-121-8848

INC: 27851 ITEM NAME: BOLT,CLOSE TOLERANCE FIIG: A003B0
 CRIT F ISC 2 Status 0 THIC 1 RPD MRC ADP DEMIL A HMIC N ESDEMI PMI U

MCRL Information 5306-00-121-8848

| Part No. | rncc | rnvc | rnfc | sadc | dac | cage | Vendor Name |
|--------------|------|------|------|------|-----|-------|------------------|
| 106467-4-17 | 5 | 2 | 4 | | 5 | 80539 | SPS TECHNOLOGIES |
| AS194-4-17 | 5 | 2 | 4 | | 6 | R1120 | SATAIR A/S |
| AS194-4-17 | 5 | 2 | 4 | | 5 | 84256 | AVIBANK MFG INC |
| CA4510-4-17 | 5 | 9 | 4 | | 5 | 29372 | ALCOA GLOBAL FAS |
| MS27576-4-17 | 5 | 9 | 3 | | 4 | 96906 | MILITARY STANDAR |
| MS27576-4-17 | 3 | 2 | | | E | 80205 | NATIONAL AEROSPA |
| SS5031-4-17 | C | 1 | | AC | 5 | 78286 | SIKORSKY AIRCRAF |

ML-C Information 5306-00-121-8848

| SA | SOS | mcd | UI | QUP | AAC | SLC | RC | CIIC | eff_date | price |
|----|-----|---------|------|-----|-----|-----|----|------|----------|-------|
| DN | S9I | 9Z----- | EA 1 | D | 0 | | | U | 2005274 | 9.86 |
| DA | S9I | T2200X- | EA 1 | D | 0 | | Z | U | 2005274 | 9.86 |
| GP | S9I | | EA 1 | D | 0 | | | U | 2005274 | 9.86 |
| DM | S9I | 17I2--- | EA 1 | D | 0 | | Z | U | 2005274 | 9.86 |
| DF | S9I | SF9SX-V | EA 1 | D | 0 | | N | U | 2005274 | 9.86 |
| DS | S9I | | EA 1 | D | 0 | | | U | 2005274 | 9.86 |

ML-C Phrase Statements 5306-00-121-8848

sa pc Phrase Statement
 DF R REFER TO REFER TO AFT095REQ

Major Organizational Entity (MOE) Data 5306-00-121-8848

| Moe Rule | Moe Code | pica | amc | amsc | nimsc | imc | imca | aac | Collaborators | Receivers |
|----------|----------|------|-----|------|-------|-----|------|-----|---------------|-----------|
| A187 | DA | KZ | 1 | G | | Z | CD | | | CT |
| C004 | GP | KZ | 1 | G | | | | | | |
| FVKZ | DF | KZ | 1 | G | | Z | SX | | | |
| MC10 | DM | KZ | 1 | G | | Z | PA | | | |
| N9ZD | DN | KZ | 1 | G | | Z | GH | | KE | |
| YB01 | YB | YB | | | | | | | | |
| YJ01 | YJ | YJ | | | | | | | | |
| ZA01 | ZA | ZA | | | | | | | | |
| ZC01 | ZC | ZC | | | | | | | | |

| | | |
|------|----|----|
| ZG01 | ZG | ZG |
| ZH01 | ZH | ZH |
| ZK01 | ZK | ZK |
| ZN01 | ZN | ZN |
| ZR01 | ZR | ZR |
| ZU01 | ZU | ZU |

Technical Characteristics (ILs) 5306-00-121-8848

| mrc | requirement | reply |
|------------|---|---|
| AAJD | THREAD CLASS | 3A |
| AAJF | THREAD DIRECTION | RIGHT-HAND |
| AASA | THREAD LENGTH | 0.283 INCHES MINIMUM AND 0.334 INCHES MAXIMUM |
| AASB | FASTENER LENGTH | 1.481 INCHES MINIMUM AND 1.501 INCHES MAXIMUM |
| AASK | HEAD STYLE | C3 DISHED HEXAGON |
| AASU | HEAD HEIGHT | 0.126 INCHES MINIMUM AND 0.141 INCHES MAXIMUM |
| AATB | WIDTH BETWEEN FLATS | 0.430 INCHES MINIMUM AND 0.439 INCHES MAXIMUM |
| AAUR | GRIP DIAMETER | 0.2483 INCHES MINIMUM AND 0.2492 INCHES MAXIMUM |
| AAWB | SHANK UNTHREADED HOLE DIAMETER | 0.076 INCHES MINIMUM AND 0.086 INCHES MAXIMUM FIRST HOLE |
| AHYM | NOMINAL THREAD DIAMETER | 0.250 INCHES |
| ANEE | GRIP LENGTH | 1.062 INCHES MINIMUM AND 1.078 INCHES MAXIMUM |
| CMLP | THREAD QUANTITY PER INCH | 28 |
| CQFM | HARDNESS RATING | 36.0 ROCKWELL C MINIMUM AND 41.0 ROCKWELL C MAXIMUM OVERALL |
| CRZS | DISTANCE FROM HEAD LARGEST BEARING SURFACE TO SHANK HOLE CENTER | 1.381 INCHES MINIMUM AND 1.411 INCHES MAXIMUM FIRST HOLE |
| CSYM | SURFACE FINISH | 63.0 MICROINCHES BEARING SURFACE OF HEAD |
| CSYM | SURFACE FINISH | 63.0 MICROINCHES GRIP |
| FEAT | SPECIAL FEATURES | W/RETAINING ELEMENT ON SHANK |
| MATT | MATERIAL | STEEL OVERALL |
| MDCL | MATERIAL DOCUMENT AND CLASSIFICATION | MIL-B-83050 MIL SPEC SINGLE MATERIAL RESPONSE OVERALL |
| SFTT | SURFACE TREATMENT | CADMIUM AND CHROMATE OVERALL |
| STDC | SURFACE TREATMENT DOCUMENT AND CLASSIFICATION | QQ-P-416 TY 2 CL 2 FED SPEC ALL TREATMENT RESPONSES OVERALL |
| THSD | THREAD SERIES DESIGNATOR | UNJF |

Current Procurement History Information 5306-00-121-8848

| AwardDate | Contract_No | ContractX | SOS | Qty | Price | Total | UI | cage | Vendor |
|------------|---------------|-----------|-----|-------|-------|-----------|----|--------------|-----------|
| 10/15/2005 | SP051005M0931 | MODF0001 | S9I | 12000 | 7.55 | 90,600.00 | EA | <u>0WGX9</u> | TAOS INI |
| 7/20/2004 | SP054004MP302 | MODF0002 | S9I | 2700 | 7.54 | 20,358.00 | EA | <u>0EER9</u> | ANIXTER |
| 7/20/2004 | SP054004MP302 | MODF0001 | S9I | 3000 | 7.54 | 22,620.00 | EA | <u>0EER9</u> | ANIXTER |
| 2/27/2004 | SP051004M0023 | MODF0002 | S9I | 2 | 8.83 | 17.66 | EA | <u>5R386</u> | T P S AVI |
| 1/16/2004 | SP054004M7940 | MODF0001 | S9I | 6500 | 7.75 | 50,375.00 | EA | <u>5R386</u> | T P S AVI |
| 10/8/2003 | SP051004M0023 | MODF0001 | S9I | 1498 | 8.83 | 13,227.34 | EA | <u>5R386</u> | T P S AVI |
| 10/8/2003 | SP051004M0023 | MODF0001 | S9I | 1500 | 8.83 | 13,245.00 | EA | <u>5R386</u> | T P S AVI |
| 10/3/2003 | SP051003M1459 | MODF0001 | S9I | 50 | 36.45 | 1,822.50 | EA | <u>00360</u> | AERO MI |
| 4/29/2003 | SP051003M0841 | MODF0001 | S9I | 50 | 40.50 | 2,025.00 | EA | <u>80539</u> | SPS TECH |
| 4/29/2003 | SP051003M0841 | MODF0002 | S9I | 50 | 40.50 | 2,025.00 | EA | <u>80539</u> | SPS TECH |
| 4/28/2003 | SP051003M0844 | MODF0001 | S9I | 2200 | 8.77 | 19,294.00 | EA | <u>7Z016</u> | KAMPI C |
| 10/21/2001 | SP054002MQ608 | MODF0001 | S9I | 483 | 8.70 | 4,202.10 | | <u>1V757</u> | WESCO A |
| 10/21/2001 | SP054002MQ608 | MODF0002 | S9I | 165 | 8.70 | 1,435.50 | | <u>1V757</u> | WESCO A |
| 1/25/2001 | SP054001MQY97 | MODF0001 | S9I | 356 | 8.55 | 3,043.80 | | <u>00360</u> | AERO MI |
| 1/25/2001 | SP054001MQY97 | MODF0002 | S9I | 444 | 8.55 | 3,796.20 | | <u>00360</u> | AERO MI |
| 3/8/2000 | SP054000MQUB9 | MODF0001 | S9I | 576 | 10.85 | 6,249.60 | | <u>5R386</u> | T P S AVI |

No Next Higher Assembly (NHA) Found for NSN: 5306-00-121-8848

No NHA 2330 Table Found for NSN: 5306-00-121-8848

Contract Technical Data File: Weapon Systems 5306-00-121-8848

| Src | wsc | crit | ricfm | Definition |
|-----|-----|------|------------|---|
| S9I | 11F | A | WR-ALC | AIRCRAFT, GALAXY C-5 |
| S9I | FMF | A | OC-ALC | AIRCRAFT,B-2 BOMBER (ATB) |
| S9I | DUF | A | WR-ALC | HELICOPTER, SOF / HH-53J/M PAVE LOW |
| S9I | FPF | C | OC-ALC | ADVANCED CRUISE MISSILE,ACM-129 |
| S9I | YYA | C | AMCOM | AIRCRAFT MH-47E SPECIAL OPERATIONS AIRCRAFT |
| S9I | 15F | C | WR-ALC | HELICOPTER, GREEN GIANT H-3 |
| S9I | AUF | C | OC-ALC | TRAINER, B-1B AIRCRAFT |
| S9I | WBN | C | NAVICPPHIL | VELOCITY POOL REPARABLE PIECE PARTS |
| S9I | 05A | A | AMCOM | HELICOPTER, CHINOOK, CH-47 |
| S9I | LBA | C | AMCOM | AH-64-D LONGBOW |

Cancelled NIINs 5306-00-121-8848

| cancelled_fsc | cancelled_niin |
|---------------|----------------|
| 5306 | 005578575 |
| 5306 | 010773892 |

Drawings/Standards 5306-00-121-8848

| DspId | KeyId | Cage | SpecCode |
|--------------|-------|------|----------|
| NASM27576 | | | T |
| MIL-B-83050D | | | S |