



```
<?xml version="1.0" encoding="UTF-8"?>
<!-- Automatically generated by EDIFECS SpecBuilder (http://www.edifeecs.com) -->
<xsd:schema targetNamespace="http://www.edifeecs.com/xdata/200" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://www.edifeecs.com/xdata/200" elementFormDefault="qualified" version="1.0">
  <xsd:element name="T_Return_Merchandise_Authorization_and_Notification" type="T_180"/>
  <xsd:complexType name="T_180">
    <xsd:annotation>
      <xsd:documentation>This Draft Standard for Trial Use contains the format and establishes the data contents of the Return Merchandise Authorization and Notification Transaction Set (180) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set can provide for customary and established business and industry practice relative to the returning of merchandise to the vendor. This transaction set may satisfy request for returns, authorization or disposition of the return, notification of return, or notification of consumer return.</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
      <xsd:element name="Internal-Properties" type="Internal-Properties" minOccurs="0"/>
      <xsd:element name="S_Transaction_Set_Header" type="S_ST"/>
      <xsd:element name="S_Beginning_Segment" type="S_BGN"/>
      <xsd:element name="L_Name" type="L_N1" maxOccurs="200"/>
      <xsd:element name="L_Baseline_Item_Data" type="L_BLI" maxOccurs="unbounded"/>
      <xsd:element name="S_Transaction_Set_Trailer" type="S_SE"/>
    </xsd:sequence>
    <xsd:attribute name="Type" type="xsd:string" default="Transaction"/>
    <xsd:attribute name="ID" type="xsd:string" default="180"/>
    <xsd:attribute name="Name" type="xsd:string" default="Return Merchandise Authorization and Notification"/>
    <xsd:attribute name="XDataVersion" type="xsd:string" fixed="1.0"/>
    <xsd:attribute name="Standard" type="xsd:string" fixed="X12"/>
    <xsd:attribute name="Version" type="xsd:string" default="V4010"/>
    <xsd:attribute name="GUID" type="xsd:string"/>
    <xsd:attribute name="CreatedBy" type="xsd:string"/>
    <xsd:attribute name="CreatedDate" type="xsd:dateTime"/>
  </xsd:complexType>
  <xsd:complexType name="EDI-Element-String-Type">
    <xsd:simpleContent>
      <xsd:extension base="xsd:string">
        <xsd:attribute name="Type" type="xsd:string" default="Element"/>
        <xsd:attribute name="EDIDataType" type="xsd:string"/>
        <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
        <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
        <xsd:attribute name="ID" type="xsd:string"/>
        <xsd:attribute name="Name" type="xsd:string"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>
  <xsd:complexType name="EDI-Element-Integer-Type">
    <xsd:simpleContent>
      <xsd:extension base="xsd:integer">
        <xsd:attribute name="Type" type="xsd:string" default="Element"/>
        <xsd:attribute name="EDIDataType" type="xsd:string"/>
        <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
        <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
        <xsd:attribute name="ID" type="xsd:string"/>
        <xsd:attribute name="Name" type="xsd:string"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>
  <xsd:complexType name="EDI-Element-Decimal-Type">
    <xsd:simpleContent>
      <xsd:extension base="xsd:decimal">
        <xsd:attribute name="Type" type="xsd:string" default="Element"/>
        <xsd:attribute name="EDIDataType" type="xsd:string"/>
        <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
        <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
        <xsd:attribute name="ID" type="xsd:string"/>
        <xsd:attribute name="Name" type="xsd:string"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>

```



```
<xsd:complexType name="EDI-Element-hexBinary-Type">
  <xsd:simpleContent>
    <xsd:extension base="xsd:hexBinary">
      <xsd:attribute name="Type" type="xsd:string" default="Element"/>
      <xsd:attribute name="EDIDataType" type="xsd:string"/>
      <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
      <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
      <xsd:attribute name="ID" type="xsd:string"/>
      <xsd:attribute name="Name" type="xsd:string"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="EDI-Element-base64Binary-Type">
  <xsd:simpleContent>
    <xsd:extension base="xsd:base64Binary">
      <xsd:attribute name="Type" type="xsd:string" default="Element"/>
      <xsd:attribute name="EDIDataType" type="xsd:string"/>
      <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
      <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
      <xsd:attribute name="ID" type="xsd:string"/>
      <xsd:attribute name="Name" type="xsd:string"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="EDI-Element-Any-Type">
  <xsd:simpleContent>
    <xsd:extension base="xsd:string">
      <xsd:attribute name="Type" type="xsd:string" default="Element"/>
      <xsd:attribute name="EDIDataType" type="xsd:string"/>
      <xsd:attribute name="Macro" type="xsd:string" use="optional"/>
      <xsd:attribute name="ApplicationInfo" type="xsd:string"/>
      <xsd:attribute name="ID" type="xsd:string"/>
      <xsd:attribute name="Name" type="xsd:string"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="Internal-Properties">
  <xsd:sequence>
    <xsd:element name="Data-Structure" type="Data-Structure" minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="Data-Structure">
  <xsd:sequence>
    <xsd:element name="Lookup" type="Lookup" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="Property" type="Property" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="Data-Structure" type="Data-Structure" minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="Lookup">
  <xsd:simpleContent>
    <xsd:extension base="xsd:string">
      <xsd:attribute name="Name" type="xsd:string"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="Property">
  <xsd:simpleContent>
    <xsd:extension base="xsd:string">
      <xsd:attribute name="Name" type="xsd:string"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="S_ST">
  <xsd:annotation>
    <xsd:documentation>To indicate the start of a transaction set and to assign a control number</xsd:documentation>
  </xsd:annotation>
```



```
<xsd:sequence>
  <xsd:element name="E_Transaction_Set_Identifier_Code" type="E_143"/>
  <xsd:element name="E_Transaction_Set_Control_Number" type="E_329"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="ST"/>
<xsd:attribute name="Name" type="xsd:string" default="Transaction Set Header"/>
</xsd:complexType>
<xsd:complexType name="E_143">
  <xsd:annotation>
    <xsd:documentation>Code uniquely identifying a Transaction Set</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="180"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="143"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Transaction Set Identifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_329">
  <xsd:annotation>
    <xsd:documentation>Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="9"/>
      <xsd:minLength value="4"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="329"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Transaction Set Control Number"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="S_BGN">
  <xsd:annotation>
    <xsd:documentation>To indicate the beginning of a transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Transaction_Set_Purpose_Code" type="E_353"/>
    <xsd:element name="E_Reference_Identification" type="E_127"/>
    <xsd:element name="E_Date" type="E_373"/>
    <xsd:element name="E_Time" type="E_337"/>
    <xsd:element name="E_Time_Code" type="E_623" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Reference_Identification_1" type="E_127_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Transaction_Type_Code" type="E_640"/>
    <xsd:element name="E_Action_Code" type="E_306" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Security_Level_Code" type="E_786" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="BGN"/>
  <xsd:attribute name="Name" type="xsd:string" default="Beginning Segment"/>
</xsd:complexType>
<xsd:complexType name="E_353">
  <xsd:annotation>
    <xsd:documentation>Code identifying purpose of transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="00"/>
      <xsd:enumeration value="77"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="353"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Transaction Set Purpose Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
```



```
</xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_127">
  <xsd:annotation>
    <xsd:documentation>Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="30"/>
      <xsd:minLength value="1"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="127"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Reference Identification"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_373">
  <xsd:annotation>
    <xsd:documentation>Date expressed as CCYYMMDD</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="8"/>
      <xsd:minLength value="8"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="DT"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="373"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Date"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_337">
  <xsd:annotation>
    <xsd:documentation>Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="8"/>
      <xsd:minLength value="4"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="TM"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="337"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Time"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_623">
  <xsd:annotation>
    <xsd:documentation>Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_127_1">
  <xsd:annotation>
    <xsd:documentation>Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_640">
  <xsd:annotation>
    <xsd:documentation>Code specifying the type of transaction</xsd:documentation>
  </xsd:annotation>

```



```
</xsd:annotation>
<xsd:simpleContent>
  <xsd:restriction base="EDI-Element-String-Type">
    <xsd:enumeration value="FT"/>
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="640"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Transaction Type Code"/>
  </xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_306">
  <xsd:annotation>
    <xsd:documentation>Code indicating type of action</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="C"/>
      <xsd:enumeration value="T"/>
      <xsd:enumeration value="RF"/>
      <xsd:enumeration value="RS"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="306"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Action Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_786">
  <xsd:annotation>
    <xsd:documentation>Code indicating the level of confidentiality assigned by the sender to the information following</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="L_N1">
  <xsd:annotation>
    <xsd:documentation>To identify a party by type of organization, name, and code</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="S_Name" type="S_N1"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
  <xsd:attribute name="ID" type="xsd:string" default="N1"/>
  <xsd:attribute name="Name" type="xsd:string" default="Name"/>
</xsd:complexType>
<xsd:complexType name="S_N1">
  <xsd:annotation>
    <xsd:documentation>To identify a party by type of organization, name, and code</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Entity_Identifier_Code" type="E_98"/>
    <xsd:element name="E_Name" type="E_93" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Identification_Code_Qualifier" type="E_66"/>
    <xsd:element name="E_Identification_Code" type="E_67"/>
    <xsd:element name="E_Entity_Relationship_Code" type="E_706" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Entity_Identifier_Code_1" type="E_98_1"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="N1"/>
  <xsd:attribute name="Name" type="xsd:string" default="Name"/>
</xsd:complexType>
<xsd:complexType name="E_98">
  <xsd:annotation>
    <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="41"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
```



```
<xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
<xsd:attribute name="ID" type="xsd:string" fixed="98"/>
<xsd:attribute name="Name" type="xsd:string" fixed="Entity Identifier Code"/>
</xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_93">
  <xsd:annotation>
    <xsd:documentation>Free-form name</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_66">
  <xsd:annotation>
    <xsd:documentation>Code designating the system/method of code structure used for Identification Code (67)</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="1"/>
      <xsd:enumeration value="9"/>
      <xsd:enumeration value="10"/>
      <xsd:enumeration value="A2"/>
      <xsd:enumeration value="M4"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="66"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Identification Code Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_67">
  <xsd:annotation>
    <xsd:documentation>Code identifying a party or other code</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="80"/>
      <xsd:minLength value="2"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="67"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Identification Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_706">
  <xsd:annotation>
    <xsd:documentation>Code describing entity relationship</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_98_1">
  <xsd:annotation>
    <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="FR"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="98"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Entity Identifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="L_BLI">
  <xsd:annotation>
    <xsd:documentation>To specify basic item data: item identification, quantity, and price</xsd:documentation>
  </xsd:annotation>
</xsd:annotation>
```



```

<xsd:sequence>
  <xsd:element name="S_Baseline_Item_Data" type="S_BLI"/>
  <xsd:element name="S_Reference_Identification" type="S_N9" maxOccurs="20"/>
  <xsd:element name="S_Carrier_Details_Routing_Sequence_Transit_Time_" type="S_TD5" nillable="true" minOccurs="0" maxOccurs="5"/>
  <xsd:element name="L_Code_Source_Information" type="L_LM" maxOccurs="10"/>
  <xsd:element name="L_Name" type="L_N1_1" maxOccurs="200"/>
  <xsd:element name="L_Quantity" type="L_QTY" maxOccurs="unbounded"/>
  <xsd:element name="L_Type_of_Financial_Accounting_Data" type="L_FA1" nillable="true" minOccurs="0" maxOccurs="unbounded"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Loop"/>
<xsd:attribute name="ID" type="xsd:string" default="BLI"/>
<xsd:attribute name="Name" type="xsd:string" default="Baseline Item Data"/>
</xsd:complexType>
<xsd:complexType name="S_BLI">
  <xsd:annotation>
    <xsd:documentation>To specify basic item data: item identification, quantity, and price</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Product_Service_ID_Qualifier" type="E_235"/>
    <xsd:element name="E_Product_Service_ID" type="E_234"/>
    <xsd:element name="E_Quantity" type="E_380" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Price_Identifier_Code" type="E_236" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_Price" type="E_212" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code_1" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_Qualifier_1" type="E_235_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_1" type="E_234" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_Qualifier_2" type="E_235_2" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_2" type="E_234_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_Qualifier_3" type="E_235_2" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Service_ID_3" type="E_234_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Option_Code" type="E_1161" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Option_Code_1" type="E_1161" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Option_Code_2" type="E_1161" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Product_Option_Code_3" type="E_1161" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Frequency_Code" type="E_594" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="BLI"/>
  <xsd:attribute name="Name" type="xsd:string" default="Baseline Item Data"/>
</xsd:complexType>
<xsd:complexType name="E_235">
  <xsd:annotation>
    <xsd:documentation>Code identifying the type/source of the descriptive number used in Product/Service ID (234)</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="A1"/>
      <xsd:enumeration value="A2"/>
      <xsd:enumeration value="A4"/>
      <xsd:enumeration value="FB"/>
      <xsd:enumeration value="FS"/>
      <xsd:enumeration value="MG"/>
      <xsd:enumeration value="YP"/>
      <xsd:enumeration value="ZZ"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="235"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Product/Service ID Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_234">
  <xsd:annotation>
    <xsd:documentation>Identifying number for a product or service</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>

```



```
<xsd:restriction base="EDI-Element-String-Type">
  <xsd:maxLength value="48"/>
  <xsd:minLength value="1"/>
  <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
  <xsd:attribute name="ID" type="xsd:string" fixed="234"/>
  <xsd:attribute name="Name" type="xsd:string" fixed="Product/Service ID"/>
</xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_380">
  <xsd:annotation>
    <xsd:documentation>Numeric value of quantity</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_355">
  <xsd:annotation>
    <xsd:documentation>Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_236">
  <xsd:annotation>
    <xsd:documentation>Code identifying pricing specification</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="ACT"/>
      <xsd:enumeration value="EST"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="236"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Price Identifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_212">
  <xsd:annotation>
    <xsd:documentation>Price per unit of product, service, commodity, etc.</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-Decimal-Type">
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="R"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="212"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Unit Price"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_235_1">
  <xsd:annotation>
    <xsd:documentation>Code identifying the type/source of the descriptive number used in Product/Service ID (234)</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="ZB"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="235"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Product/Service ID Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_235_2">
  <xsd:annotation>
    <xsd:documentation>Code identifying the type/source of the descriptive number used in Product/Service ID (234)</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
```



```
</xsd:complexType>
<xsd:complexType name="E_234_1">
  <xsd:annotation>
    <xsd:documentation>Identifying number for a product or service</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_1161">
  <xsd:annotation>
    <xsd:documentation>Code indicating an option chosen for the product</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_594">
  <xsd:annotation>
    <xsd:documentation>Code indicating frequency or type of payment</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="S_N9">
  <xsd:annotation>
    <xsd:documentation>To transmit identifying information as specified by the Reference Identification Qualifier</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Reference_Identification_Qualifier" type="E_128"/>
    <xsd:element name="E_Reference_Identification" type="E_127"/>
    <xsd:element name="E_Free-form_Description" type="E_369" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Date" type="E_373_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Time" type="E_337_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Time_Code" type="E_623" nillable="true" minOccurs="0"/>
    <xsd:element name="C_Reference_Identifier" type="C_C040" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="N9"/>
  <xsd:attribute name="Name" type="xsd:string" default="Reference Identification"/>
</xsd:complexType>
<xsd:complexType name="E_128">
  <xsd:annotation>
    <xsd:documentation>Code qualifying the Reference Identification</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="TG"/>
      <xsd:enumeration value="TN"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="128"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Reference Identification Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_369">
  <xsd:annotation>
    <xsd:documentation>Free-form descriptive text</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_373_1">
  <xsd:annotation>
    <xsd:documentation>Date expressed as CCYYMMDD</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_337_1">
  <xsd:annotation>
    <xsd:documentation>Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD =</xsd:documentation>
  </xsd:annotation>

```



```
hundredths (00-99)</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="C_C040">
  <xsd:annotation>
    <xsd:documentation>To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier</xsd:documentation>
  </xsd:annotation>
  </xsd:sequence>
  <xsd:element name="E_Reference_Identification_Qualifier" type="E_128_1"/>
  <xsd:element name="E_Reference_Identification" type="E_127"/>
  <xsd:element name="E_Reference_Identification_Qualifier_1" type="E_128_2" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Reference_Identification_1" type="E_127_1" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Reference_Identification_Qualifier_2" type="E_128_2" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Reference_Identification_2" type="E_127_1" nillable="true" minOccurs="0"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Composite"/>
<xsd:attribute name="ID" type="xsd:string" default="C040"/>
<xsd:attribute name="Name" type="xsd:string" default="Reference Identifier"/>
</xsd:complexType>
<xsd:complexType name="E_128_1">
  <xsd:annotation>
    <xsd:documentation>Code qualifying the Reference Identification</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="W8"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="128"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Reference Identification Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_128_2">
  <xsd:annotation>
    <xsd:documentation>Code qualifying the Reference Identification</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="S_TD5">
  <xsd:annotation>
    <xsd:documentation>To specify the carrier and sequence of routing and provide transit time information</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Routing_Sequence_Code" type="E_133" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Identification_Code_Qualifier" type="E_66_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Identification_Code" type="E_67_1" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Transportation_Method_Type_Code" type="E_91" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Routing" type="E_387" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Shipment_Order_Status_Code" type="E_368" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Location_Qualifier" type="E_309" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Location_Identifier" type="E_310" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Transit_Direction_Code" type="E_731" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Transit_Time_Direction_Qualifier" type="E_732" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Transit_Time" type="E_733" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Service_Level_Code" type="E_284" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Service_Level_Code_1" type="E_284" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Service_Level_Code_2" type="E_284" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Country_Code" type="E_26" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="TD5"/>
  <xsd:attribute name="Name" type="xsd:string" default="Carrier Details (Routing Sequence/Transit Time)"/>
</xsd:complexType>
<xsd:complexType name="E_133">
```



```
<xsd:annotation>
  <xsd:documentation>Code describing the relationship of a carrier to a specific shipment movement</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_66_1">
  <xsd:annotation>
    <xsd:documentation>Code designating the system/method of code structure used for Identification Code (67)</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_67_1">
  <xsd:annotation>
    <xsd:documentation>Code identifying a party or other code</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_91">
  <xsd:annotation>
    <xsd:documentation>Code specifying the method or type of transportation for the shipment</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="91"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Transportation Method/Type Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_387">
  <xsd:annotation>
    <xsd:documentation>Free-form description of the routing or requested routing for shipment, or the originating carrier's identity</xsd:documentation>
  </xsd:annotation>
</xsd:complexType>
<xsd:complexType name="E_368">
  <xsd:annotation>
    <xsd:documentation>Code indicating the status of an order or shipment or the disposition of any difference between the quantity ordered and the quantity shipped for a line item or transaction</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_309">
  <xsd:annotation>
    <xsd:documentation>Code identifying type of location</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_310">
  <xsd:annotation>
    <xsd:documentation>Code which identifies a specific location</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_731">
  <xsd:annotation>
    <xsd:documentation>The point of origin and point of direction</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_732">
  <xsd:annotation>
    <xsd:documentation>Code specifying the value of time used to measure the transit time</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
```



```
</xsd:complexType>
<xsd:complexType name="E_733">
  <xsd:annotation>
    <xsd:documentation>The numeric amount of transit time</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_284">
  <xsd:annotation>
    <xsd:documentation>Code indicating the level of transportation service or the billing service offered by the transportation carrier</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_26">
  <xsd:annotation>
    <xsd:documentation>Code identifying the country</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="L_LM">
  <xsd:annotation>
    <xsd:documentation>To transmit standard code list identification information</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="S_Code_Source_Information" type="S_LM"/>
    <xsd:element name="S_Industry_Code" type="S_LQ" maxOccurs="100"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
  <xsd:attribute name="ID" type="xsd:string" default="LM"/>
  <xsd:attribute name="Name" type="xsd:string" default="Code Source Information"/>
</xsd:complexType>
<xsd:complexType name="S_LM">
  <xsd:annotation>
    <xsd:documentation>To transmit standard code list identification information</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Agency_Qualifier_Code" type="E_559"/>
    <xsd:element name="E_Source_Subqualifier" type="E_822" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="LM"/>
  <xsd:attribute name="Name" type="xsd:string" default="Code Source Information"/>
</xsd:complexType>
<xsd:complexType name="E_559">
  <xsd:annotation>
    <xsd:documentation>Code identifying the agency assigning the code values</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="DF"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="559"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Agency Qualifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_822">
  <xsd:annotation>
    <xsd:documentation>A reference that indicates the table or text maintained by the Source Qualifier</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="S_LQ">
  <xsd:annotation>
    <xsd:documentation>Code to transmit standard industry codes</xsd:documentation>
  </xsd:annotation>
```



```

</xsd:annotation>
<xsd:sequence>
    <xsd:element name="E_Code_List_Qualifier_Code" type="E_1270"/>
    <xsd:element name="E_Industry_Code" type="E_1271"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="LQ"/>
<xsd:attribute name="Name" type="xsd:string" default="Industry Code"/>
</xsd:complexType>
<xsd:complexType name="E_1270">
    <xsd:annotation>
        <xsd:documentation>Code identifying a specific industry code list</xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:restriction base="EDI-Element-String-Type">
            <xsd:enumeration value="0"/>
            <xsd:enumeration value="78"/>
            <xsd:enumeration value="79"/>
            <xsd:enumeration value="80"/>
            <xsd:enumeration value="87"/>
            <xsd:enumeration value="A9"/>
            <xsd:enumeration value="AJ"/>
            <xsd:enumeration value="AL"/>
            <xsd:enumeration value="DE"/>
            <xsd:enumeration value="DF"/>
            <xsd:enumeration value="COG"/>
            <xsd:enumeration value="IMC"/>
            <xsd:enumeration value="MCC"/>
            <xsd:enumeration value="SMI"/>
            <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
            <xsd:attribute name="ID" type="xsd:string" fixed="1270"/>
            <xsd:attribute name="Name" type="xsd:string" fixed="Code List Qualifier Code"/>
        </xsd:restriction>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_1271">
    <xsd:annotation>
        <xsd:documentation>Code indicating a code from a specific industry code list</xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:restriction base="EDI-Element-String-Type">
            <xsd:maxLength value="30"/>
            <xsd:minLength value="1"/>
            <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
            <xsd:attribute name="ID" type="xsd:string" fixed="1271"/>
            <xsd:attribute name="Name" type="xsd:string" fixed="Industry Code"/>
        </xsd:restriction>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="L_N1_1">
    <xsd:annotation>
        <xsd:documentation>To identify a party by type of organization, name, and code</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="S_Name" type="S_N1_1"/>
    </xsd:sequence>
    <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
    <xsd:attribute name="ID" type="xsd:string" default="N1"/>
    <xsd:attribute name="Name" type="xsd:string" default="Name"/>
</xsd:complexType>
<xsd:complexType name="S_N1_1">
    <xsd:annotation>
        <xsd:documentation>To identify a party by type of organization, name, and code</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="E_Entity_Identifier_Code" type="E_98_2"/>
    </xsd:sequence>

```



```
<xsd:element name="E_Name" type="E_93" nillable="true" minOccurs="0"/>
<xsd:element name="E_Identification_Code_Qualifier" type="E_66"/>
<xsd:element name="E_Identification_Code" type="E_67"/>
<xsd:element name="E_Entity_Relationship_Code" type="E_706" nillable="true" minOccurs="0"/>
<xsd:element name="E_Entity_Identifier_Code_1" type="E_98_3" nillable="true" minOccurs="0"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="N1"/>
<xsd:attribute name="Name" type="xsd:string" default="Name"/>
</xsd:complexType>
<xsd:complexType name="E_98_2">
<xsd:annotation>
  <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
</xsd:annotation>
<xsd:simpleContent>
  <xsd:restriction base="EDI-Element-String-Type">
    <xsd:enumeration value="77"/>
    <xsd:enumeration value="CN"/>
    <xsd:enumeration value="SF"/>
    <xsd:enumeration value="Z1"/>
    <xsd:enumeration value="Z4"/>
    <xsd:enumeration value="ZB"/>
    <xsd:enumeration value="ZZ"/>
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="98"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Entity Identifier Code"/>
  </xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_98_3">
<xsd:annotation>
  <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
</xsd:annotation>
<xsd:simpleContent>
  <xsd:restriction base="EDI-Element-String-Type">
    <xsd:enumeration value="TO"/>
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="98"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Entity Identifier Code"/>
  </xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="L_QTY">
<xsd:annotation>
  <xsd:documentation>To specify quantity information</xsd:documentation>
</xsd:annotation>
<xsd:sequence>
  <xsd:element name="S_Quantity" type="S_QTY"/>
  <xsd:element name="S_Date_Time_Reference" type="S_DTM" nillable="true" minOccurs="0" maxOccurs="10"/>
  <xsd:element name="L_Code_Source_Information" type="L_LM_1" nillable="true" minOccurs="0" maxOccurs="10"/>
  <xsd:element name="L_Assigned_Number" type="L_LX" nillable="true" minOccurs="0" maxOccurs="unbounded"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Loop"/>
<xsd:attribute name="ID" type="xsd:string" default="QTY"/>
<xsd:attribute name="Name" type="xsd:string" default="Quantity"/>
</xsd:complexType>
<xsd:complexType name="S_QTY">
<xsd:annotation>
  <xsd:documentation>To specify quantity information</xsd:documentation>
</xsd:annotation>
<xsd:sequence>
  <xsd:element name="E_Quantity_Qualifier" type="E_673"/>
  <xsd:element name="E_Quantity" type="E_380_1"/>
  <xsd:element name="C_Composite_Unit_of_Measure" type="C_C001" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Free-Form_Message" type="E_61" nillable="true" minOccurs="0"/>
</xsd:sequence>
```



```
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="QTY"/>
<xsd:attribute name="Name" type="xsd:string" default="Quantity"/>
</xsd:complexType>
<xsd:complexType name="E_673">
  <xsd:annotation>
    <xsd:documentation>Code specifying the type of quantity</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="01"/>
      <xsd:enumeration value="28"/>
      <xsd:enumeration value="38"/>
      <xsd:enumeration value="39"/>
      <xsd:enumeration value="AA"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="673"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Quantity Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_380_1">
  <xsd:annotation>
    <xsd:documentation>Numeric value of quantity</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-Decimal-Type">
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="R"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="380"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Quantity"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="C_C001">
  <xsd:annotation>
    <xsd:documentation>To identify a composite unit of measure(See Figures Appendix for examples of use)</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code" type="E_355_1"/>
    <xsd:element name="E_Exponent" type="E_1018" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Multiplier" type="E_649" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code_1" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Exponent_1" type="E_1018" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Multiplier_1" type="E_649" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code_2" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Exponent_2" type="E_1018" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Multiplier_2" type="E_649" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code_3" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Exponent_3" type="E_1018" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Multiplier_3" type="E_649" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Unit_or_Basis_for_Measurement_Code_4" type="E_355" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Exponent_4" type="E_1018" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Multiplier_4" type="E_649" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Composite"/>
  <xsd:attribute name="ID" type="xsd:string" default="C001"/>
  <xsd:attribute name="Name" type="xsd:string" default="Composite Unit of Measure"/>
</xsd:complexType>
<xsd:complexType name="E_355_1">
  <xsd:annotation>
    <xsd:documentation>Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
```



```
<xsd:attribute name="ID" type="xsd:string" fixed="355"/>
<xsd:attribute name="Name" type="xsd:string" fixed="Unit or Basis for Measurement Code"/>
</xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_1018">
<xsd:annotation>
  <xsd:documentation>Power to which a unit is raised</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_649">
<xsd:annotation>
  <xsd:documentation>Value to be used as a multiplier to obtain a new value</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_61">
<xsd:annotation>
  <xsd:documentation>Free-form information</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="S_DTM">
<xsd:annotation>
  <xsd:documentation>To specify pertinent dates and times</xsd:documentation>
</xsd:annotation>
<xsd:sequence>
  <xsd:element name="E_Date_Time_Qualifier" type="E_374"/>
  <xsd:element name="E_Date" type="E_373"/>
  <xsd:element name="E_Time" type="E_337_1" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Time_Code" type="E_623" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Date_Time_Period_Format_Qualifier" type="E_1250" nillable="true" minOccurs="0"/>
  <xsd:element name="E_Date_Time_Period" type="E_1251" nillable="true" minOccurs="0"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="DTM"/>
<xsd:attribute name="Name" type="xsd:string" default="Date/Time Reference"/>
</xsd:complexType>
<xsd:complexType name="E_374">
<xsd:annotation>
  <xsd:documentation>Code specifying type of date or time, or both date and time</xsd:documentation>
</xsd:annotation>
<xsd:simpleContent>
  <xsd:restriction base="EDI-Element-String-Type">
    <xsd:enumeration value="036"/>
    <xsd:enumeration value="168"/>
    <xsd:enumeration value="510"/>
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="374"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Date/Time Qualifier"/>
  </xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_1250">
<xsd:annotation>
  <xsd:documentation>Code indicating the date format, time format, or date and time format</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="E_1251">
<xsd:annotation>
  <xsd:documentation>Expression of a date, a time, or range of dates, times or dates and times</xsd:documentation>
</xsd:annotation>
<xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
```



```
<xsd:complexType name="L_LM_1">
  <xsd:annotation>
    <xsd:documentation>To transmit standard code list identification information</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="S_Code_Source_Information" type="S_LM"/>
    <xsd:element name="S_Industry_Code" type="S_LQ_1" maxOccurs="100"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
  <xsd:attribute name="ID" type="xsd:string" default="LM"/>
  <xsd:attribute name="Name" type="xsd:string" default="Code Source Information"/>
</xsd:complexType>
<xsd:complexType name="S_LQ_1">
  <xsd:annotation>
    <xsd:documentation>Code to transmit standard industry codes</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Code_List_Qualifier_Code" type="E_1270_1"/>
    <xsd:element name="E_Industry_Code" type="E_1271"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="LQ"/>
  <xsd:attribute name="Name" type="xsd:string" default="Industry Code"/>
</xsd:complexType>
<xsd:complexType name="E_1270_1">
  <xsd:annotation>
    <xsd:documentation>Code identifying a specific industry code list</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="83"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="1270"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Code List Qualifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="L_LX">
  <xsd:annotation>
    <xsd:documentation>To reference a line number in a transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="S_Assigned_Number" type="S_LX"/>
    <xsd:element name="S_Reference_Identification" type="S_N9_1" nillable="true" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="S_Name" type="S_N1_2" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
  <xsd:attribute name="ID" type="xsd:string" default="LX"/>
  <xsd:attribute name="Name" type="xsd:string" default="Assigned Number"/>
</xsd:complexType>
<xsd:complexType name="S_LX">
  <xsd:annotation>
    <xsd:documentation>To reference a line number in a transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Assigned_Number" type="E_554"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="LX"/>
  <xsd:attribute name="Name" type="xsd:string" default="Assigned Number"/>
</xsd:complexType>
<xsd:complexType name="E_554">
  <xsd:annotation>
    <xsd:documentation>Number assigned for differentiation within a transaction set</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>

```



```
<xsd:restriction base="EDI-Element-Integer-Type">
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="N0"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="554"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Assigned Number"/>
</xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="S_N9_1">
    <xsd:annotation>
        <xsd:documentation>To transmit identifying information as specified by the Reference Identification Qualifier</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="E_Reference_Identification_Qualifier" type="E_128_3"/>
        <xsd:element name="E_Reference_Identification" type="E_127"/>
        <xsd:element name="E_Free-form_Description" type="E_369" nillable="true" minOccurs="0"/>
        <xsd:element name="E_Date" type="E_373_1" nillable="true" minOccurs="0"/>
        <xsd:element name="E_Time" type="E_337_1" nillable="true" minOccurs="0"/>
        <xsd:element name="E_Time_Code" type="E_623" nillable="true" minOccurs="0"/>
        <xsd:element name="C_Reference_Identifier" type="C_C040_1" nillable="true" minOccurs="0"/>
    </xsd:sequence>
    <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
    <xsd:attribute name="ID" type="xsd:string" default="N9"/>
    <xsd:attribute name="Name" type="xsd:string" default="Reference Identification"/>
</xsd:complexType>
<xsd:complexType name="E_128_3">
    <xsd:annotation>
        <xsd:documentation>Code qualifying the Reference Identification</xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:restriction base="EDI-Element-String-Type">
            <xsd:enumeration value="BT"/>
            <xsd:enumeration value="LT"/>
            <xsd:enumeration value="SE"/>
            <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
            <xsd:attribute name="ID" type="xsd:string" fixed="128"/>
            <xsd:attribute name="Name" type="xsd:string" fixed="Reference Identification Qualifier"/>
        </xsd:restriction>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="C_C040_1">
    <xsd:annotation>
        <xsd:documentation>To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="E_Reference_Identification_Qualifier" type="E_128_4"/>
        <xsd:element name="E_Reference_Identification" type="E_127_2"/>
        <xsd:element name="E_Reference_Identification_Qualifier_1" type="E_128_4"/>
        <xsd:element name="E_Reference_Identification_1" type="E_127_2"/>
        <xsd:element name="E_Reference_Identification_Qualifier_2" type="E_128_4"/>
        <xsd:element name="E_Reference_Identification_2" type="E_127_2"/>
    </xsd:sequence>
    <xsd:attribute name="Type" type="xsd:string" default="Composite"/>
    <xsd:attribute name="ID" type="xsd:string" default="C040"/>
    <xsd:attribute name="Name" type="xsd:string" default="Reference Identifier"/>
</xsd:complexType>
<xsd:complexType name="E_128_4">
    <xsd:annotation>
        <xsd:documentation>Code qualifying the Reference Identification</xsd:documentation>
    </xsd:annotation>
</xsd:complexType>
<xsd:complexType name="E_127_2">
    <xsd:annotation>
        <xsd:documentation>Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier</xsd:documentation>
    </xsd:annotation>
</xsd:complexType>
```



```
</xsd:complexType>
<xsd:complexType name="S_N1_2">
  <xsd:annotation>
    <xsd:documentation>To identify a party by type of organization, name, and code</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Entity_Identifier_Code" type="E_98_4"/>
    <xsd:element name="E_Name" type="E_93" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Identification_Code_Qualifier" type="E_66_2"/>
    <xsd:element name="E_Identification_Code" type="E_67"/>
    <xsd:element name="E_Entity_Relationship_Code" type="E_706" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Entity_Identifier_Code_1" type="E_98_5" nillable="true" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="N1"/>
  <xsd:attribute name="Name" type="xsd:string" default="Name"/>
</xsd:complexType>
<xsd:complexType name="E_98_4">
  <xsd:annotation>
    <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="MF"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="98"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Entity Identifier Code"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_66_2">
  <xsd:annotation>
    <xsd:documentation>Code designating the system/method of code structure used for Identification Code (67)</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:enumeration value="33"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="66"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Identification Code Qualifier"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_98_5">
  <xsd:annotation>
    <xsd:documentation>Code identifying an organizational entity, a physical location, property or an individual</xsd:documentation>
  </xsd:annotation>
  <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="L_FA1">
  <xsd:annotation>
    <xsd:documentation>To specify the organization controlling the content of the accounting citation, and the purpose associated with the accounting citation</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="S_Type_of_Financial_Accounting_Data" type="S_FA1"/>
    <xsd:element name="S_Accounting_Data" type="S_FA2" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Loop"/>
  <xsd:attribute name="ID" type="xsd:string" default="FA1"/>
  <xsd:attribute name="Name" type="xsd:string" default="Type of Financial Accounting Data"/>
</xsd:complexType>
<xsd:complexType name="S_FA1">
  <xsd:annotation>
    <xsd:documentation>To specify the organization controlling the content of the accounting citation, and the purpose associated with the accounting citation</xsd:documentation>
  </xsd:annotation>
```



```

</xsd:annotation>
<xsd:sequence>
    <xsd:element name="E_Agency_Qualifier_Code" type="E_559_1"/>
    <xsd:element name="E_Service__Promotion__Allowance__or_Charge_Code" type="E_1300" nillable="true" minOccurs="0"/>
    <xsd:element name="E_Allowance_or_Charge_Indicator" type="E_248" nillable="true" minOccurs="0"/>
</xsd:sequence>
<xsd:attribute name="Type" type="xsd:string" default="Segment"/>
<xsd:attribute name="ID" type="xsd:string" default="FA1"/>
<xsd:attribute name="Name" type="xsd:string" default="Type of Financial Accounting Data"/>
</xsd:complexType>
<xsd:complexType name="E_559_1">
    <xsd:annotation>
        <xsd:documentation>Code identifying the agency assigning the code values</xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:restriction base="EDI-Element-String-Type">
            <xsd:enumeration value="DF"/>
            <xsd:enumeration value="DN"/>
            <xsd:enumeration value="DY"/>
            <xsd:enumeration value="DZ"/>
            <xsd:enumeration value="FG"/>
            <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
            <xsd:attribute name="ID" type="xsd:string" fixed="559"/>
            <xsd:attribute name="Name" type="xsd:string" fixed="Agency Qualifier Code"/>
        </xsd:restriction>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_1300">
    <xsd:annotation>
        <xsd:documentation>Code identifying the service, promotion, allowance, or charge</xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:restriction base="EDI-Element-String-Type">
            <xsd:enumeration value="A170"/>
            <xsd:enumeration value="A520"/>
            <xsd:enumeration value="C930"/>
            <xsd:enumeration value="D340"/>
            <xsd:enumeration value="F060"/>
            <xsd:enumeration value="F560"/>
            <xsd:enumeration value="I260"/>
            <xsd:enumeration value="R060"/>
            <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
            <xsd:attribute name="ID" type="xsd:string" fixed="1300"/>
            <xsd:attribute name="Name" type="xsd:string" fixed="Service, Promotion, Allowance, or Charge Code"/>
        </xsd:restriction>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_248">
    <xsd:annotation>
        <xsd:documentation>Code which indicates an allowance or charge for the service specified</xsd:documentation>
    </xsd:annotation>
    <xsd:attribute name="Type" type="xsd:string" default="Element"/>
</xsd:complexType>
<xsd:complexType name="S_FA2">
    <xsd:annotation>
        <xsd:documentation>To specify the detailed accounting data</xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="E_Breakdown_Structure_Detail_Code" type="E_1196"/>
        <xsd:element name="E_Financial_Information_Code" type="E_1195"/>
    </xsd:sequence>
    <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
    <xsd:attribute name="ID" type="xsd:string" default="FA2"/>
    <xsd:attribute name="Name" type="xsd:string" default="Accounting Data"/>
</xsd:complexType>
<xsd:complexType name="E_1196">

```



```
<xsd:annotation>
  <xsd:documentation>Codes identifying details relating to a reporting breakdown structure tree</xsd:documentation>
</xsd:annotation>
<xsd:simpleContent>
  <xsd:restriction base="EDI-Element-String-Type">
    <xsd:enumeration value="18"/>
    <xsd:enumeration value="A1"/>
    <xsd:enumeration value="A2"/>
    <xsd:enumeration value="A3"/>
    <xsd:enumeration value="A4"/>
    <xsd:enumeration value="A5"/>
    <xsd:enumeration value="A6"/>
    <xsd:enumeration value="B1"/>
    <xsd:enumeration value="B2"/>
    <xsd:enumeration value="B5"/>
    <xsd:enumeration value="BL"/>
    <xsd:enumeration value="C1"/>
    <xsd:enumeration value="C2"/>
    <xsd:enumeration value="C3"/>
    <xsd:enumeration value="D1"/>
    <xsd:enumeration value="D2"/>
    <xsd:enumeration value="D3"/>
    <xsd:enumeration value="D4"/>
    <xsd:enumeration value="D5"/>
    <xsd:enumeration value="D6"/>
    <xsd:enumeration value="D7"/>
    <xsd:enumeration value="E1"/>
    <xsd:enumeration value="E2"/>
    <xsd:enumeration value="E3"/>
    <xsd:enumeration value="F1"/>
    <xsd:enumeration value="F2"/>
    <xsd:enumeration value="F3"/>
    <xsd:enumeration value="F4"/>
    <xsd:enumeration value="G1"/>
    <xsd:enumeration value="G2"/>
    <xsd:enumeration value="H1"/>
    <xsd:enumeration value="H2"/>
    <xsd:enumeration value="H3"/>
    <xsd:enumeration value="H4"/>
    <xsd:enumeration value="I1"/>
    <xsd:enumeration value="J1"/>
    <xsd:enumeration value="L1"/>
    <xsd:enumeration value="N1"/>
    <xsd:enumeration value="P1"/>
    <xsd:enumeration value="P2"/>
    <xsd:enumeration value="P3"/>
    <xsd:enumeration value="ZZ"/>
    <xsd:attribute name="EDIDataType" type="xsd:string" fixed="ID"/>
    <xsd:attribute name="ID" type="xsd:string" fixed="1196"/>
    <xsd:attribute name="Name" type="xsd:string" fixed="Breakdown Structure Detail Code"/>
  </xsd:restriction>
</xsd:simpleContent>
</xsd:complexType>
<xsd:complexType name="E_1195">
  <xsd:annotation>
    <xsd:documentation>Code representing financial accounting information</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="80"/>
      <xsd:minLength value="1"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="AN"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="1195"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Financial Information Code"/>
    </xsd:restriction>
  </xsd:simpleContent>

```



```
</xsd:complexType>
<xsd:complexType name="S_SE">
  <xsd:annotation>
    <xsd:documentation>To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)</xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="E_Number_of_Included_Segments" type="E_96"/>
    <xsd:element name="E_Transaction_Set_Control_Number" type="E_329"/>
  </xsd:sequence>
  <xsd:attribute name="Type" type="xsd:string" default="Segment"/>
  <xsd:attribute name="ID" type="xsd:string" default="SE"/>
  <xsd:attribute name="Name" type="xsd:string" default="Transaction Set Trailer"/>
</xsd:complexType>
<xsd:complexType name="E_96">
  <xsd:annotation>
    <xsd:documentation>Total number of segments included in a transaction set including ST and SE segments</xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:restriction base="EDI-Element-String-Type">
      <xsd:maxLength value="10"/>
      <xsd:minLength value="1"/>
      <xsd:attribute name="EDIDataType" type="xsd:string" fixed="N0"/>
      <xsd:attribute name="ID" type="xsd:string" fixed="96"/>
      <xsd:attribute name="Name" type="xsd:string" fixed="Number of Included Segments"/>
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
</xsd:schema>
```