

870 Order Status Report

Functional Group=RS

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Order Status Report Transaction Set (870) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to report on the current status of a requirement forecast, an entire purchase order, selected line items on a purchase order, selected products/services on a purchase order, or purchase orders for a specific customer in their entirety or on a selection basis. The transaction set can also be used to report on the current status of single or multiple requisitions. The report format allows for the inclusion of "reasons" relative to the status. This transaction set may also be used to update the supplier's scheduled shipment or delivery dates. This transaction set can result from either an inquiry or a prearranged schedule agreed to by the trading partners.

DLMS Note:

1. *Country Representatives/Freight Forwarders (CRs/FFs) use this transaction set to respond to a Foreign Military Sales (FMS) Notice of Availability (NOA) providing shipment instructions for materiel reported available for shipment.*
2. *Users operating under the Defense Logistics Management Standards (DLMS) must reference DoD/ASC X12 Conversion Guides for Unit of Materiel Measure, Type of Pack and Transportation Method/Type Code, which can be found on the Defense Enterprise Data Standards Office (DEDSO) Website at www.dla.mil/does/DLMS.*
3. *This DLMS Implementation Convention (IC) contains:*
 - a. *Data associated with a DLMS enhancement which may not be received or understood by the recipient's automated processing system. DLMS procedures may not have been developed. Components must coordinate requirements and business rules with DEDSO prior to use.*
 - b. *Data associated with an Approved Change which may not have an established implementation date. This data may not be received or understood by the recipient's automated processing system. Components must coordinate implementation with DEDSO prior to use.*
 - c. *Legacy MILSTRIP data which must be retained in the DLMS for a transition period to support transaction conversion in a mixed legacy MILSTRIP/DLMS environment. This data will be streamlined out once full DLMS implementation is reached. Components may coordinate with DEDSO for early termination (or retention) of specific data requirements for users operating in a full DLMS environment.*
 - d. *Data elements which have an expanded files size above existing legacy MILSTRIP capability which may not be supported by the recipient's automated processing system. Components must coordinate implementation with DEDSO prior to use.*
 - e. *Data associated with a DLMS enhancement authorized for implementation by modernized systems under DLMS migration. This data (including expanded field sizes) should be adopted during, or subsequent to, modernization when applicable to the Component's business process. Prior coordination is not required. Components should ensure that inclusion of this data in a DLMS transaction does not cause inappropriate rejection of the transaction.*
4. *Effective April 1, 2014, refer to ADC 1075. Users must reference the GENC Standard for country codes (<https://nsgreg.nga.mil/gencc/discovery>) for a listing of authorized values. Under DLMS, use the GENC Digraph (two-character).*
5. *This revision to the DLMS IC incorporates Proposed DLMS Changes (PDCs) and Approved DLMS Changes (ADCs) listed. PDCs and ADCs are available from the DEDSO Web site: <http://www.dla.mil/HQ/InformationOperations/DLMS/eLibrary/Changes/processchanges/>*
 - ADC 309, NOA and NOA Reply Transaction Data Content/Mapping including Addition of Type Pack Code for 463L Pallets
 - ADC 436, Administrative Revisions to DLMS Supplements to Remove Obsolete Routing Identifier Code (RIC) "Streamline" Notes and Update MILSTRIP/DLMS Documentation Associated with Routing Identifiers
 - ADC 448, Implementation of International Organization for Standardization (ISO) 3166-1 Codes for the Identification of Countries and their Subdivisions
 - ADC 448B, Delayed implementation for International Organization for Standardization (ISO) 3166-1 Codes for the Identification of Countries and their Subdivisions
 - Organizational Name and Other Non-Substantive (Administrative) Updates Completed on June 05, 2014
 - ADC 1043C, Administrative Corrections for SLOA Data in the 810L Logistics Bill and other DLMS ICs
 - ADC 1098, Updates to DD Form 1348-5 Notice of Availability (NOA) and Corresponding DLMS 856N NOA and 870N NOA Reply
 - Administrative Update to Reflect Realignment of DLMS Program Office to Enterprise Business Standards Office (EBSO) - Completed on April 21, 2020
 - ADC 1353, Transportation Method and Transportation Mode Codes on all DLMS ICs
 - ADC 1367, Administrative Update to Convert Federal Notes to DLMS Notes within DLMS Implementation Conventions
 - ADC 1370, Administrative Update to Change Data Element N106 Usage from Must Use to Used
 - Administrative Update to Reflect Realignment of Enterprise Business Standards Office (EBSO) to Defense Enterprise Data Standards Office (DEDSO) - Completed on March 16, 2022
 - ADC 1412, Replacement of Data Universal Numbering System Number with Unique Entity Identifier and Electronic Funds Transfer Indicator to Wide Area Workflow
 - ADC 1503, DLMS Implementation Convention Notes Updates_MFR

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
10	ST	Transaction Set Header	M	1			Must use
20	BSR	Beginning Segment for Order Status Report	M	1			Must use
* 42	TD3	Carrier Details (Equipment)	O	1			Not Used
* 43	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1			Not Used
44	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Used
* 45	DTM	Date/Time Reference	O	10			Not Used
* LOOP ID - REF					≥1		
* 46	REF	Reference Identification	O	1			Not Used
* 47	DTM	Date/Time Reference	O	>1			Not Used
LOOP ID - N1					200		
50	N1	Name	O	1			Must use
* 60	N2	Additional Name Information	O	2			Not Used
* 70	N3	Address Information	O	2			Not Used
* 80	N4	Geographic Location	O	1			Not Used
* 90	REF	Reference Identification	O	12			Not Used
* 100	PER	Administrative Communications Contact	O	3			Not Used
* 105	PWK	Paperwork	O	1			Not Used
* LOOP ID - LM					10		
* 120	LM	Code Source Information	O	1			Not Used
130	LQ	Industry Code	M	100			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					1000		
10	HL	Hierarchical Level	M	1			Must use
* 20	PRF	Purchase Order Reference	O	1			Not Used
* LOOP ID - ISR					104		
* 30	ISR	Item Status Report	O	1			Not Used
* 40	PID	Product/Item Description	O	6			Not Used
* 50	QTY	Quantity	O	4			Not Used
* 70	PER	Administrative Communications Contact	O	3			Not Used
80	DTM	Date/Time Reference	O	10			Used
* 86	CS	Contract Summary	O	3		N2/86	Not Used
LOOP ID - REF					≥1		
87	REF	Reference Identification	O	1			Must use
* 88	DTM	Date/Time Reference	O	>1			Not Used
LOOP ID - N1					200		
90	N1	Name	O	1			Must use
100	N2	Additional Name Information	O	2			Used
110	N3	Address Information	O	2			Used
120	N4	Geographic Location	O	1			Used
* 130	REF	Reference Identification	O	12			Not Used
140	PER	Administrative Communications Contact	O	3			Used
LOOP ID - LM					10		
144	LM	Code Source Information	O	1			Used
145	LQ	Industry Code	M	100			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
* LOOP ID - PO1					1000		
* 150	PO1	Baseline Item Data	O	1			Not Used
* 155	CUR	Currency	O	1			Not Used
* 160	SLN	Subline Item Detail	O	100			Not Used
* 170	PO3	Additional Item Detail	O	1			Not Used
* 180	PID	Product/Item Description	O	1000			Not Used
* 190	MEA	Measurements	O	40			Not Used
* 200	PKG	Marking, Packaging, Loading	O	25			Not Used
* LOOP ID - ISR					104		
* 210	ISR	Item Status Report	O	1			Not Used
* 220	PID	Product/Item Description	O	6			Not Used
* 230	QTY	Quantity	O	4			Not Used
* 240	DTM	Date/Time Reference	O	10			Not Used
* 250	N1	Name	O	1			Not Used
* 251	N2	Additional Name Information	O	2			Not Used
* 252	N3	Address Information	O	2			Not Used
* 253	N4	Geographic Location	O	1			Not Used
* 260	TD1	Carrier Details (Quantity and Weight)	O	1			Not Used
* 270	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Not Used
* 280	TD3	Carrier Details (Equipment)	O	1			Not Used
* 290	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1			Not Used
* 300	REF	Reference Identification	O	12			Not Used
* 310	SAC	Service, Promotion, Allowance, or Charge Information	O	25			Not Used
* LOOP ID - LM					10		
* 320	LM	Code Source Information	O	1			Not Used
330	LQ	Industry Code	M	100			Must use
* LOOP ID - LX					>1	N2/340L	
* 340	LX	Assigned Number	O	1		N2/340	Not Used
* 350	REF	Reference Identification	O	>1			Not Used
* 360	N1	Name	O	1			Not Used
* 370	DTM	Date/Time Reference	O	10			Not Used
* LOOP ID - LM					10		
* 380	LM	Code Source Information	O	1			Not Used
390	LQ	Industry Code	M	100			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
* 10	CTT	Transaction Totals	O	1		N3/10	Not Used
20	SE	Transaction Set Trailer	M	1			Must use

Notes:

2/86 Use is limited to intra-organizational transactions.

2/340L The LX loop conveys serial number, lot number, and inventory data.

2/340 The LX loop conveys serial number, lot number, and inventory data.

3/10 The number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

ST Transaction Set Header

Pos: 10

Max: 1

Heading - Mandatory

Loop: N/A

Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use	1
Description: Code uniquely identifying a Transaction Set							
Code Name							
870 Order Status Report							
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use	1
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set							

BSR Beginning Segment for Order Status Report

Pos: 20Max: 1

Heading - Mandatory

Loop: N/AElements: 6

User Option (Usage): Must use

Purpose: To indicate the beginning of an Order Status Report Transaction Set

Semantics:

- 1. BSR03 indicates a status report document number assigned by the sender.
- 2. BSR04 indicates the date of this report from the sender.
- 3. BSR07 indicates the time of this report from the sender.
- 4. BSR08 indicates a status report document number assigned by the inquirer.
- 5. BSR09 indicates the date this report was requested from the sender by the inquirer.
- 6. BSR10 indicates the time this report was requested from the sender by the inquirer.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
BSR01	850	Status Report Code	M	ID	1/2	Must use	1
<div>Description: Code indicating the reason for sending the report</div> <div>Code Name</div> <div>8Response to Notice of Availability</div>							
BSR02	847	Order/Item Code	M	ID	1/2	Must use	1
<div>Description: Code identifying a group of orders and items</div> <div>Code Name</div> <div>COAll Orders - Unshipped Items</div> <div>DLMS Note: Use to indicate that all orders remain open.</div>							
BSR03	127	Reference Identification	M	AN	1/30	Must use	1
<div>Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier</div> <div>DLMS Note: Use Code "Z" for this data element to satisfy mandatory X12 syntax requirements.</div>							
BSR04	373	Date	M	DT	8/8	Must use	1
<div>Description: Date expressed as CCYYMMDD</div> <div>DLMS Note: This date is the date of the transaction set preparation and corresponds to the Universal Time Coordinate (UTC).</div>							
BSR07	337	Time	O	TM	4/8	Must use	1
<div>Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD =</div>							

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
		hundredths (00-99)					
		DLMS Note: 1. Express the originating activity's time of transaction set preparation in UTC.					
		2. Express time in a four-position (HHMM) format.					
BSR11	353	Transaction Set Purpose Code	O	ID	2/2	Must use	1
		Description: Code identifying purpose of transaction set					
		<u>Code</u>	<u>Name</u>				
		00	Original				
		77	Simulation Exercise				
		DLMS Note: Activities initiating simulated mobilization exercises must ensure complete coordination with all activities involved. All transaction set recipients must use caution to ensure that transactions do not process as action documents which affect accountable records.					

TD5Carrier Details (Routing Sequence/Transit Time)

Pos: 44Max: 1

Heading - Optional

Loop: N/AElements: 5

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

- Syntax Rules:
- 1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
 - 2. C0203 - If TD502 is present, then TD503 is required.
 - 3. C0708 - If TD507 is present, then TD508 is required.
 - 4. C1011 - If TD510 is present, then TD511 is required.
 - 5. C1312 - If TD513 is present, then TD512 is required.
 - 6. C1413 - If TD514 is present, then TD513 is required.
 - 7. C1512 - If TD515 is present, then TD512 is required.

- Semantics:
- 1. TD515 is the country where the service is to be performed.

- Comments:
- 1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

DLMS Note:

Use to identify the ship mode (air or surface) to the final destination, the port of embarkation and the port of debarkation. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
TD502	66	Identification Code Qualifier	O	ID	1/2	Used	1
Description: Code designating the system/method of code structure used for Identification Code (67)							
<u>Code</u> <u>Name</u>							
7 Loading Dock							
DLMS Note: <i>Use to identify the Port of Embarkation (DOD Code) associated with the ship mode (air or surface) to final destination.</i>							
TD503	67	Identification Code	O	AN	2/80	Used	1
Description: Code identifying a party or other code							
TD504	91	Transportation Method/Type Code	O	ID	1/2	Used	1
Description: Code specifying the method or type of transportation for the shipment							
DLMS Note: <i>DLMS users see the Transportation Method/Type Code Conversion Guide for available codes.</i>							
TD507	309	Location Qualifier	O	ID	1/2	Used	1
Description: Code identifying type of location							

Code	Name
PB	Port of Discharge
DLMS Note: <i>Use to identify the Port of Debarkation (DOD Code) associated with the ship mode (air or surface) to final destination.</i>	

TD508	310	Location Identifier	O	AN	1/30	Used	1
-------	-----	---------------------	---	----	------	------	---

Description: Code which identifies a specific location

N1	Name	Pos: 50	Max: 1
		Heading - Optional	
		Loop: N1	Elements: 5

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

- Syntax Rules:**
- 1. R0203 - At least one of N102 or N103 is required.
 - 2. P0304 - If either N103 or N104 is present, then the other is required.

- Comments:**
- 1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 - 2. N105 and N106 further define the type of entity in N101.

- DLMS Note:**
- 1. Must use this N1 loop to identify the organization originating the transaction set.
 - 2. Use additional iterations to identify other organizations associated with the transaction.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
N101	98	Entity Identifier Code	M	ID	2/3	Must use	1
Description: Code identifying an organizational entity, a physical location, property or an individual							
DLMS Note: 1. Use only one of code IF or CY.							
2. For conversion between MILS and DLMS formats, the transaction originator will always be identified by Qualifier CY using the SC Customer Code.							
3. Identification of the Freight Forwarder (FF) or Country Representative (CR) are identified as an Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098. Use of this enhancement requires a second iteration of the N1 loop (refer to ADC 309).							
Code Name							
CY Country							
DLMS Note:							
1. Use to identify the SC Customer Code associated with the NOA reply.							
2. Use to identify the CR originating the transaction set. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.							
IF International Freight Forwarder							
DLMS Note:							
Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.							
N102	93	Name	X	AN	1/60	Used	1
Description: Free-form name							
DLMS Note: This is a DLMS enhancement for identification of the FF or CR by clear text where coded address is not available.							
N103	66	Identification Code Qualifier	X	ID	1/2	Must use	1

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
Description: Code designating the system/method of code structure used for Identification Code (67)							
Code Name							
	38	Country Code	DLMS Note: <i>Use with N101 Qualifier CY to identify the Security Cooperation Customer Code applicable to the NOA reply. (Must be consistent with the NOA and original requisition content).</i>				
	A2	Military Assistance Program Address Code (MAPAC)	DLMS Note: <i>This is a DLMS enhancement for use of the constructed MAPAC to identify the FF or CR. Requires coordination prior to use.</i>				
	LC	Agency Location Code (U.S. Government)	DLMS Note: <i>Use to identify the International Logistics Control Office (ILCO) SC Implementing Agency Code. Authorized values are restricted to those identified in DLM 4000.25, Volume 2 Appendix 7.2. Authorized DLMS enhancement; see DLMS Introductory Note 4e. Refer to ADC 1098.</i>				
N104	67	Identification Code	X	AN	2/80	Must use	1
Description: Code identifying a party or other code							
N106	98	Entity Identifier Code	O	ID	2/3	Used	1
Description: Code identifying an organizational entity, a physical location, property or an individual							
Code Name							
	FR	Message From	DLMS Note: <i>Must use with the appropriate 1/N101/050 code to indicate that the organization cited in N104 is originating the transaction set.</i>				

HL Hierarchical Level

Pos: 10

Max: 1

Detail - Mandatory

Loop: HL

Elements: 2

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

- Comments:**
1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
 2. The HL segment defines a top-down/left-right ordered structure.
 3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
 4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
 5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
 6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

DLMS Note:

1. The transaction set hierarchical data structure is address information, followed by overall shipment information.

2. Use the first 2/HL/010 loop iteration to provide transaction set address information.

3. Use the second 2/HL/010 shipment loop iteration to identify shipment information associated with the transportation control number assigned to control the shipment.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use	1
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure							
DLMS Note: In the first 2/HL/010 loop iteration, cite numeric 1. In each subsequent loop iteration, increase incrementally by 1.							
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use	1
Description: Code defining the characteristic of a level in a hierarchical structure							
Code Name							
S Shipment							
DLMS Note:							
Use to identify the individual shipment loops addressed in the FMS NOA reply.							
V Address Information							
DLMS Note:							
Use address loop to identify the consignor (shipping activity initiating the NOA) and the ship-to when the ship-to instructions are different than those provided originally.							

DTM Date/Time Reference

Pos: 80 Max: 10

Detail - Optional

Loop: HL Elements: 2

User Option (Usage): Used

Purpose: To specify pertinent dates and times

- Syntax Rules:
- 1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
 - 2. C0403 - If DTM04 is present, then DTM03 is required.
 - 3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use	1
Description: Code specifying type of date or time, or both date and time							
Code Name							
097 Transaction Creation							
DLMS Note:							
<i>Use to indicate the date of transaction preparation.</i>							
108 Postmark							
DLMS Note:							
<i>Use to identify the date release and shipping instructions were mailed. Use only when mailing separate release and shipping instructions.</i>							
DTM02	373	Date	X	DT	8/8	Must use	1
Description: Date expressed as CCYYMMDD							

REFReference Identification

Pos: 87Max: 1

Detail - Optional

Loop: REFElements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use	1
Description: Code qualifying the Reference Identification							
Code Name							
FN Forwarder's/Agent's Reference Number							
DLMS Note: Use to identify the customer (CR/FF) assigned transportation order number used for internal control of the shipment.							
K1 Foreign Military Sales Notice Number							
DLMS Note: Must use only in 2/HL/010 shipment loops to identify the NOA Notice number, which reflects the number of times the NOA has been sent to the Freight Forwarder/Country Representative. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.							
LO Load Planning Number							
DLMS Note: Use to identify the number of transactions included in the shipment.							
TG Transportation Control Number (TCN)							
DLMS Note: Must use only in 2/HL/010 shipment loops to identify the number assigned to control the shipment between the shipper and consignee.							
REF02	127	Reference Identification	X	AN	1/30	Must use	1
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier							

N1	Name	Pos: 90	Max: 1
		Detail - Optional	
		Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

- Syntax Rules:
1. R0203 - At least one of N102 or N103 is required.
 2. P0304 - If either N103 or N104 is present, then the other is required.

- Comments:
1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2. N105 and N106 further define the type of entity in N101.

DLMS Note:

Must use this 2/N1/090 loop to identify the organization to receive the transaction.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep																
N101	98	Entity Identifier Code	M	ID	2/3	Must use	1																
Description: Code identifying an organizational entity, a physical location, property or an individual																							
<table><tr><th>Code</th><th>Name</th></tr><tr><td>CI</td><td>Consignor</td></tr></table>								Code	Name	CI	Consignor												
Code	Name																						
CI	Consignor																						
<table><tr><td colspan="8">DLMS Note:</td></tr><tr><td colspan="8"><i>Use to indicate the shipping activity (activity initiating the NOA).</i></td></tr></table>								DLMS Note:								<i>Use to indicate the shipping activity (activity initiating the NOA).</i>							
DLMS Note:																							
<i>Use to indicate the shipping activity (activity initiating the NOA).</i>																							
<table><tr><td>ST</td><td>Ship To</td></tr></table>								ST	Ship To														
ST	Ship To																						
<table><tr><td colspan="8">DLMS Note:</td></tr><tr><td colspan="8"><i>Use to identify the ship to clear text address with or without the MAPAC when the ship to address is different than what is contained in the MAPAD as originally identified by the address codes in the requisition.</i></td></tr></table>								DLMS Note:								<i>Use to identify the ship to clear text address with or without the MAPAC when the ship to address is different than what is contained in the MAPAD as originally identified by the address codes in the requisition.</i>							
DLMS Note:																							
<i>Use to identify the ship to clear text address with or without the MAPAC when the ship to address is different than what is contained in the MAPAD as originally identified by the address codes in the requisition.</i>																							
N103	66	Identification Code Qualifier	X	ID	1/2	Must use	1																
Description: Code designating the system/method of code structure used for Identification Code (67)																							
<table><tr><th>Code</th><th>Name</th></tr><tr><td>10</td><td>Department of Defense Activity Address Code (DODAAC)</td></tr><tr><td>A2</td><td>Military Assistance Program Address Code (MAPAC)</td></tr></table>								Code	Name	10	Department of Defense Activity Address Code (DODAAC)	A2	Military Assistance Program Address Code (MAPAC)										
Code	Name																						
10	Department of Defense Activity Address Code (DODAAC)																						
A2	Military Assistance Program Address Code (MAPAC)																						
<table><tr><td colspan="8">DLMS Note:</td></tr><tr><td colspan="8"><i>Use to identify Security Assistance structured address data for the Ship To. Interpretation of this data may require additional codes cited elsewhere in the transaction. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.</i></td></tr></table>								DLMS Note:								<i>Use to identify Security Assistance structured address data for the Ship To. Interpretation of this data may require additional codes cited elsewhere in the transaction. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.</i>							
DLMS Note:																							
<i>Use to identify Security Assistance structured address data for the Ship To. Interpretation of this data may require additional codes cited elsewhere in the transaction. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.</i>																							
<table><tr><td>M4</td><td>Department of Defense Routing Identifier Code (RIC)</td></tr></table>								M4	Department of Defense Routing Identifier Code (RIC)														
M4	Department of Defense Routing Identifier Code (RIC)																						
N104	67	Identification Code	X	AN	2/80	Must use	1																
Description: Code identifying a party or other code																							
N106	98	Entity Identifier Code	O	ID	2/3	Used	1																
Description: Code identifying an organizational entity, a physical location, property or an individual																							

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
		<u>Code</u> <u>Name</u>					
	TO	Message To					
		DLMS Note: <i>Must use with N101 code CI to indicate that the organization cited in N104 is receiving the transaction set.</i>					

N2Additional Name Information

Pos: 100Max: 2

Detail - Optional

Loop: N1Elements: 2

User Option (Usage): Used

Purpose: To specify additional names or those longer than 35 characters in length

DLMS Note:

Use with 2/N101/90 Code ST to identify in-the-clear exception ship-to name information if different than what is contained in the MAPAD as originally identified by the address codes in the requisition. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
N201	93	Name	M	AN	1/60	Must use	1
		Description: Free-form name					
N202	93	Name	O	AN	1/60	Used	1
		Description: Free-form name					

N3Address Information

Pos: 110Max: 2

Detail - Optional

Loop: N1Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

DLMS Note:

Use with 2/N101/90 Code ST to identify in-the-clear exception ship-to address information if different than what is contained in the MAPAD as originally identified by the address codes in the requisition. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.

Element Summary:							
Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
N301	166	Address Information	M	AN	1/55	Must use	1
		Description: Address information					
N302	166	Address Information	O	AN	1/55	Used	1
		Description: Address information					

N4Geographic Location

Pos: 120Max: 1

Detail - Optional

Loop: N1Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

- Syntax Rules:
1. C0605 - If N406 is present, then N405 is required.

- Comments:
1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
 2. N402 is required only if city name (N401) is in the U.S. or Canada.

DLMS Note:

Use with 2/N101/90 Code ST to identify in-the-clear exception ship-to geographical location information if different than what is contained in the MAPAD as originally identified by the address codes in the requisition. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
N401	19	City Name	O	AN	2/30	Used	1
		Description: Free-form text for city name					
N402	156	State or Province Code	O	ID	2/2	Used	1
		Description: Code (Standard State/Province) as defined by appropriate government agency					
N403	116	Postal Code	O	ID	3/15	Used	1
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)					
N404	26	Country Code	O	ID	2/3	Used	1
		Description: Code identifying the country					
		DLMS Note: Use to identify the GENC country code. See DLMS introductory note 4 (Refer to ADC 1075 for implementation).					

PER Administrative Communications Contact

Pos: 140Max: 3

Detail - Optional

Loop: N1Elements: 6

User Option (Usage): Used

Purpose: To identify a person or office to whom administrative communications should be directed

- Syntax Rules:
- 1. P0304 - If either PER03 or PER04 is present, then the other is required.
 - 2. P0506 - If either PER05 or PER06 is present, then the other is required.
 - 3. P0708 - If either PER07 or PER08 is present, then the other is required.

DLMS Note:

Use to provide point of contact information. Use only in the N1 loop identifying the ship to. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
PER01	366	Contact Function Code	M	ID	2/2	Must use	1
<div><div>Description: Code identifying the major duty or responsibility of the person or group named</div><div><div>Code</div><div>Name</div><div>ICInformation Contact</div></div><div>DLMS Note: Use to identify the point of contact.</div></div>							
PER02	93	Name	O	AN	1/60	Used	1
<div><div>Description: Free-form name</div></div>							
PER03	365	Communication Number Qualifier	O	ID	2/2	Used	1
<div><div>Description: Code identifying the type of communication number</div><div><div>Code</div><div>Name</div><div>TETelephone</div></div></div>							
PER04	364	Communication Number	O	AN	1/80	Used	1
<div><div>Description: Complete communications number including country or area code when applicable</div></div>							
PER05	365	Communication Number Qualifier	O	ID	2/2	Used	1
<div><div>Description: Code identifying the type of communication number</div><div><div>Code</div><div>Name</div><div>EMElectronic Mail</div></div></div>							
PER06	364	Communication Number	O	AN	1/80	Used	1
<div><div>Description: Complete communications number including country or area code when applicable</div></div>							

LM

Code Source Information

Pos: 144

Max: 1

Detail - Optional

Loop: LM

Elements: 1

User Option (Usage): Used

Purpose: To transmit standard code list identification information

Comments:

1. LM02 identifies the applicable industry code list source information.

DLMS Note:

Use this 2/LM/144 loop to identify coded information maintained in department or agency documentation.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
LM01	559	Agency Qualifier Code	M	ID	2/2	Must use	1
Description: Code identifying the agency assigning the code values							
Code Name							
DF Department of Defense (DoD)							

LQ Industry Code

Pos: 145Max: 100

Detail - Mandatory

Loop: LMElements: 2

User Option (Usage): Must use

Purpose: Code to transmit standard industry codes

Syntax Rules:

1. C0102 - If LQ01 is present, then LQ02 is required.

DLMS Note:

Use to identify codes consistent with management information requirements.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
LQ01	1270	Code List Qualifier Code	O	ID	1/3	Must use	1
Description: Code identifying a specific industry code list							
Code Name							
0 Document Identification Code							
79 Priority Designator Code							
DLMS Note:							
Recommend using in all requisitions							
96 Shipment Release Code							
DLMS Note:							
Use to provide FMS NOA shipment release instructions.							
A9 Supplemental Data							
DLMS Note:							
1. Use to identify supplemental address/data.							
2. Future streamlined data; see introductory DLMS note 3c.							
AJ Utilization Code							
DLMS Note:							
1. Under Legacy MILSTRIP, this is the first position of the document serial number.							
2. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.							
AL Special Requirements Code							
DLMS Note:							
1. Use to identify the precedence, special handling, and processing requirements.							
2. Under legacy MILSTRIP, this is carried in the required delivery date field.							
3. Authorized DLMS enhancement; see DLMS Introductory Note 3e. Refer to ADC 1098.							
COG Cognizance Symbol							
DLMS Note:							
Use to identify the materiel cognizance symbol (COG) of the end item. Indicate NSL for non-stock numbered listed items. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.							
IMC Item Management Code							
DLMS Note:							
Use to identify the Item Management Code (IMC) for integrated materiel management. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.							
MCC Material Control Code							
DLMS Note:							

Code **Name**

Use to identify the Material Control Code (MCC) for special inventory reporting. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

SMI

Special Material Identification Code

DLMS Note:

Use to identify the Special Material Identification Code (SMIC) for an end item. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

LQ02

1271

Industry Code

X

AN

1/30

Must use

1

Description: Code indicating a code from a specific industry code list

SETransaction Set Trailer

Pos: 20

Max: 1

Summary - Mandatory

Loop: N/A

Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Comments:

1. SE is the last segment of each transaction set.

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage	Rep
SE01	96	Number of Included Segments	M	N0	1/10	Must use	1
Description: Total number of segments included in a transaction set including ST and SE segments							
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use	1
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set							
DLMS Note: Cite the same number as the one cited in ST02.							