VSM FOB (Free On Board) Services REST API Collection (1.0.0)

Download OpenAPI specification: Download

VSM Webservices Support Team: JSONWebServiceInquiry@dla.mil | License: VSMFOBLicense

This API Collection provides a comprehensive set of endpoints designed to support shipment processing for vendors using DLA's Vendor Shipment Module (VSM). Each API request is documented with sample payloads, expected responses, JSON Schemas, and error descriptions.

This document will assist any vendor that wishes to create a web service to access these endpoints

Submit FOB Shipment Request

Transaction to submit all the required data to process a shipment. Data such as weight and dimensions of the shipment Container, Pickup Date, Carrier Remarks, Type of Equipment Indicator, and Quantity.

mTLS **AUTHORIZATIONS:** > REQUEST BODY SCHEMA: application/json CAGECode string = 5 characters required A unique five-character alphanumeric identifier assigned to a company. FOBCode string = 2 characters required Enum: "DS" "OG" The code used to identify the contract as Origin (OG) or Destination (DS). SCAC string <= 4 characters A code that is used to identify transportation companies. carrierRemarksLine1 string <= 70 characters Any additional information for the carrier. carrierRemarksLine2 string <= 70 characters Any additional information for the carrier. pickupDate string = 8 characters required The Date the materiel/cargo is available to be picked up.

shippingLocationID string = 10 characters required The ID associated to your shipping location, this will be a specifically formatted Vendors Cage, not the typical CAGE format. The format required will be provided during training. trackingNumber string <= 30 characters The tracking number assigned to the shipment. typeEquipmentIndicator string <= 3 characters</pre> The type of vehicle/trailer used for the shipment. vendorReferenceNumber string <= 30 characters A vendor supplied reference number. containers > Array of objects (container) non-empty required

Responses

- > 200 Success
- > default Error Response

POST /VSM/FreeOnBoardShipment

Request samples

Payload

Content type application/json

```
Copy Expand all Collapse all "CAGECode": "BADRI", "shippingLocationID": "CBADRI0000", "FOBCode": "OG", "SCAC": "",
```

Response samples

200

default

Content type application/json

```
{
    "TCN": "stringstringstrin",
    "messages": {
        + "message": [ ... ]
    },
    "requestNumber": "stringstri"
```

Copy Expand all Collapse all

Get Status On Previously Submitted Shipment Request

Returns a Message Code (messageCode), Message Value (messageValue), and Message Status (messageStatus) for a previously submitted Shipment Request. The returned message data will display if a shipment has been processed or has encountered an issue

AUTHORIZATIONS: >

mTLS

QUERY PARAMETERS

requestNumber
required

string (FOBRequestNumber) = 10 characters

Example: requestNumber=4000005153

Unique identifer returned from a successful Shipment Request.

CAGECode required

```
string (CAGECode) = 5 characters

Example: CAGECode=BADRI
```

A unique five-character alphanumeric identifier assigned to a company.

Responses

- > 200 Success
- > default Error Response

GET /VSM/FreeOnBoardStatus

Response samples

200

default

```
Content type application/json
```

```
"requestNumber": "stringstri",
- "message": {
        "messageCode": "string",
        "messageValue": "string",
        "messageStatus": "string"
}
```

Copy Expand all Collapse all

Returns shipment and address information for a previously submitted Shipment Request. The details include: Tracking Number (trackingNumber), Standard Carrier Alpha Code (SCAC), the Ship To address lines, and the Ultimate Consignee address lines

AUTHORIZATIONS: > mTLS QUERY PARAMETERS string (FOBRequestNumber) = 10 characters Example: requestNumber=4000005153 Unique identifer returned from a successful Shipment Request. CAGECode string (CAGECode) = 5 characters Example: CAGECode=BADRI A unique five-character alphanumeric identifier assigned to a company.

Responses

- > 200 Success
- > default Error Response

GET /VSM/FreeOnBoardAddress

"requestNumber": "stringstri",

Response samples

```
Content type
application/json
```

"SCAC": "stri",

```
Copy Expand all Collapse all
```

```
"trackingNumber": [
    "string"
],
"shipToDODAAC": "string",
"issuePriorityGroup ": "s",
"shipToAddressLine1": "string",
"shipToAddressLine2": "string",
"shipToAddressLine3": "string",
"shipToAddressLine4": "string",
"shipToAddressLine5": "string",
"ultimateConsigneeDODAAC": "string",
"ultimateConsigneeAddressLine1": "string",
"ultimateConsigneeAddressLine2": "string",
"ultimateConsigneeAddressLine3": "string",
"ultimateConsigneeAddressLine4": "string",
"ultimateConsigneeAddressLine5": "string",
"message": "string"
```

Submit FOB Document Request

Transaction to receive the relevant shipping documentation for a single processed shipment. This documentation can include: Item Labels, Commercial Invoices (CI), Packing Lists (PKL), Commercial or Government Bill of Lading (CBL/GBL), Country specific Customs Documents, Transportation Control and Movement Document (TCMD), Container Item Labels, and Material Inspection And Receiving Report (DD 250).

The documentation will be sent as PDF files inside a compressed ZIP file.

```
AUTHORIZATIONS: > mTLS

REQUEST BODY SCHEMA: application/json

requestNumber string (FOBRequestNumber) = 10 characters
Unique identifer returned from a successful Shipment Request.

CAGECode string (CAGECode) = 5 characters
A unique five-character alphanumeric identifier assigned to a company.
```

Responses

- > 200 Returns two parts. A JSON message and a ZIP file
- > default Error Response

```
POST /VSM/FreeOnBoardDocuments
```

Request samples

Content type

Payload

```
application/json

{
    "requestNumber": "4000005290",
    "CAGECode": "BADRI"
```

Response samples

Content type application/json

default

```
{
    "code": "string",
    "message": "string",
    "logID": "string"
```

Сору

Сору

Submit FOB Closeout Request

Transaction for Destination Contract vendors to update a shipment with additional needed information. Updateable fields are: Vendor Reference Number (vendorReferenceNumber), Standard Carrier Alpha Code (SCAC), and Tracking Number (trackingNumber)

AUTHORIZATIONS: > mTLS

REQUEST BODY SCHEMA: application/json

requestNumber string = 10 characters

required Unique identifer returned from a successful Shipment Request.

CAGECode string = 5 characters

A unique five-character alphanumeric identifier assigned to a company.

vendorReferenceNumber string <= 30 characters</pre>

A vendor supplied reference number.

SCAC string <= 4 characters

A code that is used to identify transportation companies.

trackingNumber string <= 30 characters

The tracking number assigned to the shipment.

Responses

- > 200 Success
- > default Error Response

POST /VSM/FreeOnBoardCloseout

Payload

```
Content type application/json
```

```
{
    "requestNumber": "4000005006",
    "CAGECode": "79343",
    "vendorReferenceNumber": "TEST",
    "SCAC": "UPSN",
    "trackingNumber": "123456"
}
```

Response samples

200

default

Content type application/json

{
 "message": "string"
}

Сору

Сору