



<b>APPENDIX A Revision A</b>		<b>POWER DISTRIBUTION PRODUCT DATA SHEET (PD) or PD KIT (Exterior Shelter Components)</b>	
Company Name	Alaska Structures, Inc.		
Part Number	AK-EL-2SPDS02		
Specifications as applicable			
Item Type (Distribution Box, Cable, Switch Box...)	Alaska 2-Shelter U.S. Power Distribution System		
Rating in Amps, Pole, Volts, Wire	300A 120/208V 3-Phase 5-Wire		
Input(Amount) By Amp, Phase, Pole, Wire, VAC	300A 120/208V 3-Phase, 5-Wire CAM Input		
Output (Amount) By Amp, Phase, Pole, Wire, VAC	(6) 60A 120/208V 3-Phase and (6) 20A 120V Single Phase		
MIL-SPEC Cable compatible MIL-DTL-22992	0A connections and/or cables are MIL-DTL-22992 Class 'L' Connector		
Weight Unpackaged) (lb)	350 lbs		
Dimensions Length x Width x Height in inches	52" x 48" x 24"		
Cable Type, Class	5' CAM Tail Set - 2/0 AWG Type SC, 100' CAM Feeder Set - 2/0 AWG Type SC		
Connector Type End 1 and End 2	End 1	5' CAM Tail Set - Female CAM Connector, Pigtail End; 100' CAM Feeder Set - Female & Male CAM Connector	
	End 2		
Length	5' CAM Tail Set - 5' in length, 100' CAM Feeder Set - 100' in length		
MIL-SPEC Cable compatible MIL-DTL-22992			
PD and Cable Kit Components	(1) Power Distribution Box, (1) 5' CAM Tail Set, (1) 100' CAM Feeder Set		
Special/Additional Features:	Box is rated for U.S. 60Hz power and rated for outdoor usage.		