



## APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

<b>PRODUCT DATA SHEET</b>		<b>CONTRACTOR NAME:</b> CAMSS Shelters	
<b>1.PART</b> CAMSS-18TAC32G		<b>2.NSN:</b>	
<b>NUMBER:</b>			
<b>3.NAME:</b> CAMSS18TAC32 Shelter System	<b>4.TYPE:</b> Tactical		<b>5.CLASS:</b>
<b>6.COLOR:</b> Green	<b>7. Support System:</b> External Aluminum Frame		<b>8.SERIES:</b> TAC
<b>9. INTENDED USE:</b> Tactical Shelters, Rapid Deployment			
<b>10.DIMENSIONS (IN FEET AND INCHES)</b>	<b>LENGTH:</b> 32'	<b>WIDTH:</b> 18'	<b>HEIGHT:</b> 6'11" Eave Height 9'4" Peak Height
<b>11.DIMENSIONS (EXTERNAL GUYED)</b>	<b>LENGTH</b> 32'	<b>WIDTH</b> 24'	
<b>12.SQUARE FEET INTERIOR:</b> 576 sf			
<b>13.WEIGHT (POUNDS, UNPACKAGED)</b> 1275 lbs.		<b>14.WEIGHT (PACKAGED) LBS</b> 1375 lbs.	<b>15.SHIPPING CUBE (PACKAGED)</b> 62 CU.
<b>16. SHIPPING CONTAINER</b>	<b>LENGTH:</b> 100"	<b>WIDTH</b> 48"	<b>HEIGHT</b> 22"
<b>17.SET-UP TIME/ NUMBER OF PERSONS:</b> 4 persons / < 6 minutes		<b>18.STRIKE TIME/ NUMBER OF PERSONS</b> 4 persons / < 6 minutes	
<b>19.SNOW LOAD:</b> Tested: 10 psf per TOP 10-2-175 testing of similar type and size shelter		<b>20.WIND LOAD:</b> Tested: 55 MPH sustained 65 MPH gusts testing of similar type and size shelter	
<b>21.PARTS INCLUDED (Include Quantity):</b> <p>The CAMSS18TAC32 Shelter System is a complete shelter system that deploys fully in just a few minutes. The CAMSS18TAC32 Shelter System includes a robust one-piece anodized aluminum folding frame, Mil-Spec 44103D with FR, IR, blackout, UV and mildew resistance cover with four (4) mesh windows with wind resistant blackout covers, four (4) double zipper entries (36" x 84") with vestibule connectors, and a non-slip Mil-Spec 44103D fabric floor with vector proofing that is removable without shelter disassembly. Also included is one (1) white Mil-Spec fabric liner with FR, blackout, UV and mildew resistance. Shelter comes standard with two (2) sets of two (2) 18" ECU ports with a cable port and a fabric air sock with spot cooling. Quick connect 110V outlets are included as well, optional lights are available. Double headed 18" anchoring spikes and guy ropes with guy spikes are provided for anchoring.</p>			
<b>22.DESCRPTION:</b> <p>The CAMSS18TAC32 is a the one-piece external frame is lightweight aluminum that is easy to install quickly. The Mil-Spec fabric cover system is secured to the frame. The liner is integrated into the cover system to assist with quick assembly and strike. The floor is removable without any disassembly of the shelter system for easy replacement or repair. The CAMSS18TAC32 is configured to complex multiple shelters into one customizable configurations. The four (4) doors can connect to other CAMSS shelters, and is also compatible with other shelters in the DOD inventory</p>			

<b>23. ACCESSORY AND SUPPORT EQUIPMENT:</b>	<b>PART NUMBER Or NSN</b>	<b>Check if Included</b>	<b>DESCRIPTION</b>
	HIT-20Q-ELC01	OPTIONAL	Two (2) light strings with a total of ten (10) incandescent bulb lights
<b>LIGHT SET Product Data Sheet</b>	HIT-20Q-ELC-LED-01	OPTIONAL	LED bulb lights with metal cages. Two (2) light strings with a total of ten (10) LED bulbs and hanging lanyards
	CAMSS-EL-F50-1	OPTIONAL	Ruggedized Fluorescent Tube Light. Quantity 1 light (recommend ten [10] lights)
	CAMSS-EL-LEDT-1	OPTIONAL	Ruggedized LED Tube Lights. Quantity 1 light.
<b>ELECTRIC AL OUTLET SET Product Data Sheet</b>	HIT-18TAC-ERPL02	INCLUDED	Triplex outlets - long
	HIT-18TAC-ERPS02	INCLUDED	Triplex outlets – short
	HIT-18TEK01-EU	OPTIONAL	CAMSS20TAC EU Electrical Kit. All electric components changed to 220V 50Hz
<b>FLOORING Product Data Sheet</b>	HIT-18TAC32-PFL01	INCLUDED	Standard Fabric Flooring. 15 oz./sq. yd. MIL-SPEC 44103D fabric flooring.
	CAMSS-HFLD/576	OPTIONAL	Personnel Hard Flooring. High-impact polypropylene with UV inhibitors – load capacity of 8,000 lbs. PSF when installed properly over cleared, stable ground
<b>HEATER Product Data Sheet</b>			
<b>AIR CONDITIONER Product Data Sheet</b>	CAMSS-5TECU01	OPTIONAL	CAMSS 5-Ton Ruggedized ECU. For cooling and heating.
	CAMSS-5TECU01-EU	OPTIONAL	CAMSS 5-Ton Ruggedized ECU. For cooling and heating. 50 Hz (European)
<b>GENERATOR Product Data Sheet</b>			

<b>POWER DISTRIBUTION Product Data Sheet</b>	CAMSS-E2SPDS	OPTIONAL	Two (2) shelter power distribution system
<b>TRAILER MOUNTED SUPPORT SYSTEM Product Data Sheet</b>			
<b>INSULATED LINER Product Data Sheet</b>	HIT-18TAC32-HBH	INCLUDED	Shelter includes an internal liner system that helps to maintain internal working conditions of 40° - 80° F in ambient temperatures of -25° to 125 F when supported by a 5-Ton military environmental control unit
<b>INSULATED FLOORING Product Data Sheet</b>			
<b>SOLAR SHADE/CAMOU. NETT Product Data Sheet</b>	CAMSS-18TAC32-TSF-T	OPTIONAL	CAMSS independent lab tested CAMSS18TAC32 Shelter System Thermacam SolarFly. TSF provides energy savings & is wind tested to withstand 55 MPH sustained winds (similar size and type test)
<b>PACKAGING Connectors</b>	CAMSS-HIT-CR4149102	OPTIONAL	CAMSS Tall Rotationally molded container (41" x 49" x 102")
		OPTIONAL	End to End Connector
	CAMSSPCON-CSTS-01-T	OPTIONAL	Side to Side Connector
	CAMSS-CON-CSTE-01-T	OPTIONAL	End to Side Connector
	CAMSS18TAC-CTC-01-T	OPTIONAL	Cover to Cover Connector