



**APPENDIX A
Revision A****SHEET (PD) or PD KIT
(Exterior Shelter Components)****CAMSS Shelters****CAMSS-E2PDS**

Specifications as applicable

Item Type (Distribution Box,
Cable, Switch Box)

1

4 Position Tuff Box

Rating in Amps, Pole, Volts,
Wire

225A 3 ph 120/208V

Input(Amount) By Amp, Phase, Pole,
Wire, VAC

400A 5 Wire CAM-Lok Inlets

Output (Amount) By Amp,
Phase, Pole, Wire, VAC

2-20A 12/208V Wetguards, 2 – 60A 5 Wire Milspecs

MIL-SPEC Cable compatible
MIL-DTL-22992

Yes

Weight Unpackaged) (lb)

38lbs

Dimensions Length xWidth x
Heightin inches

Cable Type, Class

Type W – Portable Power Cable, double Insulated

Connector Type End 1 and End 2

End 1

1 – 5 x 50' #4 Color Coded (RBBWG) cable and cam-loks, imprinted
every ft. with specified identification, sewn on D ring strap, 1-5' 5
wire pigtail set

End 2

Length

50'

MIL-SPEC Cable compatible MIL-
DTL-22992

2

50' 60A 5 wire Milspec DTL-22992 Extension Cable to AC

PD and Cable Kit Components

2

50' 12/5 20A wetguard Extension Cable to Interior Panel

Special/Additional Features:

Panel is powder coated aluminum, mounted in aluminum stackable cage.