



APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

PRODUCT DATA SHEET		CONTRACTOR NAME: CAMSS Shelters	
1.PART NUMBER: CAMSS-HIT-20EX40		2.NSN:	
3.NAME: CAMSS20EX40	4.TYPE: Shelter System		5.CLASS:
6.COLOR: 483 Olive Drab	7. Support System: Frame		8.SERIES: CAMSS20EX
9. INTENDED USE:, Command Post, Medical, Kitchen, Communication Centers, Laundry, TOCs, Billeting			
10.DIMENSIONS (IN FEET AND INCHES)	LENGTH: 40'	WIDTH: 20'	HEIGHT: RIDGE/EAVE: 7' Eave 10' Peak Height
11.DIMENSIONS (EXTERNAL GUYED)	LENGTH: 40'	WIDTH 26'	
12.SQUARE FEET INTERIOR: 770Square Feet			
13.WEIGHT (POUNDS, UNPACKAGED) 1,650 lbs		14.WEIGHT (PACKAGED) 1,950 lbs	15.SHIPPING CUBE (PACKAGED) 75 cu. ft
16SHIPPING CONTAINER	LENGTH: 102"	WIDTH: 44"	HEIGHT: 29"
17.SET-UP TIME/ NUMBER OF PERSONS 30 minutes/4 persons		18.STRIKE TIME/ NUMBER OF PERSONS: 20 minutes/4 persons	
19.PARTS INCLUDED: The CAMSS20EX40 includes the aluminum frame system with a complete perimeter base and a tensioned fabric cover system. The shelter includes a aluminum hard door and a double zipper door. The cover system includes 14 windows. Also includes is an extreme temperature kit, fabric floor, and internal distribution system that includes lights, outlets and distribution panel. The CAMSS20EX40 includes an anchoring package with double headed spikes, guy spikes and guy ropes and a repair kit. The complete CAMSS20EX40 is packed in a wooden crate. Both composite and rotationally molded containers are optional			
20.DESCRPTION: The CAMSS20EX40 is a complete shelter system with a 2" x 3" aluminum frame system and a tensioned MIL Spec fabric cover system. The 7' vertical sidewall maximizes the useable square feet inside the shelter. The straight sidewall allows for cots, desks, and equipment to be placed directly against the wall allowing for increased walkways and work areas inside the shelter. The increase in space is accomplished without increasing the footprint of the shelter system. The CAMSS shelter is compatible with existing military fluorescent lighting systems. Optional lights in accordance with MIL-L-44259 are available. It may be connected to a TEMPER vestibule and it is supported by optional trailer systems with generators and ECUs.			
21. SUPPORT EQUIPMENT:	PART NUMBER Or NSN	Included or Optional	DESCRIPTION
LIGHT SET Product Data Sheet	CAMSS20EX-ELC01	Included	Light String with Incandescent Lights
	CAMSS2EX-ELC01-LED	Optional	Light String with LED light bulbs
	CAMSS20EX-ELC01-CFL	Optional	Light String with CFL light bulbs
ELECTRICAL OUTLET SET Product Data	HIT-20EX-ERPL02	Included	CAMSS20EX Triplex Outlet Cord Long
FLOORING Product Data Sheet	CAMSS20EX40-PFL01	Included	Fabric floor with cutouts for base stubs and Velcro to attach to cover
	CAMSS-HFLD/SF	Optional	hard plastic flooring
HEATER			

Product Data Sheet			
AIR CONDITIONER Product Data Sheet	CAMSS-5TECU01	Optional	Five ton ECU with 12kw of heating
	CAMSS-2.5TECU01	Optional	2.5 ton ECU with 12kw of heating
GENERATOR Product Data Sheet			
	CAMSS-G20KW	Optional	20Kw Generator
POWER DISTRIBUTION Product Data Sheet			
	CAMSS-E2SPDS	Optional	Two shelter power distribution system
TRAILER MOUNTED SUPPORT SYSTEM Product Data Sheet			
	CAMSS-LTT-LE	Optional	CAMSS Light Tactical Trailer System
INSULATED LINER Product Data Sheet	CAMSS20EX-HLLE	Optional	CAMSS Insulcam liner system installs quickly and easily like the basic liner system and reduces demand on ECUs by 42%
INSULATED FLOORING Product Data Sheet			
SOLAR SHADE/ CAMOU. NETT Product Data Sheet	CAMSS20EX-PSF01	Optional	CAMSS Solar Fly is a unique fly system that slides over the cover and reduces solar load on the shelter.