



APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

| | | | |
|---|---|---|---|
| PRODUCT DATA SHEET | | CONTRACTOR NAME: CAMSS Shelters | |
| 1.PART NUMBER: CAMSS-HIT-20EX40T | | 2.NSN: | |
| 3.NAME: CAMSS20EX Shelter System | 4.TYPE: Gable | | 5.CLASS: |
| 6.COLOR: Desert Tan | 7. Support System: Aluminum Frame | | 8.SERIES: EX |
| 9. INTENDED USE: Billeting, Command Posts, Medical, Communications, Dining & Kitchens | | | |
| 10.DIMENSIONS (IN FEET AND INCHES) | LENGTH: 40' | WIDTH: 20' | HEIGHT: 10' tall with 7' eaves |
| 11.DIMENSIONS (EXTERNAL GUYED) | LENGTH: 40' | WIDTH: 26' | |
| 12.SQUARE FEET INTERIOR: 800 sf | | | |
| 13.WEIGHT (POUNDS, UNPACKAGED) LBS. 1,650 lbs. | | 14.WEIGHT (PACKAGED) LBS 1,950 lbs. | 15.SHIPPING CUBE (PACKAGED) 75 CU. |
| 16. SHIPPING CONTAINER | LENGTH 102" Inches | WIDTH 44" Inches | HEIGHT 29" Inches |
| 17.SET-UP TIME/ NUMBER OF PERSONS: 4 persons / 30 minutes TIME UNDER CANOPY 30 minutes | | 18.STRIKE TIME/ NUMBER OF PERSONS 4 persons / 30 minutes | |
| 19.SNOW LOAD: Design: 20 PSF Ground Snow Load per ASCE 7-16 Tested: 10 psf 12 hour snow load test per TOP 10-2-175 | | 20.Wind Load: Design: 100 MPH per ASCE 7-16 Tested: Wind: 55 MPH sustained/65 MPH gusts per TOP 10-2-175 | |
| Durability: ATC 20 strike/erect set-ups | | Wind-Driven Rain: 55 MPH sustained/65 MPH gusts with simulated rain per TOP 10-2-175 | |
| 21.PARTS INCLUDED (Include Quantity): <p>The CAMSS20EX40 Shelter System is a complete shelter system, which includes: high strength aluminum frame, tensioned MIL-SPEC 44103D fabric cover system with total fourteen (14) mesh windows with wind resistant blackout covers, non-slip fabric floor, extreme temperature liner system to maintain comfortable internal temperatures, quick connect electrical system with plug and play outlets, electrical distribution panel and lights, which may be upgraded for an additional cost. One (1) 30" W x 80" H aluminum personnel door with locking flush mount handle. Also included is the anchoring package with double headed 18" base frame spikes and guy ropes and guy spikes, 30 day spares / repair, and the verified technical manual. Shelter comes standard in wood crates, but can be upgraded to CAMSS Roto-Mold Container for shipping and storage.</p> | | | |

22.DESCRPTION:

The straight sidewalls of the CAMSS20EX40 Shelter System and 20ft wide interior makes it ideal for many applications. Unlike curved or slanted sidewalls, the straight sidewalls allow for equipment and furniture to be placed adjacent to the walls, maximizing available space. This makes the CAMSS20EX40 Shelter System the preferred choice for billeting, hospitals, kitchens, and other applications requiring tall sidewalls.

The CAMSS20EX40 shelter is rugged and durable for long life. It is able to withstand extreme temperatures, high winds, and heavy snow loads. The CAMSS20EX40 Shelter System uses a high strength aluminum frame to meet a 20PSF ground snow load and a 100 mph wind load per ASCE 7-16.

CAMSS20EX Brochure: <https://youtu.be/7Xlv5v6AM9g>

CAMSS20EX Shelter Testing: <https://youtu.be/NCNPpx5bXU4>

Air Force report: Balad Hospital & CAMSS20EX Shelter Systems: <https://youtu.be/pF2JgRRRrkI>

| | | | |
|--|---------------------------|--------------------------|---|
| 23. ACCESSORY AND SUPPORT EQUIPMENT: LIGHT SET Product Data Sheet | PART NUMBER Or NSN | Check if Included | DESCRIPTION |
| | HIT-20EX-ELC01 | INCLUDED | Two (2) light strings with a total of ten (10) incandescent bulb lights |
| | HIT-20EX-ELC-LED-01 | OPTIONAL | LED bulb lights with metal cages. Two (2) light strings with a total of ten (10) LED bulbs and hanging lanyards |
| | CAMSS-EL-F50-1 | OPTIONAL | Ruggedized Fluorescent Tube Lights. Quantity 1 light. |
| ELECTRICAL OUTLET SET Product Data Sheet | CAMSS-EL-LEDT-1 | OPTIONAL | Ruggedized LED Tube Lights. Quantity 1 light |
| | HIT-20EX-EDP01 | INCLUDED | (1) single phase power distribution box with (2) GFCI breakers (1) 20A breaker (4) twist lock connectors and (1) light switch with (1) 50' 20A power cable |
| | HIT-20EX-ERP01 | INCLUDED | Triplex outlets – long |
| | HIT-20EX-ERO01 | INCLUDED | Triplex outlets – short |
| FLOORING Product Data Sheet | CAMSS2040EL-EU | OPTIONAL | CAMSS20EX EU Electrical Kit. All electric components changed to 220V 50Hz |
| | HIT-20EX40-PFL01 | INCLUDED | Standard Fabric Flooring. 15 oz./sq. yd. MIL-SPEC 44103D fabric flooring. |
| | CAMSS-HIT-20EX40-PFL03 | OPTIONAL | Heavy-Duty Fabric Flooring. 18 oz/sq. yd. MIL-SPEC 44103D fabric flooring. |
| | CAMSS-HIT-20EX40-PFL28 | OPTIONAL | Extra Heavy-Duty Fabric Flooring. 28 oz./sq. yd. MIL-SPEC 44103D fabric flooring. |
| | CAMSS-SFS-800 | OPTIONAL | CAMSS Sub Flooring System |
| | CAMSS-HFLD/800 | OPTIONAL | Personnel Hard Flooring. High-impact polypropylene with UV inhibitors – load capacity of 8,000 lbs. PSF when installed properly over cleared, stable ground |
| | CAMSS20EX40-RFS | OPTIONAL | Adjustable raised Floor System for CAMSS20EX Shelter System. |
| HEATER Product Data Sheet | | | |
| | | | |
| | | | |
| | | | |
| AIR CONDITIONER Product Data Sheet | CAMSS-5TECU01 | OPTIONAL | CAMSS 5-Ton Ruggedized ECU. For cooling and heating. |
| | CAMSS-5TECU01-EU | OPTIONAL | CAMSS 5-Ton Ruggedized ECU. For cooling and heating. 50 Hz (European) |
| | | | |
| | | | |
| GENERATOR Product Data Sheet | | | |
| | | | |

| | | | |
|--|----------------------|----------|--|
| | | | |
| | | | |
| POWER DISTRIBUTION Product Data Sheet | CAMSS-E2SPDS | OPTIONAL | Two (2) shelter power distribution system |
| | | | |
| TRAILER MOUNTED SUPPORT SYSTEM Product Data Sheet | | | |
| | | | |
| | | | |
| | | | |
| INSULATED LINER Product Data Sheet | CAMSS2040HH | INCLUDED | Shelter includes an internal liner system that helps to maintain internal working conditions of 40° - 80° F in ambient temperatures of -25° to 125 F when supported by a 5-Ton military environmental control unit |
| | CAMSS20EX40-HLLE | OPTIONAL | CAMSS20EX Insulcam Insulating Liner System. Tests have shown ECU usage to drop dramatically compared to standard liner. |
| | | | |
| INSULATED FLOORING Product Data Sheet | CAMSS20EX40-ECW-SF01 | OPTIONAL | CAMSS20EX Extreme Cold Weather Subfloor. Creates a thermal barrier between the ground and the shelter fabric floor. |
| SOLAR SHADE/ CAMOU. NETT Product Data Sheet | CAMSS-20EX40-SF-T | OPTIONAL | CAMSS20EX Shelter System SolarFly. SolarFly provides energy savings. |
| PACKAGING | CAMSS-HIT-CR4149102 | OPTIONAL | CAMSS Tall Rotationally molded container (41" x 49" x 102") |
| | CAMSS-HIT-CR4133102 | OPTIONAL | CAMSS LP Rotationally molded container (41" x 33" x 102") |