



## APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

<b>PRODUCT DATA SHEET</b>		<b>CONTRACTOR NAME: CAMSS Shelters</b>	
1.PART CAMSS-KSS-IG		2.NSN:	
NUMBER:			
3.NAME: CAMSS20EX Kitchen Shelter System I (initial)	4.TYPE: EX Kitchen Shelter System	5.CLASS:	
6.COLOR: Olive Drab Green	7. Support Aluminum Frame System:	8.SERIES: 20EX	
9. INTENDED Kitchen Shelter System includes multiple shelters that complex together			
USE:			
10.DIMENSIONS (IN FEET AND INCHES)	LENGTH: 40'/shelter	WIDTH: 20'/shelter	HEIGHT: 10' tall with 7' eaves
11.DIMENSIONS (EXTERNAL GUYED)	LENGTH 40'/shelter	WIDTH 26'/shelter	
12.SQUARE FEET INTERIOR: 4800 sf			
13.WEIGHT (POUNDS, UNPACKAGED) 6,680 LBS.		14.WEIGHT (PACKAGED) 8,350 LBS.	15.SHIPPING CUBE (PACKAGED) 943 CU.
16. SHIPPING CONTAINER	LENGTH Inches 101" / container	WIDTH Inches 42" / container	HEIGHT Inches 48" / container
17.SET-UP TIME/ NUMBER OF PERSONS: 3 hours / 8 persons Complete CAMSS Kitchen Shelter System		18.STRIKE TIME/ NUMBER OF PERSONS 1.5 hours/8 persons	
19.SNOW LOAD: Design: 20 PSF Ground Snow Load per ASCE 7-16 Tested: 10 psf 12 hour snow load test per TOP 10-2-175		20.Wind Load: Design: 100 MPH per ASCE 7-16 Tested: Wind: 55 MPH sustained/65 MPH gusts per TOP 10-2-175	
21.PARTS INCLUDED (Include Quantity):  The CAMSS KSS I (initial) comes with two (2) CAMSS20EX40 shelter systems and two (2) vestibules and four (4) corridors. Each CAMSS20EX40 Shelter System is a complete shelter system, which includes: high strength aluminum frame, tensioned MIL-SPEC 44103D fabric cover system with total of ten (10) mesh windows with wind resistant blackout covers, non-slip fabric floor, extreme temperature liner system to maintain comfortable internal temperatures, air sock, HVAC ports and cable ports, quick connect electrical system with plug and play outlets, electrical distribution panel and lights, which may be upgraded for an additional cost. One (1) 48" W x 80" H aluminum personnel door with locking flush mount handle and two (2) 36" w x 84" h double zipper entry are also included. Also included is the anchoring package with twenty-eight (28) double headed 18" base frame spikes and twelve (12) guy ropes and guy spikes, 30 day spares / repair, and the verified technical manual. Shelter comes standard in containers.			
22.DESCRPTION:  The CAMSS KSS is an integrated system of shelters designed to provide a dining facility for 500 to 1100 personnel. The CAMSS KSS was developed in cooperation with U.S. Natick Laboratories, U.S. Air Force Services, Air Combat Command, and Holloman AFB. This kitchen system provides a more compact, yet more functional kitchen dining facility with greater usable space.  The straight sidewalls of the CAMSS20EX40 Shelter System and 20ft wide interior makes it ideal for many applications. Unlike curved or slanted sidewalls, the straight sidewalls allow for equipment and furniture to be placed adjacent to the walls, maximizing available space. This makes the CAMSS20EX40 Shelter System the preferred choice for hospitals, kitchens, and other applications requiring tall sidewalls.  The CAMSS20EX40 shelter is rugged and durable for long life. It is able to withstand extreme temperatures, high winds, and heavy snow loads. The CAMSS20EX40 Shelter System uses a high strength aluminum frame to meet a 20 PSF ground snow load and a 100 mph wind load per ASCE 7-16 CAMSS20EX Brochure: <a href="https://youtu.be/7Xlv5v6AM9g">https://youtu.be/7Xlv5v6AM9g</a> CAMSS20EX Shelter Testing: <a href="https://youtu.be/NCNPpx5bXU4">https://youtu.be/NCNPpx5bXU4</a>			

Air Force report: Balad Hospital & CAMSS20EX Shelter Systems: <https://youtu.be/pF2JgRRRrkI>

<b>23. ACCESSORY AND SUPPORT EQUIPMENT:</b>	<b>PART NUMBER Or NSN</b>	<b>Check if Included</b>	<b>DESCRIPTION</b>
	HIT-20EX-ELC01	INCLUDED	Two (2) light strings (need qty 2)
<b>LIGHT SET Product Data Sheet</b>	HIT-20EX-ELC-LED-01	OPTIONAL	LED bulb lights with metal cages (need qty 2)
	CAMSS-EL-F50-1	OPTIONAL	Ruggedized Fluorescent Tube Lights. Quantity 1 light
	CAMSS-EL-LEDT-1	OPTIONAL	Ruggedized LED Tube Lights. Quantity 1 light.
<b>ELECTRIC AL OUTLET SET Product Data Sheet</b>	HIT-20EX-EDP01	INCLUDED	(1) single phase power distribution box with (2) GFCI breakers (1) 20A breaker (4) twist lock connectors and (1) light switch with (1) 50' 20A power cable
	HIT-20EX-ERP01	INCLUDED	Triplex outlets – long
	HIT-20EX-ERO01	INCLUDED	Triplex outlets – short
	CAMSS2040EL-EU	OPTIONAL	CAMSS20EX EU Electrical Kit. All electric components changed to 220V 50Hz
<b>FLOORING Product Data Sheet</b>	HIT-20EX40-PFL01	INCLUDED	Standard Fabric Flooring. 15 oz./sq. yd. MIL-SPEC 44103D fabric flooring.
	CAMSS-HIT-20EX40-PFL03	OPTIONAL	Heavy-Duty Fabric Flooring. 18 oz/sq. yd. MIL-SPEC 44103D fabric flooring.
	CAMSS-HIT-20EX40-PFL28	OPTIONAL	Extra Heavy-Duty Fabric Flooring. 28 oz./sq. yd. MIL-SPEC 44103D fabric flooring.
	CAMSS-SFS-KSS-I	OPTIONAL	CAMSS Sub Flooring System
	CAMSS-HFLD/KSS-I	OPTIONAL	Personnel Hard Flooring. High-impact polypropylene with UV inhibitors – load capacity of 8,000 lbs. PSF when installed properly over cleared, stable ground
	CAMSS20EX40-RFS	OPTIONAL	Adjustable raised Floor System for CAMSS20EX Shelter System.
<b>HEATER Product Data Sheet</b>			
<b>AIR CONDITIONER Product Data Sheet</b>	CAMSS-5TECU01	OPTIONAL	CAMSS 5-Ton Ruggedized ECU. For cooling and heating.
	CAMSS-5TECU01-EU	OPTIONAL	CAMSS 5-Ton Ruggedized ECU with EU, 50hz electrical. For cooling and heating.
<b>GENERATOR</b>			

<b>Product Data Sheet</b>			
<b>POWER DISTRIBUTION Product Data Sheet</b>	CAMSS-E2SPDS	OPTIONAL	Two (2) shelter power distribution system
<b>TRAILER MOUNTED SUPPORT SYSTEM Product Data Sheet</b>			
<b>INSULATED LINER Product Data Sheet</b>	CAMSS2040HH	INCLUDED	Shelter includes an internal liner system that helps to maintain internal working conditions of 40° - 80° F in ambient temperatures of -25° to 125 F when supported by a 5-Ton military environmental control unit
	CAMSS20EX40-HLLE	OPTIONAL	CAMSS20EX Insulcam Insulating Liner System. Tests have shown ECU usage to drop dramatically compared to standard liner.
<b>INSULATED FLOORING Product Data Sheet</b>	CAMSS20EX40-ECW-SF01	OPTIONAL	CAMSS20EX Extreme Cold Weather Subfloor. Creates a thermal barrier between the ground and the shelter fabric floor.
<b>SOLAR SHADE/CAMOU. NETT Product Data Sheet</b>	CAMSS-20EX40-SF-G	OPTIONAL	CAMSS20EX Shelter System SolarFly. SolarFly provides energy savings.
<b>PACKAGING</b>	CAMSS-HIT-CR4149102	OPTIONAL	CAMSS Tall Rotationally molded container (41" x 49" x 102")
	CAMSS-HIT-CR4133102	OPTIONAL	CAMSS LP Rotationally molded container (41" x 33" x 102")