





FEDMALL 

CLICK HERE TO ORDER THIS ITEM IN FEDMALL

LOG ON TO FEDMALL IN A 2nd TAB FIRST

APPENDIX A Revision B Company Manufacturing Source Company Part Number or NSN	ACCESSORY PRODUCT DATASHEET CAMSS Shelters CAMSS20Q-SF-T 8340-01-653-3332	
Specifications as applicable	CAMSS20Q SolarFly System. Verified to fit CAMSS20Q Small Shelter System and other Small Shelter Systems	
Insulated Liner		
Insulated Flooring		
Solar Shade/ Camouflage Netting		SolarFly is designed to install on existing Small Shelter Systems
Weight (Unpackaged) (lb.)		
Color in accordance with FED-STD-595		Desert Tan
Testing		Successfully tested to 55 mph sustained winds with 65 mph gusts per TOP 10-2-175 by independent testing agency
Special/Additional Features:		<p>Successfully tested to 55 mph sustained / 65 mph gusts the CAMSS20Q SolarFly reduces solar gain and significantly enhances cooling. Designed to easily install over existing Small Shelter System (SSS) without disassembly of SSS or use of mechanical equipment. The only Small Shelter System fly to have successfully met Military TOP 10-2-175 standards for high winds and gusts.</p> <ul style="list-style-type: none"> • Reduced ECU cold air output time required by approximately 15% with a similar reduction in power consumption per independent test • Tested in real world conditions with extreme solar loads • Cubic volume: 46" L x 62" W x 20" H • 100% Berry Amendment Compliant • Flame resistant to ASTM D6413 • Mildew and Fungus resistant per Mil-Spec fabric