

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET			
Company				
Part Number or NSN				
Specifications as applicable				
Safety and Mobility Certification by Military Test Center				
Trailer				
Stowage Components included with trailer				
Cargo Volume Stowage, For shelter and accessory components In cubic feet				
Physical Dimensions for trailer				
Height				
Width				
Length				
Recommended Prime Mover Vehicle				
Empty GVW				
Tongue Weight				
Tire Type and Size				
Fuel Tank Capacity				
Generator				
Nominal Output in kW, Volts AC, Hertz, Phase				
Operating Environment				
Engine type				
Fuel Type				

Fuel Consumption			
(AC Compressor On)			
At 25% load			
At 50% Load			
At 75% Load			
at maximum output			
Noise in DB at 25 feet			
(AC Compressor On)			
At 25% load			
At 25% load			
At 50% load			
At 75% Load			
At maximum rated load			
Heater			
N : I O : : : BTIII	· · · · · · · · · · · · · · · · · · ·		
Nominal Output in BTU's			
Electric Requirement		 	
Volts/Amps			
Air Conditioning	L		
. i. Conamonning			
Maximum Cooling Capacityin			
BTU's			
Maximum Heat Output			
Capacity in BTU's			
Refrigerant Type			
CFM Air Flow			
Air Duct Diameter			
Power Requirements in kW, VAC, HZ,			
Phase			
Special/Additional Features:			
opeolal// aditional i dataros.			