

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET	
Company	DHS Systems LLC	
Part Number or NSN	TG201-0008T DRASH HP-2C/188, Desert Tan, Analog	
Specifications as applicable		
Safety and Mobility Certification by Military Test Center		
Trailer		
Stowage Components included with trailer	NA	
Cargo Volume Stowage, For shelter and accessory components In cubic feet	77 cu. ft.	
Physical Dimensions for trailer	6.5 ft H	
Height	7.2 ft W	
Width	16.2 ft L	
Length Recommended Prime Mover Vehicle	HMMWV	Requires a vehicle capable of towing a 4,200 lb. trailer.
Empty GVW	3,549 lb.	
Tongue Weight	379 lb.	
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias-ply, run-flat tires.
Fuel Tank Capacity	16 gal.	
Generator		
Nominal Output in kW, Volts AC, Hertz, Phase	18kW	120/208 Volt, 3-Phase, 60 Hz
Operating Environment	All	Operating Range from -50 °F to +140 °F.
Engine type	Diesel	Four cylinder, liquid cooled, direct injection, 1800 RPM.
Fuel Type	Diesel	Can also use JP8 or JP5.

(

(

(

Fuel Consumption		
(AC Compressor On)		
At 25% load	NA	
At 50% Load	NA	
At 75% Load	NA	
at maximum output	1.25	
Noise in DB at 25 feet		
(AC Compressor On)		
At 25% load	NA	
At 50% load	NA	
At 75% Load	NA	
At maximum rated load	76 dB	
Heater		
I Nominal Output in BTU's	1	
	NA	
Electric Requirement		
Volts/Amps	NA	
Air Conditioning	1	
Air Conditioning		
Movimum Coaliza Cara attain	1	
Maximum Cooling Capacity in		96,000 BTU/hr
BTU's		
Maximum Heat Output		
Capacity in BTU's		2 stage heat 92,000 BTU/hr electric heat. 80,000 BTU/hr fuel fired A
Refrigerant Type	1	
Reingerant Type	D 407 0	
	R407-C	
CFM Air Flow		
	3,000 CFM	
Air Duct Diameter		
	4 Ducts	Two 14 in Supply Two 14 in Return
Power Requirements in kW, VAC, HZ,		
Phase		
	28kW	208 VAC, 60 Hz, 3-phase.
		200 VAC, 00 HZ, 3-phase.
Special/Additional Factures:		
Special/Additional Features:	The HP-20	/188 Trailer provides three primary features for the end user of a
		ASH shelter: cargo space, environmental control and electrical power.
	It has a 77	cubic foot cargo area, includes a 16-gallon fuel tank and comes with
		enset and an 8-ton ECU.
	INCLUDES:	
1	Drip Berm (P/N: T295188), qty. = 1	
	Trailer Electrical Set (P/N: T2-95220), qty. = 1	
		n Package (P/N: TR20IS), qty. = 1
	Auxiliary Fuel Kit (P/N: TG430-6001-PH), qty. = 1	
	Air Supply Duct (P/N: T291230), qty. = 2	
	Air Return Duct (P/N: T291432), qty. = 2	
	Fire Extingu	uisher, 5lbs, (P/N T295175), Qty. = 1
	l ű	· · · ·

(

(

(