



# APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

<b>PRODUCT DATA SHEET</b>		<b>CONTRACTOR NAME: Johnson Outdoors Gear, Inc.</b>	
<b>1. PART NUMBER: 2480583</b>		<b>2. NSN: 0</b>	
<b>3. NAME:</b> RDS 720 Tan with Stove Pipe and Thermal Liner	<b>4. TYPE:</b> RDS (Rapid Deployable Tent System)	<b>5. CLASS:</b> Tent Complete	
<b>6. COLOR:</b> Tan	<b>7. SUPPORT SYSTEM:</b> Frame	<b>8. SERIES:</b> N/A	
<b>9. INTENDED USE:</b> Mission-ready in minutes for first responders, medical & surgical suites; Command Post, Operations Centers. Designed specifically for extreme hot or cold climates			
<b>10. DIMENSIONS (IN FEET AND INCHES)</b>	<b>LENGTH:</b> 29' 9"	<b>WIDTH:</b> 24' 6"	<b>HEIGHT:</b> RIDGE/EAVE 10' 4" / 8' 11"
<b>11. DIMENSIONS (EXTERNAL GUYED)</b>	<b>LENGTH:</b> 42'	<b>WIDTH:</b> 37'	
<b>12. SQUARE FEET</b> INTERIOR 675 ft2 ft <sup>2</sup>			
<b>13. WEIGHT (POUNDS, UNPACKAGED)</b> 907 lbs pounds		<b>14. WEIGHT (PACKAGED)</b> 1329 lbs pounds	<b>15. SHIPPING CUBE (PACKAGED)</b> 118.75
<b>16. SHIPPING CONTAINER</b>	<b>LENGTH</b> 96"	<b>WIDTH</b> 45"	<b>HEIGHT</b> 47.5"
<b>17. SET-UP TIME/ NUMBER OF PERSONS</b> <18 min./ 5 persons req.		<b>18. STRIKE TIME/ NUMBER OF PERSONS</b> <18 min./ 5 persons req.	
<b>19. SNOW LOAD:</b>  10 lbs/ft2  Design-yes Tested-yes		<b>20 WIND LOAD:</b>  55/65(gusts) mph  Design-yes Tested-yes	
<b>21. PARTS INCLUDED:</b> Three bay frame, with end walls in package #1(563 lbs). Floor, liner and plenum in package #2(351 lbs); and side walls in package #3(110 lbs). Along with repair kit and stake bag in package #4(35 lbs) (all packages wrapped seperately)			
<b>22. DESCRIPTION:</b> RDS (Rapid Deployable System) 720 tan with stove pipe and thermal liner			

<b>23. ACCESSORY AND SUPPORT EQUIPMENT</b>	<b>PART NUMBER Or NSN</b>	<b>Check If included</b>	<b>DESCRIPTION</b>
<b>LIGHT SET</b> Product Data Sheet			<b>BATLite 14 Light Kit</b> <b>Blue PN 2480478    NSN 6210016642036</b> <b>Red PN 2480456    NSN 6210016642055</b>
<b>ELECTRICAL OUTLET SET</b> Product Data Sheet			N/A
<b>FLOORING</b> Product Data Sheet			<b>Bike Track Flooring</b> <b>1 inch            PN 2480483    NSN 5680015435495</b> <b>2 inch            PN 2480482    NSN 5680015538740</b> <b>2 Inch ICM    PN 2480481    NSN 5680015538745</b>
<b>HEATER</b> Product Data Sheet			N/A
<b>AIR CONDITIONER</b> Product Data Sheet			N/A
<b>GENERATOR</b> Product Data Sheet			N/A
<b>POWER DISTRIBUTION</b> Product Data Sheet			N/A
<b>TRAILER MOUNTED SUPPORT</b> Product Data Sheet			N/A
<b>INSULATED LINER</b> Product Data Sheet		included	<b>RTEQ-6 thermal liner</b> <b>(Operational temperature range of -40°F to 120°F)</b> <b>Data Sheet follows</b>
<b>INSULATED FLOORING</b> Product Data Sheet			N/A
<b>SOLAR SHADE/ CAMOU. NET</b> Product Data Sheet			N/A

# Eureka!

## RTEQ™ THERMAL LINER

Another Tactical Innovation from Eureka!



### *Save Time, Save Energy, Reduce Fuel Consumption*

*The Rteq-6 Thermal Liner employs a double layer of the material, where energy loss and solar load are at their highest. This double layer also has the benefit of an optimally-sized air gap, which enhances thermal efficiency even further. These liner enhancements require no additional materials or installation requirements.*

★ **ALWAYS READY** ★