

APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

| PRODUCT DATA | SHEET | CONTRA UTS System | | NAME | : | | | |
|---|-------------------------|---------------------------|---|----------|--------------|-----------------------------------|------------------------------|-------------------|
| 1.PART NUMBER: UTM36B1- | OD | | <u> </u> | 2.NS | 1 | | | |
| 3.NAME: 4.TYPE: | | | Soft Shelter N/A | | | | | |
| | | | t Exterior Folding Frame 8.SERIES: TM Series | | | | | |
| 9. INTENDED USE: | amp | | | | | | | |
| 10.DIMENSIONS (IN FEET AND INCHES) | LENGTH: Feet 19' | | WIDTH F 20'3" | eet | Inches | HEIGHT Feet RIDGE: EAVE: | Inches 9' / 6'9.6" | |
| 11.DIMENSIONS (EXTERNAL GUYED) | LENGTH Feet 31'6" | | WIDTH F 24'6" | eet | Inches | | | |
| 12.SQUARE FEET INTERIOR: | | | 388 Sq | Ft | | | | |
| 13.WEIGHT (POUNDS, UNPACKAGED) LBS. 563 lbs | | | 14.WEIGHT (PACKAGED) _{660 lbs} LBS | | | 15.SHIPPING C (PACKAGED) 48 | UBE | CU. |
| 16. SHIPPING CONTAINER | LENGTH 96" | | WIDTH 47" | | Inches | HEIGHT 36" | | Inches |
| 17.SET-UP TIME/ NUMBER OF PERSON TIME UNDER CANOP | 5-7 Min | | 18.STRII NUMBEI | | e/ Ersons | | 3 People 5-7 Mins | People Minutes |
| 19.SNOW LOAD: | | Design Tested | 20.Wind | Load: | | | | Design Tested |
| 21.PARTS INCLUDED Liner, Fabric Floor, The | • | • · | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 22.DESCRIPTION: | | | | | | | | |
| UTS TM36 Std, 4-Door | r w/ Liner, Fal | bric Floor, Th | ermal Fly | / & Stał | ke Bag - OE |) Green | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| - | RT NUMBEF NSN | R Check if Includec | | ESCRI | PTION | | | |

| LIGHT SET Product Data | |
|---------------------------------------|--|
| Sheet | |
| | |
| | |
| | |
| OUTLET SET Product Data | |
| Sheet | |
| | |
| | |
| FLOORING | |
| Product Data Sheet | |
| | |
| | |
| HEATER | |
| Product Data | |
| Sheet | |
| | |
| | |
| AIR CONDITIONER | |
| Product Data Sheet | |
| | |
| | |
| GENERATOR Product Data | |
| Sheet | |
| | |
| | |
| POWER DISTRIBUTION Product Data | |
| Sheet | |
| | |
| TRAILER MOUNTED | |
| SUPPORT | |
| SYSTEM Product Data Sheet | |

| INSULATED LINER Product Data Sheet | | |
|--|--|--|
| INSULATED FLOORING Product Data Sheet | | |
| SOLAR SHADE/ CAMOU. NETT Product Data Sheet | | |

- 1. PART NUMBER: List Manufacturers identification number.
- 2. NSN: List the National Stock Number if it had been established.
- 3. NAME: List Manufacturers product name.
- 4. TYPE: List Type of Tent or support equipment (example: Command Post,Modular, Expandable)
- 5. CLASS: List class if established.
- 6. COLOR: List Color or Shade reference FED-STD 595 color number if applicable.
- 7. SUPPORT SYSTEM: List type of support, state type examples: frame, pole, air beam
- 8. SERIES: List product line designation is applicable example: Series 50HH
- 9. INTENDED USE: List (examples: General Purpose, Command Post, Maintenance,

Kitchen, Billeting)

- 10. DIMENSIONS: External in feet and inches
- 11. DIMENSIONS: (EXTERNAL GUYDED): List the area for deployment needed including anchoring.
- 12. SQUARE FEET INTERIOR: List usable internal area.
- 13. WEIGHT (UNPACKAGED): List weight minus and packaging for the entire system.
- 14. Weight Shipping: List weight including allpackaging.
- 15. SHIPPING CUBE: List the Cubic measurement of the shipping container.
- 16. SHIPPING CONTAINER: Listmeasurements.
- 17. SET-UP TIME: List total time fully staked and list specific amount of people used for the setup. Time under Canopy is the minimum time operational equipment can be started to safely be moved into the shelter while the shelter is being set-up.

18. STRIKE TIME: List total time to take down and pack into storage bags and amount of people needed.

19. SNOW LOAD: List the actual maximum snow load the design can safely be operational in and the list the Snow Load as documented under a controlled laboratory test.

20. WIND LOAD: List the actual maximum snow load the design can safely be operational in and the list the Wind Load as documented under a controlled laboratory test.

21. PARTS INCLUDED: List all parts with NSN's if established (example: Type and ground anchoring support system quantity of stake or pin., Type of flooring., Type and quantity of transport/storage container bags., Includes electrical wiring/outlets with surge suppressors (must meet UL and NEC standards if supplied). Include quantities (example: Stakes, 12" steel 18 each) 22. DESCRIPTION:

State compatible with existing military fluorescent lighting system or includes lights in accordance with MIL-L-44259

Type and quantity of doorways and if closures and screens are part of the door assembly Are there optional accessories

Is it supported by a trailer system that provides controlled environments and electrical capabilities Can it provide interconnection capabilities/supported by TEMPER Vestibule connector interoperable

With vestibule accordance with drawing 5-4-9755-16

23. ACCESSORY AND SUPPORT EQUIPMENT:

List optional or included Support Equipment as applicable. A product data sheet for each part number or nsn is required to be submitted.