

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

## **SECTION C**

This document covers fruits, infused and dried for use by the Department of Defense as a component of operational rations.

### **C-1 ITEM DESCRIPTION**

#### **PACKAGING REQUIREMENTS AND QUALITY ASSURANCE PROVISIONS FOR CID A-A-20299B FRUITS, INFUSED AND DRIED**

Types, styles, flavors, varieties, fortifications, and classes.

Type VII- Cranberries

Style B - Sliced

Flavor 1 - Plain

Fortification a - Not fortified

Class (1) - No Sulfur dioxide (SO<sub>2</sub>)

Type IX- Whole Raisins

Variety A - Seedless

Fortification a - Not fortified

Class (1) No Sulfur dioxide (SO<sub>2</sub>)

Packages.

Package A - Meal, Cold Weather (MCW)

Package B - Food Packet, Long Range Patrol (LRP)

Package C - Meal, Ready-to-Eat™ (MRE™)

Package J - First Strike Ration® (FSR™)

Package L - Food Packet, Modular Operational Ration Enhancement™ (MORE™)

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

**C-2 PERFORMANCE REQUIREMENTS**

A. Product standard. A sample shall be subjected to first article (FA) or product demonstration model (PDM) inspection as applicable, in accordance with the tests and inspections of Section E of this Packaging Requirements and Quality Assurance Provisions document. The approved sample shall serve as the product standard. Should the contractor at any time plan to, or actually produce the product using different raw material or process methodologies from the approved product standard, which result in a product non comparable to the product standard, the contractor shall submit a replacement FA or PDM for approval. In any event, all product produced must meet all requirements of this document including product standard comparability.

B. Shelf life. The packaged product shall meet the minimum shelf life requirement of 36 months at 80°F.

C. Net weight. The net weight of one serving of Type VII product shall be 57 grams (2.0 ounces). The net weight of one serving of Type IX product shall be 43 grams (1.5 ounces).

D. Palatability and overall appearance. The finished product shall be equal to or better than the approved product standard in palatability and overall appearance.

E. Analytical requirements.

(1) Calorie content. The calorie content of one serving is as follows:

<u>Type</u>	<u>Calorie content not less than</u>
VII	150 calories
IX	120 calories

(2) Analytical and microbiological tests. The following identifies the analytical and microbiological tests to be performed on the dried fruit type(s) in accordance with the AOAC or test methods specified in A-A-20299B.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

Type	Water activity	Standard plate count	Yeast	Mold	<i>Coliform</i>	<i>E. coli</i>	<i>Staph. aureus</i>	Oil added
VII	X	X	X	X	X	X	X	X
IX	X	X	X	X	X	X	X	X

**SECTION D**

**D-1 PACKAGING**

A. Packaging. Fifty-seven grams (2.0 ounces) of Type VII cranberries shall be packed in a preformed or form-fill seal barrier pouch. Forty-three grams (1.5 ounces) of Type IX whole raisins shall be packed in a preformed or form-fill seal barrier pouch.

(1) Preformed pouches.

a. Pouch material. The preformed pouch shall be fabricated from 0.002 inch thick ionomer or polyethylene film laminated or extrusion coated to 0.00035 inch thick aluminum foil which is then laminated to 0.0005 inch thick polyester. Tolerances for thickness of plastic films shall be plus or minus 20 percent and tolerance for foil layer shall be plus or minus 10 percent. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product. The complete exterior surface of the pouch shall be uniformly colored in the range of 20219, 30219, 30227, 30279, 30313, 30324, or 30450 of FED-STD-595, Colors Used in Government Procurement.

b. Pouch construction. The pouch shall be a flat style preformed pouch having maximum inside dimensions of 5 inches wide by 7-1/4 inches long. The pouch shall be made by heat sealing three edges with 3/8 inch (-1/8 inch, +3/16 inch) wide seals. The side and bottom seals shall have an average seal strength of not less than 6 pounds per inch of width and no individual specimen shall have a seal strength of less than 5 pounds per inch of width. Alternatively, the pouch shall exhibit no rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch when tested for internal pressure resistance. A tear nick, notch or serrations shall be provided to facilitate

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

opening of the filled and sealed pouch. A 1/8 inch wide lip may be incorporated at the open end of the pouch.

c. Pouch filling and sealing. The product shall be inserted into the pouch. The filled pouch shall be sealed. The closure seal shall be free of foldover wrinkles or entrapped matter that reduces the effective closure seal width to less than 1/16 inch. Seals shall be free of impression or design on the seal surface that would conceal or impair visual detection of seal defects. The average seal strength shall be not less than 6 pounds per inch of width and no individual specimen shall have a seal strength of less than 5 pounds per inch of width. Alternatively, the filled and sealed pouch shall exhibit no rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch when tested for internal pressure resistance.

(2) Horizontal form-fill-seal pouches.

a. Pouch material. The horizontal form-fill-seal pouch shall consist of a formed tray-shaped body with a flat sheet, heat sealable cover or a tray-shaped body with a tray-shaped heat sealable cover. The tray-shaped body and the tray-shaped cover shall be fabricated from a 3-ply flexible laminate barrier material consisting of, from outside to inside, 0.0009 inch thick oriented polypropylene bonded to 0.0007 inch thick aluminum foil with 10 pounds per ream pigmented polyethylene or adhesive and bonding the opposite side of the aluminum foil to 0.003 inch thick ionomer or a blend of not less than 50 percent linear low density polyethylene and polyethylene. The linear low density polyethylene portion of the blend shall be the copolymer of ethylene and octene-1 having a melt index range of 0.8 to 1.2 g/10 minutes in accordance with ASTM D 1238, Standard Test Method for Melt Flow Rates of Thermoplastics by Extrusion Plastometer and a density range of 0.918 to 0.922 g/cc in accordance with ASTM D 1505, Standard Test Method for Density of Plastics by Density Gradient Technique. Alternatively, 0.0005 inch thick polyester may be used in place of the oriented polypropylene as the outer ply of the laminate. The flat sheet cover shall be made of the same 3-ply laminate as specified for the tray-shaped body except the aluminum foil thickness may be 0.00035 inch. Tolerances for thickness of plastic films shall be plus or minus 20 percent and tolerance for foil layer shall be plus or minus 10 percent. The color requirements of the exterior (oriented polypropylene or polyester side) of the laminate shall be as specified in D-1,A(1)a. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches. The material shall be suitably formulated for food packaging and shall not impart any odor or flavor to the product.

**PKG&QAP A-A-20299B**

**12 September 2011**

**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**

**SUPERSEDING**

**PKG&QAP A-A-20299A**

**27 November 2002**

b. Pouch construction. The tray-shaped body and the tray-shaped cover shall be formed by drawing the flexible laminate material into an appropriately shaped cavity. The flat cover shall be in the form of a flat sheet of the barrier material taken from roll stock. The product shall be placed into the tray-shaped body of the pouch. The filled pouch body shall be hermetically sealed. Pouch closure shall be effected by heat sealing together the cover and body along the entire pouch perimeter. The closure seal width shall be a minimum of 1/8 inch. The closure seal shall have an average seal strength of not less than 6 pounds per inch of width and no individual specimen shall have a seal strength of less than 5 pounds per inch of width. Alternatively, the filled and sealed pouch shall exhibit no rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch when tested for internal pressure resistance. The maximum outside dimensions of the sealed pouches shall be 5-1/2 inches wide by 8-5/8 inches long. A tear nick, notch or serrations shall be provided to facilitate opening of the filled and sealed pouch. The sealed pouches shall not show any evidence of material degradation, aluminum stress cracking, delamination or foreign odor. Heat seals shall be free of occluded matter. Seals shall be free of impression or design on the seal surface that would conceal or impair visual detection of seal defects.

## **D-2 LABELING**

A. Pouches. Each pouch shall be correctly and legibly labeled. Printing ink shall be permanent black ink or other dark contrasting color which is free of carcinogenic elements. The label shall contain the following information:

- (1) Name and flavor of product (letters not less than 1/8 inch high)
- (2) Ingredients
- (3) Date 1/
- (4) Net weight
- (5) Name and address of packer
- (6) "Nutrition Facts" label in accordance with the Nutrition Labeling and Education Act (NLEA) and all applicable FDA regulations

1/ Each pouch shall have the date of pack noted by using a four-digit code beginning with the final digit of the current year followed by the three digit Julian day code. For example, 14 February 2012 would be coded as 2045. The Julian day code shall represent the day the product was packaged into the pouch.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

### **D-3 PACKING**

A. Packing. Not more than 40 pounds of product shall be packed in a fiberboard shipping box constructed in accordance with style RSC-L of ASTM D 5118/D 5118M, Standard Practice for Fabrication of Fiberboard Shipping Boxes. The fiberboard shall conform to type CF, class D, variety SW, burst grade 200 or ECT grade 32 of ASTM D 4727/D 4727M, Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes. Each box shall be closed in accordance with ASTM D 1974, Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes.

### **D-5 MARKING**

A. Shipping containers. Shipping containers shall be marked in accordance with DLA Troop Support Form 3556, Marking Instructions for Boxes, Sacks, and Unit Loads of Perishable and Semiperishable Subsistence.

## **SECTION E INSPECTION AND ACCEPTANCE**

The following quality assurance criteria, utilizing ANSI/ASQ Z1.4, Sampling Procedures and Tables for Inspection by Attributes, are required. Unless otherwise specified, single sampling plans indicated in ANSI/ASQ Z1.4 will be utilized. When required, the manufacturer shall provide the Certificate(s) of Conformance to the appropriate inspection activity. Certificate(s) of Conformance not provided shall be cause for rejection of the lot.

### A. Definitions.

(1) Critical defect. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending on the item; or a defect that judgment and experience indicate is likely to prevent the performance of the major end item, i.e., the consumption of the ration.

(2) Major defect. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

(3) Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

B. Classification of inspections. The inspection requirements specified herein are classified as follows:

(1) Product standard inspection. The first article or product demonstration model shall be inspected in accordance with the provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the performance requirements or any appearance or palatability failure, shall be cause for rejection of the lot. The approved first article or product demonstration model shall be used as the product standard for periodic review evaluations. All food components that are inspected by the USDA shall be subject to periodic review sampling and evaluation. The USDA shall select sample units during production of contracts and submit them to the following address for evaluation:

US Army Research, Development and Engineering Command  
Natick Soldier Research, Development and Engineering Center  
RDNS-CFF  
15 Kansas Street  
Natick, MA 01760-5056

One lot shall be randomly selected during each calendar month of production. Six (6) sample units of each item produced shall be randomly selected from that one production lot. The six (6) sample units shall be shipped to Natick within five working days upon completion of all USDA inspection requirements. The sample units will be evaluated for the characteristics of appearance, odor, flavor, texture and overall quality.

(2) Conformance inspection. Conformance inspection shall include the product examination and the methods of inspection cited in this section.

#### **E-5 QUALITY ASSURANCE PROVISIONS (PRODUCT)**

A. Product examination. The finished product shall be examined for compliance with the performance requirements in A-A-20299B and specified in Section C of the Packaging Requirements and Quality Assurance Provisions document utilizing the double sampling plans indicated in ANSI/ASQ Z1.4. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5 for major defects and 4.0 for minor defects. Defects and defect classifications are listed in table I.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

TABLE I. Product defects 1/ 2/ 3/ 4/

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>General</u>
101		Product not type or not style or not flavor or not variety or not fortification or not class as specified.
102		Dried cranberries not a red to dark red color.
		<u>Appearance</u>
	201	Dried cranberries not small slices. <del>4/</del> <u>5/</u>
103		Raisins not a medium brown color.
	202	Raisins not intact pieces.
		<u>Odor and flavor</u>
104		Odor or flavor not characteristic of the applicable type, style, flavor, variety, fortification or class as specified.
		<u>Texture</u>
105		Dried cranberries not soft or not chewy.
106		Raisins not soft or not chewy.
		<u>Net weight</u>
	203	Net weight of an individual pouch not as specified.

1/ Presence of any foreign materials such as, but not limited to dirt, insect parts, hair, glass, wood, or metal, or any foreign odors or flavors such as, but not limited to burnt, scorched, rancid, sour, stale, musty or moldy shall be cause for rejection of the lot.



**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

2/ Finished product not equal to or better than the approved product standard in palatability and overall appearance shall be cause for rejection of the lot.

3/ Grade requirements for the fruit shall be verified by Certificate of Conformance (CoC).

4/ The producer shall provide a CoC from the supplier for each incoming lot indicating that the fruit supplied and used meet all the requirements for the latest season's crop at the time of issue. The CoC shall be dated, state the harvest period for the lot(s) (for example – Harvested during October 2020 through January 2021 crop season), and identify the lot(s) covered by the CoC. Any nonconformance to this requirement shall be cause for rejection of any component lot(s) or any involved product.

~~4/~~ 5/ Visually examine the sample for comparability to approved product standard. Small slices that are significantly less than an apparent portion of a whole cranberry (look like “bits”) are not acceptable.

B. Methods of inspection.

(1) Shelf life. The contractor shall provide a Certificate of Conformance that the product has a 36 month shelf life when stored at 80°F. Government verification may include storage for 6 months at 100°F or 36 months at 80°F. Upon completion of either storage period, the product will be subjected to a sensory evaluation panel for appearance and palatability and must receive an overall score of 5 or higher based on a 9 point hedonic scale to be considered acceptable.

(2) Net weight examination. The net weight of the filled and sealed pouches shall be determined by weighing each sample on a suitable scale tared with a representative empty pouch. Results shall be reported to the nearest 1 gram or to the 0.1 ounce.

(3) Calorie content. The calorie content shall be verified by the NLEA “Nutrition Facts” label. Product not conforming to the calorie content as specified in Section C of this document shall be cause for rejection of the lot.

(4) Analytical and microbiological tests. The following conditions apply for analytical and microbiological testing:

- a. For prepackaged product received from a supplier that is not further

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

processed, the contractor will furnish a Certificate of Analysis (CoA) providing test results showing that the product meets all analytical and microbiological requirements. No additional testing is required.

b. For bulk product received that is to be repackaged, the contractor will furnish a Certificate of Analysis (CoA) providing test results showing that the bulk product received meets all analytical and microbiological requirements. Water activity testing is required for each end item lot. For standard plate count, yeast, mold, *coliform*, *E. coli*, *Staph. aureus*, and oil added testing, if the bulk and end item lot identities have been preserved, then skip lot testing may be implemented once an acceptable quality history, as determined by the contracting officer, has been established.

c. If the dried fruits are received in bulk and the conditions in (b) above are not met, each end item lot must be sampled and tested by the USDA and skip lot is not applicable.

**E-6 QUALITY ASSURANCE PROVISIONS (PACKAGING AND PACKING MATERIALS)**

A. Packaging.

(1) Pouch material certification. The pouch material shall be tested for these characteristics. A Certificate of Conformance (CoC) may be accepted as evidence that the characteristics conform to the specified requirements.

<u>Characteristic</u>	<u>Requirement paragraph</u>	<u>Test procedure</u>
Thickness of films for laminated material	D-1,A(1)a and D-1,A(2)a	ASTM D 2103 <u>1/</u>
Aluminum foil thickness	D-1,A(1)a and D-1,A(2)a	ASTM B 479 <u>2/</u>
Laminated material identification and construction	D-1,A(1)a and D-1,A(2)a	Laboratory evaluation
Color of laminated material	D-1,A(1)a and D-1,A(2)a	FED-STD-595 <u>3/</u>

1/ ASTM D 2103 Standard Specification for Polyethylene Film and Sheeting

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

2/ ASTM B 479 Standard Specification for Annealed Aluminum and Aluminum-Alloy Foil for Flexible Barrier, Food Contact, and Other Applications

3/ FED-STD-595 Colors Used in Government Procurement

(2) Unfilled preformed pouch certification. A CoC may be accepted as evidence that unfilled pouches conform to the requirements specified in D-1,A(1) a and b. When deemed necessary by the USDA, testing of the unfilled preformed pouches for seal strength shall be as specified in E-6,B(1)a.

(3) Filled and sealed pouch examination. The filled and sealed pouches shall be examined for the defects listed in table II. The lot size shall be expressed in pouches. The sample unit shall be one pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

TABLE II. Filled and sealed pouch defects 1/

Category		Defect
<u>Major</u>	<u>Minor</u>	
101		Tear or hole or open seal.
102		Seal width less than 1/16 inch. <u>2/</u>
103		Presence of delamination. <u>3/</u>
104		Unclean pouch. <u>4/</u>
105		Pouch has foreign odor.
106		Any impression or design on the heat seal surfaces which conceals or impairs visual detection of seal defects. <u>5/</u>
107		Not packaged as specified.
108		Presence of stress cracks in the aluminum foil. <u>6/ 7/</u>
	201	Label missing or incorrect or illegible.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

- |     |   |
|-----|---|
| 202 | Tear nick or notch or serrations missing or does not facilitate opening.        |
| 203 | Seal width less than 1/8 inch but greater than or equal to 1/16 inch. <u>2/</u> |
| 204 | Presence of delamination. <u>3/</u>   |
- 

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

2/ The effective closure seal is defined as any uncontaminated, fusion bonded, continuous path, minimum 1/16 inch wide, from side seal to side seal that produces a hermetically sealed pouch.

3/ Delamination defect classification:

Major - Delamination of the outer ply in the pouch seal area that can be propagated to expose aluminum foil at the food product edge of the pouch after manual flexing of the delaminated area. To flex, the delaminated area shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delaminated area shall then be rapidly flexed 10 times by rotating both hands in alternating clockwise- counterclockwise directions. Care shall be exercised when flexing delaminated areas near the tear notches to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between thumb and forefinger and gently lifted toward the food product edge of the seal or if the separated area is too small to be held between thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to the product edge of the seal with no discernible resistance to the gentle lifting, the delamination shall be classified as a major defect. Additionally, spot delamination of the outer ply in the body of the pouch that is able to be propagated beyond its initial borders is also a major defect. To determine if the laminated area is a defect, use the following procedure: Mark the outside edges of the delaminated area using a bold permanent marking pen. Open the pouch and remove the contents. Cut the pouch transversely not closer than 1/4 inch ( $\pm 1/16$  inch) from the delaminated area. The pouch shall be flexed in the area in question using the procedure described above. Any propagation of the delaminated area, as evidenced by the delaminated area exceeding the limits of the outlined borders, shall be classified as a major defect.

**PKG&QAP A-A-20299B**

**12 September 2011**

**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**

**SUPERSEDING**

**PKG&QAP A-A-20299A**

**27 November 2002**

Minor - Minor delamination of the outer ply in the pouch seal area is acceptable and shall not be classified as a minor defect unless it extends to within 1/16 inch of the food product edge of the seal. All other minor outer ply delamination in the pouch seal area or isolated spots of delamination in the body of the pouch that do not propagate when flexed as described above shall be classified as minor defects.

4/ Outer packaging shall be free from foreign matter which is unwholesome, has the potential to cause pouch damage (for example, glass, metal filings) or generally detracts from the clean appearance of the pouch. The following examples shall not be classified as defects for unclean:

a. Foreign matter which presents no health hazard or potential pouch damage and which can be readily removed by gently shaking the package or by gently brushing the pouch with a clean dry cloth.

b. Dried product which affects less than 1/8 of the total surface area of one pouch face (localized and aggregate).

5/ If doubt exists as to whether or not the sealing equipment leaves an impression or design on the closure seal surface that could conceal or impair visual detection of seal defects, samples shall be furnished to the contracting officer for a determination as to acceptability.

6/ Applicable to form-fill-seal pouches only.

7/ The initial examination shall be a visual examination of the closed package. Any suspected visual evidence of stress cracks in the aluminum foil (streaks, breaks, or other disruptions in the laminated film) shall be verified by the following physical examination. To examine for stress cracks, the inside surface of both tray-shaped bodies shall be placed over a light source and the outside surface observed for the passage of light. Observation of light through the pouch material in the form of a curved or straight line greater than 2 mm in length shall be evidence of the presence of stress cracks. Observation of light through the pouch material in the form of a curved or straight line 2 mm in length or smaller or of a single pinpoint shall be considered a pinhole. Observation of ten or more pinholes per pouch shall be evidence of material degradation.

B. Methods of inspection.

**PKG&QAP A-A-20299B**

**12 September 2011**

**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**

**SUPERSEDING**

**PKG&QAP A-A-20299A**

**27 November 2002**

(1) Seal testing. The pouch seals shall be tested for seal strength as required in a, b, or c, as applicable.

a. Unfilled preformed pouch seal testing. The seals of the unfilled preformed pouch shall be tested for seal strength in accordance with ASTM F 88, Standard Test Method for Seal Strength of Flexible Barrier Materials. The lot size shall be expressed in pouches. The sample unit shall be one pouch. The sample size shall be the number of pouches indicated by inspection level S-1. Three adjacent specimens shall be cut from each of the three sealed sides of each pouch in the sample. The average seal strength of any side shall be calculated by averaging the three specimens cut from that side. Any average seal strength of less than 6 pounds per inch of width or any test specimen with a seal strength of less than 5 pounds per inch of width shall be classified as a major defect and shall be cause for rejection of the lot.

b. Pouch closure seal testing. The closure seals of the pouches shall be tested for seal strength in accordance with ASTM F 88. The lot size shall be expressed in pouches. The sample unit shall be one pouch. The sample size shall be the number of pouches indicated by inspection level S-1. For the closure seal on preformed pouches, three adjacent specimens shall be cut from the closure seal of each pouch in the sample. For the form-fill-seal pouches, three adjacent specimens shall be cut from each side and each end of each pouch in the sample. The average seal strength of any side, end or closure shall be calculated by averaging the three specimens cut from that side, end or closure. Any average seal strength of less than 6 pounds per inch of width or any test specimen with a seal strength of less than 5 pounds per inch of width shall be classified as a major defect and shall be cause for rejection of the lot.

c. Internal pressure test. The internal pressure resistance shall be determined by pressurizing the pouches while they are restrained between two rigid plates. The lot size shall be expressed in pouches. The sample unit shall be one pouch. The sample size shall be the number of pouches indicated by inspection level S-1. If a three seal tester (one that pressurizes the pouch through an open end) is used, the closure seal shall be cut off for testing the side and bottom seals of the pouch. For testing the closure seal, the bottom seal shall be cut off. The pouches shall be emptied prior to testing. If a four-seal tester (designed to pressurize filled pouches by use of a hypodermic needle through the pouch wall) is used, all four seals can be tested simultaneously. The distance between rigid restraining plates on the four-seal tester shall be equal to the thickness of the product +1/16 inch. Pressure shall be applied at the approximate uniform rate of 1 pound per square inch gage (psig) per second until 14 psig pressure is reached. The 14 psig pressure shall be held constant for 30 seconds and then released. The pouches shall then be examined for separation or yield of the heat seals. Any rupture of the pouch or evidence of seal separation greater than 1/16 inch in the

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

pouch manufacturer's seal shall be considered a test failure. Any seal separation that reduces the effective closure seal width to less than 1/16 inch (see table II, footnote 2/) shall be considered a test failure. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

C. Packing.

(1) Shipping container and marking examination. The filled and sealed shipping containers shall be examined for the defects listed in table III. The lot size shall be expressed in shipping containers. The sample unit shall be one shipping container fully packed. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total defects.

**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

TABLE III. Shipping container and marking defects

Category		Defect
<u>Major</u>	<u>Minor</u>	
101		Marking missing or incorrect or illegible.
102		Inadequate workmanship. <u>1/</u>
	201	More than 40 pounds of product.

1/ Inadequate workmanship is defined as, but not limited to, incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, or bulged or distorted container.

**SECTION J REFERENCE DOCUMENTS**

Unless otherwise specified, the issues of these documents are those active on the date of the solicitation or contract.

DLA Troop Support Forms

Form 3556                      Marking Instructions for Boxes, Sacks, and Unit Loads of  
Perishable and Semiperishable Subsistence

FEDERAL STANDARD

FED-STD-595      Colors Used in Government Procurement

U.S. STANDARDS FOR GRADES

U.S. Standards for Grades of Frozen Cranberries

U.S. Standards for Grades of Processed Raisins

NON-GOVERNMENTAL STANDARDS



**PKG&QAP A-A-20299B**  
**12 September 2011**  
**W/Change 01 28 Jun 21 ES21-029 (DSCP-SS-21-00535)**  
**SUPERSEDING**  
**PKG&QAP A-A-20299A**  
**27 November 2002**

AMERICAN SOCIETY FOR QUALITY (ASQ) [www.asq.org](http://www.asq.org)

ANSI/ASQ Z1.4                      Sampling Procedures and Tables for Inspection by  
Attributes

AOAC INTERNATIONAL [www.aoac.org](http://www.aoac.org)

Official Methods of Analysis (OMA) of AOAC International

ASTM INTERNATIONAL [www.astm.org](http://www.astm.org)

B 479                                  Standard Specification for Annealed Aluminum and  
Aluminum-Alloy Foil for Flexible Barrier, Food Contact,  
and Other Applications

D 1238                                Standard Test Method for Melt Flow Rates of  
Thermoplastics by Extrusion Plastometer

D 1505                                Standard Test Method for Density of Plastics by the Density-  
Gradient Technique

D 1974                                Standard Practice for Methods of Closing, Sealing, and  
Reinforcing Fiberboard Boxes

D 2103                                Standard Specification for Polyethylene Film and Sheeting

D 4727/D 4727M                    Standard Specification for Corrugated and Solid Fiberboard  
Sheet Stock (Container Grade) and Cut Shapes

D 5118/D 5118M                   Standard Practice for Fabrication of Fiberboard Shipping  
Boxes

F 88                                    Standard Test Method for Seal Strength of Flexible Barrier  
Materials