

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

SECTION C

This document covers shelf stable apple pieces in spiced sauce packaged in a flexible pouch for use by the Department of Defense as a component of operational rations.

C-1 ITEM DESCRIPTION

PCR-A-001C, APPLE PIECES IN SPICED SAUCE, PACKAGED IN A FLEXIBLE POUCH, SHELF STABLE

C-2 PERFORMANCE REQUIREMENTS

A. Product standard. A sample shall be subjected to first article (FA) or product demonstration model (PDM) inspection as applicable, in accordance with the tests and inspections of Section E of this Performance-based Contract Requirements (PCR) document. The approved sample shall serve as the product standard. Should the contractor at any time plan to or actually produce the product using different raw material or process methodologies from the approved product standard, which result in a product noncomparable to the product standard, the contractor shall submit a replacement FA or PDM for approval. In any event, all product produced must meet all requirements of this document including product standard comparability.

B. Commercial sterility. The packaged food shall be processed until commercially sterile.

C. Shelf life. The packaged product shall meet the minimum shelf life requirement of 36 months at 80°F.

D. Appearance.

(1) General. The finished product shall be cooked apple pieces in spiced sauce. ~~The finished product shall be free from core and seed material. The finished product shall be practically free of peel material.~~ The finished product shall be practically free from core, stem, seed, and peel material. The finished product shall be free from foreign materials.

(2) Apple pieces. A minimum of sixty-five percent by weight of the apple pieces shall be not less than 3/4 inch in length and 1/4 inch in thickness. The apple pieces shall have a cooked, medium golden yellow to light tan color.

PCR-A-001C

19 July 2017

W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)

SUPERSEDING

PCR-A-001B

24 July 2012

(3) Sauce. The sauce shall be glossy, translucent, light to medium golden color with visible specks of ground spices and shall be slightly to moderately thick.

E. Odor and flavor. The packaged food shall have a moderately sweet and slightly acidic odor and flavor of cooked apples with cinnamon and may have nutmeg. The packaged food shall be free from foreign odors and flavors.

F. Texture.

(1) Apple pieces. The apple pieces shall be slightly firm and tender.

(2) Sauce. The sauce shall be smooth and moderately thick.

G. Net weight. The average net weight shall be not less than 5.0 ounces (142 grams). The net weight of an individual pouch shall be not less than 4.5 ounces (128 grams).

H. Drained weight. The drained weight of apple pieces in an individual pouch shall be not less than 2.4 ounces (68 grams).

I. Palatability and overall appearance. The finished product shall be equal to or better than the approved product standard in palatability and overall appearance.

J. Analytical requirements.

(1) Trans fat. The *trans* fat content shall be not greater than 0 grams per serving.

(2) Moisture. The moisture content shall be not greater than 80.0 percent.

(3) pH. The pH shall be not less than 2.8 and not greater than 3.8.

SECTION D

D-1 PACKAGING

Product shall be filled into pouches and sealed in accordance with MIL-PRF-44073, Packaging of Food in Flexible Pouches, Type I, Style 1.

PCR-A-001C

19 July 2017

W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)

SUPERSEDING

PCR-A-001B

24 July 2012

D-2 LABELING

A. Pouches. Each pouch shall be correctly and legibly labeled. Printing ink shall be permanent black ink or any other contrasting color, which is free of carcinogenic elements. Prior to thermal processing of the pouches, the product name, lot number, filling equipment number and time stamp shall be applied. All other marking may be applied before or after thermal processing.

(1) Product name (not less than 1/8 inch high). Commonly used abbreviations may be used.

(2) Pouch code includes: 1/

Lot number

Filling equipment identification number

Company code

Retort identification number and Retort cook number (Optional)

Time stamp (hour and minute of filling/sealing operation)

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, 14 February 2018 would be coded as 8045). The Julian code shall represent the day the product was packaged into the pouch and processed. Following the four digit Julian code, the other required code information shall be printed in the sequence as listed above.

B. Paperboard sleeves.

(1) The sleeves shall be clearly printed on one of the panels with permanent black ink as follows: 1/ 2/

Product name (7/32 to 9/32 inch block letters)

Ingredients

Net weight

Name and address of packer

“Nutrition Facts” label in accordance with the Nutrition Labeling and Education Act (NLEA) and all applicable FDA regulations

PCR-A-001C

19 July 2017

W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)

SUPERSEDING

PCR-A-001B

24 July 2012

1/ With contracting officer approval, this information may be printed on the pouch or on a separate paperboard insert card in lieu of the paperboard sleeve.

2/ If printed on the sleeve, it shall be configured to fit alongside similar information for an accompanying pouched product. Identity of accompanying pouched product and approval of label design shall be obtained from the contracting officer.

(2) The product shall be formulated and labeled in accordance with all FDA labeling regulations and policies. The sleeves (or pouches, or insert cards, as applicable) shall be labeled with the following product name.

APPLE PIECES IN SPICED SAUCE

D-3 PACKING

A. Packing. Not more than 40 pounds of product shall be packed in a fiberboard shipping box constructed in accordance with style RSC of ASTM D5118/D5118M, Standard Practice for Fabrication of Fiberboard Shipping Boxes. The fiberboard shall conform to type CF, class D, variety SW, burst grade 200 or ECT grade 32 of ASTM D4727/D4727M, Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes. Each box shall be closed in accordance with ASTM D1974/D1974M, Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes.

D-5 MARKING

A. Shipping containers and unit loads. Shipping containers shall be marked in accordance with DLA Troop Support Form 3556, Marking Instructions for Boxes, Sacks, and Unit Loads of Perishable and Semiperishable Subsistence.

SECTION E INSPECTION AND ACCEPTANCE

The following quality assurance criteria, utilizing ANSI/ASQ Z1.4, Sampling Procedures and Tables for Inspection by Attributes, are required. Unless otherwise specified, single sampling plans indicated in ANSI/ASQ Z1.4 will be utilized. When required, the manufacturer shall provide the Certificate(s) of Conformance to the appropriate inspection activity. Certificate(s) of Conformance not provided shall be cause for rejection of the lot.

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

A. Definitions.

(1) Critical defect. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending on the item; or a defect that judgment and experience indicate is likely to prevent the performance of the major end item, i.e., the consumption of the ration.

(2) Major defect. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

(3) Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

B. Classification of inspections. The inspection requirements specified herein are classified as follows:

(1) Product standard inspection. The first article or product demonstration model shall be inspected in accordance with the provisions of this document and evaluated for appearance, odor, flavor, and texture. Any failure to conform to the performance requirements or any appearance or palatability failure shall be cause for rejection of the lot.

(2) Periodic review evaluation. The approved first article or product demonstration model shall be used as the product standard for periodic review evaluations. All food components that are inspected by the USDA shall be subject to periodic review sampling and evaluation. The USDA shall select sample units during production of contracts and submit them to the following address for evaluation:

DEPARTMENT OF THE ARMY
RDNS-SEC-EMR
NATICK SOLDIER SYSTEMS CENTER
10 GENERAL GREENE AVENUE
NATICK, MA 01760

One lot shall be randomly selected during each calendar month of production or as otherwise specified in the contract. Three (3) sample units shall be randomly selected from that one production lot. The three (3) sample units shall be shipped to Natick within five (5) working days from the end of the production month from which they are randomly selected and upon

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

completion of all USDA inspection requirements. The sample units will be evaluated for overall quality against the current first article or product demonstration model.

(3) Conformance inspection. Conformance inspection shall include the examinations/tests and methods of inspection cited in this section and in section 4 of MIL-PRF-44073.

E-5 QUALITY ASSURANCE PROVISIONS (PRODUCT)

A. Product examination. The finished product shall be examined for compliance with the performance requirements specified in Section C of this Performance-based Contract Requirements document utilizing the double sampling plans indicated in ANSI/ASQ Z1.4. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5 for major defects and 4.0 for minor defects. Defects and defect classifications are listed in table I. For drained weight inspection, a separate set of pouches shall be selected from the lot using the same sampling criteria as above. The pouches shall be immersed in not less than 140°F and not greater than 190°F water for 10 minutes prior to conducting the product examination and the drained weight inspection.

TABLE I. Product defects 1/ 2/ 3/

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>General</u>
101		Product not cooked apple pieces in spiced sauce.
102		Less than sixty-five percent by weight of the apple pieces are at least 3/4 inch in length and 1/4 inch in thickness.
	201	Product not free of core and seed material.
	201	Product not practically free of core or not stem or not seed or not peel material. 4/
	202	Product not practically free of peel material.

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

TABLE I. Product defects 1/ 2/ 3/ - Continued

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>Appearance</u>
	203 2	Apple pieces not a cooked, medium golden yellow to light tan color.
	204 3	Sauce not glossy or not translucent or not light to medium golden color or not with visible specks of ground spices.
	205 4	Sauce not slightly to moderately thick.
		<u>Odor and flavor</u>
103		Not a moderately sweet or not a slightly acidic odor or flavor of cooked apples with cinnamon.
		<u>Texture</u>
	206 5	Apple pieces not slightly firm or not tender.
	207 6	Sauce not smooth or not moderately thick.
		<u>Net weight</u>
	208 7	Net weight of an individual pouch less than 4.5 ounces (128 grams). <u>4/</u> <u>5/</u>
	209 8	Drained weight of apple pieces in an individual pouch less than 2.4 ounces (68 grams).

1/ Presence of any foreign materials such as, but not limited to dirt, insect parts, hair, glass, wood, or metal, or any foreign odors or flavors such as, but not limited to burnt, scorched, rancid, sour, stale, musty or moldy shall be cause for rejection of the lot.

2/ Finished product not equal to or better than the approved product standard in palatability and overall appearance shall be cause for rejection of the lot.

PCR-A-001C

19 July 2017

W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)

SUPERSEDING

PCR-A-001B

24 July 2012

3/ The *trans* fat content shall be verified by the NLEA “Nutrition Facts” label. Product not conforming to the *trans* fat content as specified in Section C of this document shall be cause for rejection of the lot.

4/ Evidence of core, stem, and peel material in the finished product shall be verified by visual exam, and if present shall be less than 5 percent by weight of the drained weight of the apple pieces. For seeds only, practically free is defined as one or fewer seeds per pouch. Any result not conforming to the requirement shall be cause for rejection of the lot.

45/ Sample average net weight less than 5.0 ounces (142 grams) shall be cause for rejection of the lot.

B. Methods of inspection.

(1) Commercial sterility. Commercial sterility shall be verified in accordance with FDA regulations.

(2) Shelf life. The contractor shall provide a Certificate of Conformance that the product has a 36 month shelf life when stored at 80°F. Government verification may include storage for 6 months at 100°F or 36 months at 80°F. Upon completion of either storage period, the product will be subjected to a sensory evaluation panel for appearance and palatability and must receive an overall score of 5 or higher based on a 9 point quality scale to be considered acceptable.

(3) Net weight. The net weight of the filled and sealed pouches shall be determined by weighing each sample on a suitable scale tared with a representative empty pouch. Results shall be reported to the nearest 0.1 ounce or to the nearest 1 gram.

(4) Drained weight. Weigh a U.S. Standard 1/4 inch sieve to obtain the sieve tare weight. The pouch contents shall be poured into a flat-bottom container. A minimum of three times the volume of the pouch of not less than 140°F and not greater than 190°F water shall be added to the container so as to cover the contents. The contents and water shall be gently agitated so as to remove the sauce without breaking the apple pieces. The contents shall then be poured into a U.S. Standard 1/4 inch sieve in a manner that will distribute the product over the sieve without breaking the apple pieces. The sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at such an angle to assure complete drainage of liquid from the product. Drain product for two minutes before determining the drained weight by subtracting the sieve tare weight from the

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

gross weight. The drained weights shall be reported to the nearest 0.1 ounce or to the nearest 1 gram.

(5) Analytical. The sample to be analyzed shall be a composite of eight filled and sealed pouches which have been selected at random from the lot. The composite sample shall be prepared and analyzed in accordance with the following Official Methods of Analysis (OMA) of AOAC International:

<u>Test</u>	<u>Method Number</u>
Moisture	934.06
pH	981.12

Test results shall be reported to the nearest 0.1 percent. Government verification will be conducted through actual testing by a Government laboratory. Any result not conforming to the analytical requirements shall be cause for rejection of the lot.

E-6 QUALITY ASSURANCE PROVISIONS (PACKAGING AND PACKING MATERIALS)

A. Packaging.

(1) Pouch material testing. The pouch material shall be examined for the characteristics listed in table I of MIL-PRF-44073 for Type I. The lot size, sample unit, and inspection level criteria for each of the test characteristics are listed below. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

Characteristic	Lot size expressed in	Sample unit	Inspection level
Oxygen transmission rate	yards	1/2 yard	S-1
Water vapor transmission rate	yards	1/2 yard	S-1
Camouflage	yards	1/2 yard	S-1
Thermal processing	pouches	1 pouch	S-2
Low temperature	pouches	1 pouch	S-2
High temperature	pouches	1 pouch	S-2
Directional tear	pouches	1 pouch	S-3

(2) Filled and sealed pouch testing. The filled and sealed commercially sterile pouches shall be examined for the characteristics listed in table I of MIL-PRF-44073 for Type I. The lot size, sample unit, and inspection level criteria for each of the test

PCR-A-001C

19 July 2017

W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)

SUPERSEDING

PCR-A-001B

24 July 2012

characteristics are listed below. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

Characteristic	Lot size expressed in	Sample unit	Inspection level
Residual gas volume	pouches	1 pouch	S-2
Internal pressure	pouches	1 pouch	S-2 <u>1/</u>

1/ When a three-seal tester is used, a separate set of samples is required for testing of the closure seal.

(3) Pouch examination. The pouches shall be examined for the defects listed in table II of MIL-PRF-44073 for Type I. The lot size shall be expressed in pouches. The sample unit shall be one thermal processed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major A defects, 2.5 for major B defects, and 4.0 for minor defects. Two hundred sample units shall be examined for critical defects. The finding of any critical defect shall be cause for rejection of the lot.

(4) Sleeve examination 1/. The sleeves shall be examined for the defects listed in table III of MIL-PRF-44073 for Type I. The lot size shall be expressed in units of sleeves. The sample unit shall be one sleeve. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

1/ Or separate paperboard insert card when used in lieu of the paperboard sleeve.

B. Packing.

(1) Shipping container and marking examination. The filled and sealed shipping containers shall be examined for the defects listed in table II. The lot size shall be expressed in shipping containers. The sample unit shall be one shipping container fully packed. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total defects.

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

TABLE II. Shipping container and marking defects

Category		Defect
<u>Major</u>	<u>Minor</u>	
101		Marking missing or incorrect or illegible.
102		Inadequate workmanship. <u>1/</u>
	201	More than 40 pounds of product.

1/ Inadequate workmanship is defined as, but not limited to, incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, or bulged or distorted container.

SECTION J REFERENCE DOCUMENTS

Unless otherwise specified, the applicable version of these documents is that which is active on the date of the solicitation or contract.

DLA Troop Support Form

Form 3556 Marking Instructions for Boxes, Sacks, and Unit Loads of
Perishable and Semiperishable Subsistence

MILITARY SPECIFICATIONS

MIL-PRF-44073 Packaging of Food in Flexible Pouches

NON-GOVERNMENTAL STANDARDS

AMERICAN SOCIETY FOR QUALITY (ASQ) www.asq.org

ANSI/ASQ Z1.4 Sampling Procedures and Tables for Inspection by Attributes

ASTM INTERNATIONAL www.astm.org

PCR-A-001C
19 July 2017
W/Change 01 3 Apr 25 ES25-020 (DSCP-SS-25-00367)
SUPERSEDING
PCR-A-001B
24 July 2012

D1974/D1974M	Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes
D2103	Standard Specification for Polyethylene Film and Sheeting
D4727/D4727M	Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes
D5118/D5118M	Standard Practice for Fabrication of Fiberboard Shipping Boxes

AOAC INTERNATIONAL www.aoac.org

Official Methods of Analysis (OMA) of AOAC International