

SECTION C

This document covers shelf stable spaghetti with meatballs in sauce packaged in polymeric trays for use by the Department of Defense as a component of operational rations.

C-1 ITEM DESCRIPTION

PCR-S-012A, SPAGHETTI WITH MEATBALLS IN SAUCE, PACKAGED IN A POLYMERIC TRAY, SHELF STABLE

C-2 PERFORMANCE REQUIREMENTS

A. Product standard. A sample shall be subjected to first article (FA) or product demonstration model (PDM) inspection as applicable, in accordance with the tests and inspections of Section E of this Performance-based Contract Requirements (PCR) document. The approved sample shall serve as the product standard. Should the contractor at any time plan to or actually produce the product using different raw material or process methodologies from the approved product standard, which result in a product noncomparable to the product standard, the contractor shall submit a replacement FA or PDM approval. In any event, all product produced must meet all requirements of this document including product standard comparability.

B. Commercial sterility. The packaged food shall be processed until commercially sterile.

C. Shelf life. The packaged product shall meet the minimum shelf life requirement of 36 months at 80°F.

D. Appearance.

(1) General. The finished product shall be spaghetti with meatballs in tomato sauce. Each individual polymeric tray shall contain not less than 36 intact meatballs. The finished product shall be free from foreign materials.

(2) Spaghetti. The cooked, enriched thin spaghetti shall be a solid cylindrical shape and shall be an off-white to light tan color. At least 50 percent of the cooked spaghetti shall be a minimum of 2.0 inches in length.

(3) Meatballs. The cooked meatballs shall be a uniform size and shape and shall not contain pork. The meatballs shall have a cooked ground beef color and may have a reddish color from the sauce. The cooked meatballs shall be practically free of bone or bone fragments, cartilage, coarse connective tissue, tendons or ligaments, and glandular material.

(4) Sauce. The sauce shall be an opaque medium red to dark red color with flecks of herbs and spices and small pieces of onion and tomato.

E. Odor and flavor. The packaged food shall have an odor and flavor of cooked beef meatballs, cooked spaghetti in an Italian seasoned tomato sauce with parmesan cheese. The packaged food shall be free from foreign odors and flavors.

F. Texture.

(1) Spaghetti. The cooked spaghetti shall be slightly soft to slightly firm. The spaghetti shall not be pasty.

(2) Meatballs. The cooked meatballs shall be moist and tender.

(3) Sauce. The sauce shall be moderately thick.

G. Net weight. The average net weight shall be not less than 93 ounces. No individual polymeric tray shall have a net weight of less than 91 ounces.

H. Drained weight of spaghetti. The average drained weight of spaghetti shall be not less than 46.0 ounces. The drained weight of spaghetti in an individual polymeric tray shall be not less than 40.0 ounces.

I. Drained weight of meatballs. The average drained weight of meatballs shall be not less than 24.0 ounces. The drained weight of 36 intact meatballs in an individual polymeric tray shall be not less than 22.0 ounces.

J. Palatability and overall appearance. The finished product shall be equal to or better than the approved product standard in palatability and overall appearance.

K. Analytical requirements.

(1) Fat. The fat content shall be not greater than 12.0 percent.

(2) Salt. The salt content shall be not less than 0.5 and not greater than 1.3 percent.

SECTION D

D-1 PACKAGING

A. Preservation. Product shall be filled into polymeric trays which shall conform to the requirements of section 3 of MIL-PRF-32004, Packaging of Food in Polymeric Trays, Type

I, Retortable products. Government verification testing and inspection of trays, lids, sleeves and fiberboard pads, as applicable, shall be in accordance with Section 4 of MIL-PRF-32004 and the Quality Assurance Provisions of Section E of this Performance-based Contract Requirements document.

D-2 LABELING

A. Polymeric tray body. The polymeric tray body shall be clearly printed or stamped, in a manner that does not damage the tray, with permanent ink of any contrasting color, which is free of carcinogenic elements. One end of the polymeric tray (see figure 1 of MIL-PRF-32004) shall be marked with the product name and number of portions. If the tray body end markings are not readily legible in low light conditions, a small, easily legible label shall be applied, but not over any existing tray markings. All other markings may be applied along the tray body side. The marking of trays with the product name, lot number and filling equipment number shall be applied prior to processing. Additional tray marking may be applied before or after processing. 1/

Tray body markings shall include:

(1) Product name. Commonly used abbreviations may be used.

(2) Tray code includes: 2/

Lot number
Filling equipment identification number
Retort identification number
Retort cook number
Official establishment number

1/ As an alternate method, tray body markings may be clearly printed or stamped onto the polymeric tray lid prior to processing, in a manner that does not damage the lid, with permanent ink of any contrasting color, which is free of carcinogenic elements, provided that the required markings are applied onto the tray body after processing.

2/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, 14 February 2030 would be coded as 0045). The Julian code shall represent the day the product was packaged into the tray and processed. Sublotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

B. Polymeric tray lid. The lid shall be clearly printed or stamped in a manner that does not cause damage. Permanent ink of any contrasting color, which is free of carcinogenic elements, shall be used. As an alternate labeling method, a pre-printed self-adhering 0.002 inch thick clear polyester label printed with indelible contrasting color ink may be used.

Note: The font tested by Natick was Microsoft Helvetica. The font used shall be similarly clear/easy to read as Helvetica. The recommended font sizes are as follows: 22 for the product name, 14 for “yield” and “to heat in water.” If an additional note is required on the label it should also be in font size 14. All other information should be in font size 9.

(1) Lid labeling shall include:

- Product name
- Ingredients
- Net weight
- Name and address of packer
- Official inspection legend
- “Nutrition Facts” label in accordance with the Nutrition Labeling and Education Act (NLEA) and all applicable USDA regulations.

(2) Lid labeling shall also show the following statements:

YIELD: Serves 9 portions of 4 meatballs each plus approximately 2/3 cup spaghetti.

TO HEAT IN WATER: Submerge unopened tray in water. Bring water to a boil. Simmer gently 35-40 minutes. Avoid overheating (tray shows evidence of bulging).

WARNING: Do not heat tray in oven.

TO TRANSPORT AFTER HEATING: Insert tray back into protective sleeve to protect during transport. If sleeve is unavailable, stack trays lid-to-lid with fiberboard pads in between.

CAUTION: Use care when opening as pressure may have been generated within the tray.

TO OPEN: Using a clean knife, cut the lidding around the inside perimeter of the tray seals.

SUGGESTION: Cut lid along 3 sides and fold over uncut portion. Fold back to keep unused portions protected.

(3) The product shall be formulated and labeled in accordance with all USDA labeling regulations and policies. The lid shall be labeled with the following product name:

SPAGHETTI WITH MEATBALLS IN SAUCE

D-3 PACKING

A. Packing. Four filled, sealed and processed polymeric trays shall be packed with sleeves or fiberboard pads in a fiberboard shipping container constructed in accordance with style RSC-L of ASTM D5118/D5118M, Standard Practice for Fabrication of Fiberboard Shipping Boxes. The fiberboard shall conform to type CF, class D, variety SW, minimum burst grade 275 or ECT 44 of ASTM D4727/D4727M, Standard Specification for Corrugated and Solid Fiberboard Sheet Stock (Container Grade) and Cut Shapes. Type I trays shall be placed flat with the first two trays placed with the lids together and the next two trays with the lids together. Each box shall be closed in accordance with ASTM D1974/D1974M, Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes.

D-4 UNITIZATION

A. Unit loads. Unit loads shall be as specified in accordance with DLA Troop Support Form 3507, Loads, Unit: Preparation of Semiperishable Subsistence Items.

D-5 MARKING

A. Shipping containers and unit loads. Shipping containers and unit loads shall be marked in accordance with DLA Troop Support Form 3556, Marking Instructions for Boxes, Sacks, and Unit Loads of Perishable and Semiperishable Subsistence.

SECTION E INSPECTION AND ACCEPTANCE

The following quality assurance criteria, utilizing ANSI/ASQ Z1.4, Sampling Procedures and Tables for Inspection by Attributes, are required. Unless otherwise specified, single sampling plans indicated in ANSI/ASQ Z1.4 will be utilized. When required, the manufacturer shall provide the Certificate(s) of Conformance to the appropriate inspection activity. Certificate(s) of Conformance not provided shall be cause for rejection of the lot.

A. Definitions.

(1) Critical defect. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending on the item; or a defect that judgment and experience indicate is likely to prevent the performance of the major end item, i.e., the consumption of the ration.

(2) Major defect. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

(3) Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

B. Classification of inspections. The inspection requirements specified herein are classified as follows:

(1) Product standard inspection. The first article or product demonstration model shall be inspected in accordance with the provisions of this document and evaluated for appearance, odor, flavor, and texture. Any failure to conform to the performance requirements or any appearance or palatability failure shall be cause for rejection of the lot.

(2) Periodic review evaluation. The approved first article or product demonstration model shall be used as the product standard for periodic review evaluations. All food components that are inspected by the USDA shall be subject to periodic review sampling and evaluation. The USDA shall select sample units during production of contracts and submit them to the following address for evaluation:

DEPARTMENT OF THE ARMY
FCDD-SCC-EMR
COMBAT CAPABILITIES DEVELOPMENT COMMAND-SOLDIER CENTER
10 GENERAL GREENE AVENUE
NATICK, MA 01760-5056

One lot shall be randomly selected during each calendar month of production or as otherwise specified in the contract. Two (2) sample units shall be randomly selected from that one production lot. The two (2) sample units shall be shipped to Natick within five (5) working days from the end of the production month from which they are randomly selected and upon completion of all USDA inspection requirements. The sample units will be evaluated for overall quality against the current first article or product demonstration model.

(3) Conformance inspection. Conformance inspection shall include the examinations/tests and methods of inspection cited in this section.

E-5 QUALITY ASSURANCE PROVISIONS (PRODUCT)

A. Product examination. The finished product shall be examined for compliance with the performance requirements specified in Section C of this Performance-based Contract

Requirements document utilizing the double sampling plans indicated in ANSI/ASQ Z1.4. The lot size shall be expressed in trays. The sample unit shall be the contents of one tray. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 6.5 for minor defects. Defects and defect classifications are listed in table I. The trays shall be heated in accordance with the heating instructions from the tray label prior to conducting any portion of the product examination. The samples for drained weight inspection shall be selected using the same sampling criteria as above.

TABLE I. Product defects 1/ 2/

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>Appearance</u>
101		Finished product not spaghetti or not with meatballs or not in tomato sauce. <u>3/ 4/ 5/</u>
102		Bone or bone fragment measuring more than 0.3 inch in any dimension.
	201	Cooked spaghetti not a solid cylindrical shape or not an off-white to light tan color. <u>6/</u>
	202	Cooked meatballs not a uniform size or not a uniform shape.
	203	Meatballs not a cooked ground beef color.
	204	Sauce not opaque or not a medium red to dark red color or not with flecks of herbs or spices or not with small pieces of onion or not tomato.
	205	Total weight of cartilage, coarse connective tissue, tendons or ligaments, and glandular material is more than 2.0 ounces.
		<u>Odor and flavor</u>
103		The packaged food does not have an odor or flavor of cooked beef meatballs or not cooked spaghetti or not in an Italian seasoned tomato sauce with parmesan cheese.

TABLE I. Product defects 1/ 2/ - Continued

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>Texture</u>
	206	Cooked spaghetti not slightly soft to slightly firm.
	207	Cooked spaghetti is pasty.
	208	Cooked meatballs not moist or not tender.
	209	Sauce not moderately thick.
		<u>Net weight</u>
	210	Net weight of an individual polymeric tray is less than 91 ounces. <u>7/</u>
		<u>Drained weight</u>
	211	Drained weight of spaghetti in an individual polymeric tray is less than 40.0 ounces. <u>8/</u>
	212	Drained weight of 36 intact meatballs in an individual polymeric tray less than 22.0 ounces. <u>9/</u>

1/ Presence of any foreign materials such as, but not limited to dirt, insect parts, hair, glass, wood, or metal, or any foreign odors or flavors such as, but not limited to burnt, scorched, rancid, sour, stale, musty or moldy shall be cause for rejection of the lot.

2/ Finished product not equal to or better than the approved product standard in palatability and overall appearance shall be cause for rejection of the lot.

3/ The finding of any individual polymeric tray containing less than 36 intact meatballs shall be cause for rejection of the lot. Not intact is defined as any meatball in an individual polymeric tray broken into three or more pieces.

4/ Verification of the pasta as enriched, thin spaghetti shall be with the statement of ingredients on the label or verified by the producer's Certificate of Conformance (CoC). Any nonconforming results shall be cause for rejection of the lot.

5/ The meatballs shall not contain pork and shall be verified by the ingredient statement on the product label. Product not conforming to the pork free requirement as specified in Section C-2, D(3) of this document shall be cause for rejection of the lot.

6/ At least 50 percent of the cooked spaghetti greater than 2 inches in length shall be verified by visual examination.

7/ Sample average net weight less than 93 ounces shall be cause for rejection of the lot.

8/ Sample average drained weight of spaghetti less than 46.0 ounces shall be cause for rejection of the lot.

9/ Sample average drained weight of meatballs less than 24.0 ounces shall be cause for rejection of the lot

B. Methods of inspection.

(1) Commercial sterility. Commercial sterility shall be verified in accordance with USDA/FSIS regulations.

(2) Shelf life. The contractor shall provide a Certificate of Conformance that the product has a 36 month shelf life when stored at 80°F. Government verification may include storage for 6 months at 100°F or 36 months at 80°F. Upon completion of either storage period, the product will be subjected to a sensory evaluation panel for appearance and palatability and must receive an overall score of 5 or higher based on a 9 point quality scale to be considered acceptable.

(3) Net weight. The net weight of the filled and sealed polymeric tray shall be determined by weighing each sample unit on a suitable scale tared with a representative empty tray and lid. Results shall be reported to the nearest 1 ounce or to the nearest 1 gram.

(4) Drained weight. Weigh a U.S. Standard No. 7 sieve to obtain the sieve tare weight. The polymeric tray contents shall be poured into a flat-bottom container. A minimum of three times the volume of the polymeric tray of not less than 140°F and not greater than 190°F water shall be added to the container so as to cover the contents. The contents and water shall be gently agitated so as to liquefy rendered fat without breaking the spaghetti or meatballs. The contents shall then be poured into a U.S. Standard No. 7 sieve in a manner that will distribute the product over the sieve without breaking the spaghetti or meatballs. The sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at such an angle to ensure complete drainage of liquid from the product. Drain product for two minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. Remove the 36 intact

meatballs from the sieve, reweigh the spaghetti and subtract this weight from the drained weight of the spaghetti and meatballs. The drained weight shall be reported to the nearest 0.5 ounce or to the nearest 1 gram.

(5) Analytical. The sample to be analyzed shall be a one-pound composite of three filled and sealed polymeric trays that have been selected at random from one production lot. The composite sample shall be prepared and analyzed in accordance with the following methods of the Official Methods of Analysis (OMA) of AOAC International:

<u>Test</u>	<u>Method Number</u>
Fat	991.36, 2007.04, 2008.06, or 925.12
Salt	935.47 or 971.27

Test results shall be reported to the nearest 0.1 percent. Government verification will be conducted through actual testing by a Government laboratory. Any result not conforming to the analytical requirement shall be cause for rejection of the lot.

E-6 QUALITY ASSURANCE PROVISIONS (PACKAGING AND PACKING MATERIALS, POLYMERIC TRAY)

A. Packaging and labeling.

(1) Polymeric tray testing. For purposes of clarification, the polymeric tray without the lid will be referred to as the “tray” and the polymeric tray with the lid shall be referred to as the “container”. The tray, container and packaging materials, as applicable, in accordance with the lot size, sample unit, and inspection level criteria shall be examined for the performance characteristics listed in table I of MIL-PRF-32004, Packaging of Food in Polymeric Trays. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

(2) Examination of container. The container shall be examined for the defects listed in table II of MIL-PRF-32004. The lot size shall be expressed in containers. The sample unit shall be one processed and labeled container. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major A defects, 2.5 for major B defects and 4.0 for minor defects. Two hundred sample units shall be examined for critical defects. The finding of any critical defect shall be cause for rejection of the lot. The labeling defects are listed in table II as follows:

TABLE II. Container labeling defects

Category		Defect
<u>Major A</u>	<u>Minor</u>	
101		Polymeric tray lid or body labeling missing or incorrect or illegible.
	201	When a pre-printed self-adhering label is used, the label not adhering to tray lid (for example, label raised or peeled back from edge to corner) or presence of any areas of gaps along the perimeter of the label where the label is not properly adhered.

(3) Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D3330/D3330M, Standard Test Method for Peel Adhesion of Pressure-Sensitive Tape. In lieu of testing, a CoC shall be provided.

B. Packing.

(1) Shipping container and marking examination. The filled and sealed shipping containers shall be examined for the defects listed in table III. The lot size shall be expressed in shipping containers. The sample unit shall be one shipping container fully packed. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total defects.

TABLE III. Shipping container and marking defects

Category		Defect
<u>Major</u>	<u>Minor</u>	
101		Marking missing or incorrect or illegible.
102		Inadequate workmanship. <u>1/</u>
	201	Arrangement or number of polymeric trays not as specified.

1/ Inadequate workmanship is defined as, but not limited to, incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, or bulged or distorted container.

C. Unitization.

(1) Unit load examination. The unit load shall be examined in accordance with DLA Troop Support Form 3507, Loads, Unit: Preparation of Semiperishable Subsistence Items. Any nonconformance shall be classified as a major defect.

SECTION J REFERENCE DOCUMENTS

DLA Troop Support Forms

Form 3507	Loads, Unit: Preparation of Semiperishable Subsistence Items
Form 3556	Marking Instructions for Boxes, Sacks, and Unit Loads of Perishable and Semiperishable Subsistence

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-32004 Packaging of Food in Polymeric Trays

(Copies of these documents are available from
<http://quicksearch.dla.mil/qsSearch.aspx> or from the Standardization Document Order Desk, 700 Robbins Ave, Building 4D, Philadelphia, PA 19111-5094.)

GOVERNMENT PUBLICATION

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199) and (9 CFR Parts 1-391)

NON-GOVERNMENTAL STANDARDS

AMERICAN SOCIETY FOR QUALITY (ASQ) www.asq.org

ANSI/ASQ Z1.4	Sampling Procedures and Tables for Inspection by Attributes
---------------	---

ASTM INTERNATIONAL www.astm.org

D1974/D1974M	Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes
D3330/D3330M	Standard Test Method for Peel Adhesion of Pressure-Sensitive Tape

PCR-S-012A
4 September 2020
SUPERSEDING
PCR-S-012
26 February 2003

D4727/D4727M Standard Specification for Corrugated and Solid
Fiberboard Sheet Stock (Container Grade) and Cut
Shapes

D5118/D5118M Standard Practice for Fabrication of Fiberboard
Shipping Boxes

AOAC INTERNATIONAL www.aoac.org

Official Methods of Analysis (OMA) of AOAC International